

Below, s71 cycle stands in stainless steel, root fixed.





s23 bollard

description

Brushed 316 grade stainless steel with radially polished cap.

dimensions

Diameter/wall thickness 101/1.5mm, 114/3mm, 168/3.4mm. Standard lengths 1000mm, 1200mm, 1500mm.

options

Root fixed, below ground flange fixed, above ground flange fixed. Ground socket box for removable option, pad lock type or hidden grub screw type.



s87 bollard

description

Painted galvanised steel with machined aluminium top.

dimensions

Diameter 89mm, wall thickness 3mm, height 1200/1500mm.

options

Root fixed, below ground flange fixed, above ground flange fixed. Ground socket box for removable option, pad lock type or hidden grub screw type. Choice of colours.



s26 bollard

description

Brushed 316 grade stainless steel with radially polished cap top section on painted galvanized steel lower section.

dimensions

Diameter/wall thickness 101/1.5mm, 114/3mm, 168/3.4mm. Standard lengths 1000mm, 1200mm, 1500mm.

options

Root fixed, below ground flange fixed, above ground flange fixed. Ground socket box for removable option, pad lock type or hidden grub screw type. Choice of colours.

s71 cycle stand

description

316 grade stainless steel or galvanized mild steel.

dimensions

Height 875mm, width 950mm, outside diameter 48mm, wall thickness 2.77mm.

options

Available as root fixed, below surface flange or above surface flange fixed.



s69 cycle stand

description

316 grade stainless steel or galvanized mild steel.

dimensions

Height 875mm, width 790mm, outside diameter 50mm, wall thickness 1.5mm.

options

Available as root fixed, below surface flange or above surface flange fixed.



s36 cycle stand

description

316 grade stainless steel or galvanized mild steel.

dimensions

Height 825mm, width 850mm, outside diameter 48mm, wall thickness 2.77mm.

options

Available as root fixed, below surface flange or above surface flange fixed.



