

SAFETY DATA SHEET

ANTI - CLIMB PAINT

Page 1 Issued: 05/10/2005 Revision No: 1

1. IDENTIFICATION OF THE SUBSTANCE / PREPARATION AND OF THE COMPANY / UNDERTAKING

Product name: ANTI - CLIMB PAINT

Company name: FLAG Paints Ltd

8 Springfield Road

Springfield Industrial Estate

Burnham on Crouch

Essex

CM0 8UA

United Kingdom

Emergency tel: +44 (0) 1621 785 173

2. HAZARDS IDENTIFICATION

Main hazards: Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous ingredients: LOW BOILING POINT HYDROGEN TREATED NAPHTHA - NAPHTHA (PETROLEUM),

HYDRODESULPHURIZED HEAVY 1-10%

EINECS: 265-185-4 CAS: 64742-82-1

[-] R10; [N] R51/53; [Xn] R65

4. FIRST AID MEASURES (SYMPTOMS)

Skin contact: There may be mild irritation at the site of contact. There may be redness or whiteness of the

skin in the area of exposure.

Eye contact: There may be irritation and redness.

Ingestion: There may be soreness and redness of the mouth and throat.

4. FIRST AID MEASURES (ACTION)

Skin contact: Wash immediately with plenty of soap and water. Remove all contaminated clothes and

footwear immediately unless stuck to skin.

Eye contact: Bathe the eye with running water for 15 minutes. Consult a doctor.

Ingestion: Do not induce vomiting. Wash out mouth with water.

5. FIRE-FIGHTING MEASURES

Extinguishing media: Dry chemical powder. Alcohol or polymer foam.

Exposure hazards: Flammable.

Protection of fire-fighters: Wear protective clothing to prevent contact with skin and eyes.

Issued: 05/10/2005

SAFETY DATA SHEET

ANTI - CLIMB PAINT

Page 2

6. ACCIDENTAL RELEASE MEASURES

Personal precautions: Refer to section 8 of SDS for personal protection details.

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding.

Clean-up procedures: Contain spillage with sand or earth, sweep up and dispose of in accordance with a recognised

method of waste disposal.

7. HANDLING AND STORAGE

Handling requirements: Ensure there is sufficient ventilation of the area. Do not handle in a confined space. Smoking is

forbidden.

Storage conditions: Store in cool, well ventilated area. Keep away from sources of ignition. Keep container tightly

closed.

Suitable packaging: Must only be kept in original packaging.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Workplace exposure limits

WEL (8 hr TWA): 100PPM WEL (15 min STEL): 125PPM

Engineering measures: Ensure there is sufficient ventilation of the area. **Respiratory protection:** Gas/vapour filter, type A: organic vapours (EN141).

Hand protection: Viton gloves. Nitrile gloves.

Eye protection: Safety goggles. **Skin protection:** Protective clothing.

9. PHYSICAL AND CHEMICAL PROPERTIES

State: Paste Colour: Black

Odour: Characteristic odour

Evaporation rate: Slow

Oxidising: Oxidising (by EC criteria)

Solubility in water: Insoluble

Viscosity: Viscous

Boiling point/range°C: 150-200

Flash point°C: 38

Autoflammability°C: 230

Vapour pressure: 2.4mmhg

Relative density: 1.10

pH: 7

Issued: 05/10/2005

SAFETY DATA SHEET

ANTI - CLIMB PAINT

Page 3

10. STABILITY AND REACTIVITY

Stability: Stable under normal conditions.

Conditions to avoid: Sources of ignition.

Materials to avoid: Oxidising agents.

11. TOXICOLOGICAL INFORMATION

Chronic toxicity: Non-toxic. Prolonged and repeated contact may cause slight irritation.

Routes of exposure: Refer to section 4 of SDS for routes of exposure and corresponding symptoms.

12. ECOLOGICAL INFORMATION

Mobility: Volatile. Floats on water.

Persistence and degradability: Biodegradable.

Bioaccumulative potential: No bioaccumulation potential.

13. DISPOSAL CONSIDERATIONS

Disposal operations: The relevant EC directives and local, regional and national regulations must be complied with.

Disposal of packaging: Dispose of as normal industrial waste.

NB: The user's attention is drawn to the possible existence of regional or national regulations

regarding disposal.

14. TRANSPORT INFORMATION

ADR / RID

UN no: 1263 ADR Class: 3

Packing group: III Classification code: F1

Shipping name: PAINT

Labelling: 3 Hazard ID no: 30



IMDG / IMO

UN no: 1263 Class: 3

Packing group: III EmS: F-E,S-E

Marine pollutant: .

Labelling: 3

IATA / ICAO

UN no: 1263 Class: 3

[cont...]

SAFETY DATA SHEET

ANTI - CLIMB PAINT

Page 4

Packing group: III

Packing instructions: 309(P&CA); 310(CAO)

Labelling: 3

15. REGULATORY INFORMATION

Hazard symbols: No significant hazard.

Risk phrases: R52/53: Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic

environment.

Safety phrases: S2: Keep out of the reach of children.

S3/9/14/49: Keep only in the original container in a cool, well ventilated place away from \dots

Note: The regulatory information given above only indicates the principal regulations specifically

applicable to the product described in the safety data sheet. The user's attention is drawn to the possible existence of additional provisions which complete these regulations. Refer to all

applicable national, international and local regulations or provisions.

16. OTHER INFORMATION

Risk phrases used in s.3: R10: Flammable.

R51/53: Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic

environment.

R65: Harmful: may cause lung damage if swallowed.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive and shall

be used only as a guide. This company shall not be held liable for any damage resulting from

handling or from contact with the above product.