world class | shrinkwrap

MES – SS Series with T Series Side Sealer with Heat Shrink Tunnel

For higher speed applications we offer a range of Automatic Side-Sealers, providing excellent performance and value for money. The complete system consists of a Fully-Automatic SS Sealing machine and Heat Shrink Tunnel with shrinkwrapping speeds of up to 60 packs per minute. An automatic conveyor feeds the product into the film, the machine then measures the length of the product to allow the sealing wheels to operate automatically to produce the sealed bag. The film, which is trimmed off during the packaging process, is automatically wound up on the waste film take-up reel. It is then automatically conveyed into the high capacity Heat Shrink Tunnel for excellent shrink results all around the package.





• Optional combinations of standard Seal Bar and moving head available.



• Film Dispenser sliding carriageway under the machine to save space.



• Small footprint, Heat Shrink Tunnel optional closed pitch rollers and viewing window.



SHRINKWRAPPING SOLUTIONS

technical data

	MES S30 series
Speed	60Packs Per Minute Maximum
	(Product and film dependant)
Sealing Dimension	60-800mm(l) x 40-230mm(w) x 5-150mm(h)
	(Product height dependant)
Film Type	Polyolefin Centre folded 8-35um
Maximum Film Reel Width	400mm
Safety	EN13849
Machine Dimensions	2885mm(l) x 1060mm(w) x 1320mm(h)
	(excludes Heat Tunnel)
Power Supply	250V 50Hz I 3amp Single Phase
Max Power Consumption	5.5KW
Working Pressure	6 Bar

Options Available

Closing Conveyor, Product Collating, Polyethylene Blades, Bespoke Safety Levels, Alternative PLC's, Low Film Warning, Line Integration, Stainless Steel, Opposite Handing

	MESMES SHAR Brinke Tunnel
Chample Supply Sion	350mm(w) x 28900m60Hzl200mm(l)
Machine Dimensions	900mm(w) x 1160mm(h) x 1700mm(l)
Power Supply	400V 50Hz 3 Phase + Neutral
	(Other Voltages Available)
Max Power Consumption	I4KW

Options Available

Close Pitch Rollers, Opposite Handing, Stainless Steel



SHRINKWRAPPING SOLUTIONS