



SOVEREIGN®

The signature range from Commercial Lighting Systems Ltd

High quality lighting solutions for 30+ years

Harnessing the quality and standards of British Manufacturing, we prioritise local suppliers for our materials, and design and build the majority of our products in-house at our Southampton factory.

As such, we have been proud members of the Made in Britain campaign since its foundation.

Sovereign is the signature range from **Commercial Lighting Systems Ltd**, a well respected British lighting manufacturer and distributor based in Southampton, Hampshire.



Clean Design

Sleek, minimalist design underpins this Sovereign catalogue. From simple geometric forms to carefully concealed fixings, Sovereign exudes a quiet modesty and elegance.

High Quality

Housed in robust materials such as extruded aluminium, glass and opalised acrylic, our luminaries use only components from well respected suppliers for best quality lighting and longevity.



Versatile

Many of our products are suitable for a wide range of interior applications, and can even be adjusted after installation such as with our colour changing wireless systems.













Our linear systems in particular provide incredible flexibility, offered in any length, angle and shape to suit just about any interior space.

Customisable



Commercial Lighting’s in-house design team, manufacturing facilities, and powder coating plant, allows countless possibilities for its Sovereign products.

This catalogue details only some of our most popular options of housing colour, CCT, wattage and lighting control etc. For variants not outlined, please get in touch.











PROJECTORS

	Round Minimal <i>Projector</i>	16
	Round Shallow <i>Projector</i>	18
	Round Vertical <i>Projector</i>	20
	SLM <i>Projector</i>	30
	Tubular <i>Spotlight</i>	34
	Zoom <i>Projector</i>	40
	Zoom+ <i>Projector</i>	42
	Framing <i>Projector</i>	46
	Gobo <i>Projector</i>	50
	Art <i>Spotlight</i>	54
	48V <i>Projector</i>	58
	Soloflood <i>Projector</i>	62










CEILING DOWNLIGHTS

	Maxi <i>Fixed Downlight</i>	70
	Midi <i>Fixed Downlight</i>	72
	Mini <i>Fixed Downlight</i>	74
	Mini Darklight <i>Fixed Downlight</i>	76
	Maxi <i>Gimbal Downlight</i>	82
	Maxi Twin <i>Gimbal Downlight</i>	84
	Midi <i>Gimbal Downlight</i>	86
	Scoop <i>Adjustable Downlight</i>	88
















PENDANTS

	Broadline <i>Suspended</i>	96
	Broadline IP65 <i>Suspended</i>	98
	Broadline Cylindrical <i>Suspended</i>	100
	Globe <i>Pendant</i>	104
	High Bay <i>Pendant</i>	108
	Round <i>Suspended</i>	112
	Ecoblade <i>Pendant</i>	116
	Opal Bowl <i>Pendant</i>	120
	Ring <i>Suspended</i>	124
	Shallow Drum <i>Suspended</i>	128





SURFACE & RECESSED

	Broadline <i>Surface</i>	134
	Broadline IP65 <i>Surface</i>	136
	Broadline <i>Recessed</i>	138
	Broadline IP65 <i>Recessed</i>	140
	Drum <i>Surface</i>	146
	Round <i>Surface</i>	150
	Round <i>Recessed</i>	152
	Shallow Drum <i>Surface</i>	156
	Universal Panel <i>Recessed</i>	160
















WALL LIGHTS

	Linear Mono <i>Wall Light</i>	168
	Linear Duo <i>Wall Light</i>	170
	Slim Uplight <i>Wall Light</i>	172
	Cube Up/down <i>Wall Light</i>	178
	Ecoblade Uplight <i>Wall Light</i>	182
	Ecoblade Up/down <i>Wall Light</i>	184
	Ecoblade Wedge <i>Wall Light</i>	186
	Slimline Square <i>Wall Light</i>	190
	Round <i>Wall Light</i>	194
	Pizza <i>Wall Light</i>	196
	Exterior Bulkhead <i>Wall Light</i>	200
	Saturn Up/down <i>Wall Light</i>	204
	Mini QS Uplight <i>Wall Light</i>	206
	Mini QS Up/down <i>Wall Light</i>	208
	Quarter Sphere <i>Wall Light</i>	210

FREE STANDING

	Ecoblade <i>Free Standing</i>	214
	Ecoblade Slot <i>Free Standing</i>	216
	Ecoblade Wedge <i>Free Standing</i>	218
	Saturn <i>Free Standing</i>	220

LINEAR SYSTEMS

	Broadline <i>Surface</i>	226
	Broadline IP65 <i>Surface</i>	228
	Broadline <i>Recessed</i>	230
	Broadline IP65 <i>Recessed</i>	232
	Broadline <i>Suspended</i>	234
	Broadline IP65 <i>Suspended</i>	236
	Broadline Cylindrical <i>Suspended</i>	238
	type A <i>Linear Systems</i>	244
	type B <i>Linear Systems</i>	250
	type C <i>Linear Systems</i>	254
	Nano Surface <i>Linear System</i>	258
	Narrow Trimless <i>Linear System</i>	259
	High Output Wide <i>Linear System</i>	260
	Linear Twist <i>Linear System</i>	261
	Tape Only <i>Linear Systems</i>	266



Interior
Projectors

the
**Round
 Projector**
ranges

Our most versatile family of projectors, perfectly suited for most interior settings. Our Round Projectors have been successfully installed in many retail, museum and heritage applications over the years, becoming one of the most iconic Sovereign ranges.





Extensively customisable as standard, the Sovereign Round Projectors are also perfectly suited to our Bespoke Design service, allowing for fundamental modifications such as wall-washer illumination.



Product Family		Beam		Mounting		Bezel Colour		CCT & Output		Suffix
S18368	Round Minimal	SP	Spot	/TR	Track adapter	/05	White	00	3000K 9.8W	.8
		FL	Flood	/CP	Ceiling Plate	/04	Black	02	4000K 9.8W	
		WFL	Wide Flood			/21	Silver	03	3000K 14.1W	
								04	4000K 14.1W	

Dimmable and control options available.
See page 268 for details.

Round Minimal

Track / Ceiling



LIGHT DETAILS

Wattage	CCT	Lumens	Efficacy
9.4W	3000K	1346lm	143lm/W
9.4W	4000K	1423lm	151lm/W
13.6W	3000K	1824lm	134lm/W
13.6W	4000K	1928lm	142lm/W

Our signature LED projector, the Sovereign Round Minimal Spotlight boasts a beautifully minimal design thanks to the driver being incorporated within the main lamp housing.


Designed around the latest Tridonic SLE LED modules with optical lenses to suit a range of applications. Can also accept any of our standard Electronic Spotlight accessories including colour filter lenses, honeycomb louvres, barn doors etc.

Available with dimming gear as an option with track adaptor or ceiling plate mounting. Standard colours black, white, and silver as standard with other BS/RAL colours to order.




PHOTOMETRY


Wide flood



Flood



Spot



TECHNICAL SPECIFICATIONS

IP rating	IP20
CRI	>80
Lamp Life	50,000 hours
Light Source	Tridonic SLE LED
Voltage	240V
Driver	Integrated high efficiency
LED Warranty	5 Years

HOUSING

Material	Extruded aluminium
Finish	Powder coated
Protection Rating	Class 1
Optics	Reflector
Weight	0.66kg
Mounting	Track / Surface mounting
Accessories	(see page 16)

Round Minimal



Projectors



Product Family		Beam		Mounting		Bezel Colour		CCT & Output			Suffix
S18310	Round Shallow	SP	Spot	/TR	Track adapter	/05	White	00	3000K	9.4W	.8
		FL	Flood	/CP	Ceiling Plate	/04	Black	02	4000K	9.4W	
		WFL	Wide Flood					03	3000K	13.6W	
								04	4000K	13.6W	
								06	3000K	15.8W	
						07	4000K	15.8W			

Dimmable and control options available.
See page 268 for details.

Round Shallow

Track / Ceiling



LIGHT DETAILS

Wattage	CCT	Lumens	Efficacy
9.4W	3000K	1346lm	143lm/W
9.4W	4000K	1423lm	151lm/W
13.6W	3000K	1824lm	134lm/W
13.6W	4000K	1928lm	142lm/W
15.8W	3000K	2059lm	131lm/W
15.8W	4000K	2176lm	138lm/W

Updated to the very latest Tridonic LES10 LED modules, this highly successful spotlight now offers even greater efficiency with enhanced performance and particularly low energy consumption.


This Round Shallow Spotlight uses high quality extruded aluminium profile with machined heatsink for optimum heat dissipation and longevity. Integral high performance LED driver is fitted as standard.

Available with 3-circuit track adaptor or ceiling plate. Also available with optional built in dimming control making it an ideal choice for museums, galleries etc.




PHOTOMETRY


Wide flood



Flood



Spot



TECHNICAL SPECIFICATIONS

IP rating	IP20
CRI	>80
Lamp Life	50,000 hours
Light Source	Tridonic SLE LED
Voltage	240V
Driver	250mA / 350mA
LED Warranty	5 Years

HOUSING

Material	Extruded aluminium
Finish	Powder coated
Protection Rating	Class 1
Optics	Reflector
Weight	1.3kg
Mounting	Track / surface mounted
Accessories	(see page 16)

Round Shallow



Projectors



Product Family		Beam		Mounting		Bezel Colour		CCT & Output		Suffix
S18311	Round vertical	SP	Spot	/TR	Track adapter	/05	White	00	3000K 9.4W	.8
		FL	Flood	/CP	Ceiling Plate	/04	Black	02	4000K 9.4W	
		WFL	Wide Flood			/21	Silver	03	3000K 13.6W	
								04	4000K 13.6W	
								06	3000K 15.8W	
								07	4000K 15.8W	

Dimmable and control options available.
See page 268 for details.

Round Vertical

Track / Ceiling


LIGHT DETAILS

Wattage	CCT	Lumens	Efficacy
9.4W	3000K	1346lm	143lm/W
9.4W	4000K	1423lm	151lm/W
13.6W	3000K	1824lm	134lm/W
13.6W	4000K	1928lm	142lm/W
15.8W	3000K	2059lm	131lm/W
15.8W	4000K	2176lm	138lm/W



Updated to the very latest Tridonic LES10 LED modules, this highly successful spotlight now offers even greater efficiency with enhanced performance and particularly low energy consumption.

Manufactured in our own Hampshire factory to exacting standards, this Round Shallow Spotlight range uses high quality extruded aluminium profile with machined heatsink for optimum heat dissipation and longevity. Integral high performance LED driver is fitted as standard.

Available with 3-circuit track adaptor or ceiling plate. Also available with optional built in dimming control making it an ideal choice for museums, galleries etc.



PHOTOMETRY



TECHNICAL SPECIFICATIONS

IP rating	IP20
CRI	>80
Lamp Life	50,000 hours
Light Source	Tridonic SLE LED
Voltage	240V
Driver	250mA / 350mA
LED Warranty	5 Years

HOUSING

Material	Extruded aluminium
Finish	Powder coated
Protection Rating	Class 1
Optics	Reflector
Weight	1.3kg
Mounting	Track / Surface mounted
Accessories	(see page 16)

Round Vertical






Accessories

A full range of accessories is available for use with our highly successful British designed and built Round projectors. All versions are based around a high quality machined mounting frame incorporating a ball catch system for ease of use. Can be easily retrofitted to fittings already supplied.

Order Code	Description
950.0323	Honeycomb Louvre
950.0325.020	Blue Filter
950.0325.030	Amber Filter
950.0325.040	Green Filter
950.0325.060	Red Filter
950.0325.070	Yellow Filter
950.0336	Barn Door
950.0342	Spreader Lens
950.0343	Frosted Lens





the
SLM
Projector
range



One of our most popular projectors, the Sovereign SLM provides quality, high output illumination, as well as RGBW options.



The SLM is highly versatile, suitable for a wide range of applications such as museums, heritage and faith buildings.



Product Family		Beam Angle		Mounting		Housing Colour		Version			Suffix		
S18322	SLM	SP	Spot	/TR	Track adapter	/05	White	02	3000K	18.42W	.8		
		FL	Flood	/CP	Ceiling plate	/04	Black	03	4000K	18.42W			
		WFL	Wide flood					04	3000K	26.44W			
								05	4000K	26.44W			
								54	3000K	34.34W			
								60	4000K	34.34W			
								67	3000K	38.97W			
								68	4000K	38.97W			
									24L	RGBW		16.8W	
									24H	RGBW		28.8W	

Dimmable and control options available.
See page 268 for details.

SLM projector

Track / Ceiling Mounted



LIGHT DETAILS

Wattage	CCT	Lumens	Efficacy
18.42W	3000K	2740lm	149lm/W
18.42W	4000K	2836lm	154lm/W
26.44W	3000K	3726lm	141lm/W
26.44W	4000K	3833lm	145lm/W
34.34W	3000K	4941lm	144lm/W
34.34W	4000K	5152lm	150lm/W
38.97W	3000K	5916lm	152lm/W
38.97W	4000K	6169lm	159lm/W
RGBW	16.8W	804lm	48lm/W
RGBW	28.8W	1207lm	42lm/W

A high quality aesthetically pleasing LED projector designed specifically for use with the very latest generation Tridonic SLE LED modules.


Housing manufactured from spun aluminium with integrated passive heatsink technology for optimum thermal management, leading to exceptional performance in excess of 140 lm/W for 3000K and 4000K versions. Also available with RGBW.

High purity aluminium reflector system in a choice of beam angles. Integral high efficiency LED driver with dimmable versions available on request. Manufactured in our own Hampshire factory to exacting standards to ensure longevity.




PHOTOMETRY


Wide flood



Flood



Spot



TECHNICAL SPECIFICATIONS

IP rating	IP40
CRI	>80
Lamp Life	50,000 hours
Light Source	Tridonic SLE
Beam	15° / 26° / 45°
Voltage	240V
Driver	High efficiency

HOUSING

Material	Aluminium
Finish	Powder coated
Protection Rating	Class 1
Optics	Clear Glass
Weight	2.8kg
Mounting	Track adapter / ceiling plate
Accessories	(see page 26)

SLM Projector






A full range of accessories is available for use with our highly successful British designed and built SLM projectors. All versions are easily mounted onto the SLM housing. Can be easily retrofitted to fittings already supplied.

Order Code	Description
950.3336	Honeycomb Louvre
950.0335.020	Blue Filter
950.0335.030	Amber Filter
950.0335.040	Green Filter
950.0335.060	Red Filter
950.0325.070	Yellow Filter
950.0337	Barn Door

Accessories



the
**Tubular
Spotlight**
range



The Tubular Spotlight has been a popular mainstay of the Sovereign range, now fully updated to incorporate the latest LED technology.



Product Family		Mounting		Housing Colour		CCT & Output		Suffix
S18344	Tubular Spot	TR	Track adapter	/05	White	00	3000K 18.4W	.8
		CP	Ceiling plate	/04	Black	01	4000K 18.4W	
				/21	Silver	06	3000K 34W	
						08	4000K 34W	
						10	3000K 26W	
						11	4000K 26W	

Dimmable and control options available.
See page 268 for details.

Tubular


Track / Ceiling Spotlight

LIGHT DETAILS


Wattage	CCT	Lumens	Efficacy
18.4W	3000K	2815lm	153lm/W
18.4W	4000K	2936lm	160lm/W
26W	3000K	3838lm	147lm/W
26W	4000K	4002lm	154lm/W
34W	3000K	4823lm	132lm/W
34W	4000K	5029lm	148lm/W

The Tubular Spotlight provides an alternative to the SLM projector. Providing similarly high output illumination, the Tubular Spotlight offers a more compact style.

Keeping its iconic minimalist design, the high quality spun aluminium luminaire is assembled in our Hampshire factory using carefully selected components for maximum longevity.



PHOTOMETRY



TECHNICAL SPECIFICATIONS

IP rating	IP40
CRI	>80
Lamp Life	50,000 hours
Light Source	Tridonic SLE LED
Voltage	240V
Driver	Integrated high efficiency
LED Warranty	5 Years

HOUSING

Material	Aluminium
Finish	Powder coated
Protection Rating	Class 1
Optics	Clear glass
Weight	2.8kg
Mounting	Track adapter / ceiling plate

Tubular Spotlight



Projectors

the
Zoom
Projector
ranges



Adjustable telescopic lens for precise beam configuration makes these projectors ideal for museum and exhibition lighting.



Product Family		Mounting		Housing Colour		CCT		Suffix
S18400	Zoom 20W	TR	Track adapter	/05	White	00	2700K	.8
S18401	Zoom 30W			/04	Black	01	3000K	
S18402	Zoom 35W			/21	Silver	02	4000K	

Dimmable and control options available.
See page 268 for details.

Zoom




Track Projector

LIGHT DETAILS



Wattage	CCT	Lumens	Efficacy
20W	2700K	1965lm	98lm/W
20W	3000K	1984lm	99lm/W
20W	4000K	2049lm	102lm/W
30W	2700K	3065lm	102lm/W
30W	3000K	3082lm	103lm/W
30W	4000K	3150lm	105lm/W
35W	2700K	3482lm	99lm/W
35W	3000K	3502lm	100lm/W
35W	4000K	3570lm	102lm/W

The Sovereign Zoom Projector has an adjustable telescopic lens for precise beam configuration. Together with the high colour rendering of CRI 90, this projector is ideal for applications such as museum and exhibition lighting.

Available in 3 sizes, outputs and colour temperatures, the Sovereign Zoom comes in white, black or silver.



PHOTOMETRY



TECHNICAL SPECIFICATIONS

IP rating	IP20
CRI	>80
Lamp Life	50,000 hours
Light Source	CREE / Philips / Osram COB
Voltage	240V
Driver	Integrated high efficiency
Beam	15°-60° (15°-45° for 20W)
LED Warranty	5 Years

HOUSING

Material	Aluminium
Finish	Powder coated
Protection Rating	Class 1
Optics	Adjustable
Weight	0.8kg
Mounting	Track adapter / ceiling plate

Zoom Projector



Projectors



Product Family		Housing Colour		CCT & Output		Suffix
S18400	Zoom+	/05	White	00	2700K 20W	.8
		/04	Black	01	3000K 20W	
		/21	Silver	02	4000K 20W	
				00	2700K 30W	
				01	3000K 30W	
				02	4000K 30W	

Dimmable and control options available.
See page 268 for details.

Zoom+



Track Projector

LIGHT DETAILS

Wattage	CCT	Lumens	Efficacy
20W	2700K	2000lm	100lm/W
20W	3000K	2200lm	110lm/W
20W	4000K	2200lm	110lm/W
30W	2700K	3065lm	102lm/W
30W	3000K	3082lm	103lm/W
30W	4000K	3150lm	105lm/W



An exciting new addition to the Sovereign Zoom Projector range, the Zoom+ offers an adjustable telescopic lens with beam angle from an exceptionally narrow 6° through to a wide 60° all with a simple twist of the front housing, making this unit perfect for museums or any application involving changing displays.

Using the latest LED technology, this version is supplied as standard with high colour rendering CRI 90 and is available in a choice of colour temperatures. Available in durable white, black or silver powder coated finish.



TECHNICAL SPECIFICATIONS

IP rating	IP20
CRI	>90
Lamp Life	50,000 hours
Light Source	Philips COB LED
Voltage	240V
Beam	6° - 60°
Driver	Integrated in adapter



HOUSING

Material	Aluminium
Finish	Powder coated
Protection Rating	Class 1
Optics	Adjustable
Weight	1.55kg
Mounting	Track Mounted

Zoom+ Projector



Projectors



the
**Framing
Projector**
range



Designed for the Gallery and Museum sectors, this projector allows for precise, shaped projection to carefully accentuate individual objects and artworks.



Product Family		Mounting		Housing Colour		CCT & Output			Suffix
S18388	Framing Projector	TR	Track adapter	.05	White	00	3000K	15W	.8
		CP	Ceiling plate	.04	Black	01	4000K	15W	
				.21	Silver	02	3000K	30W	
						03	4000K	30W	

Dimmable and control options available.
See page 268 for details.

Framing Projector

Track / Ceiling


LIGHT DETAILS

Wattage	CCT	Lumens	Efficacy
15W	3000K	1932lm	90lm/W
15W	4000K	1987lm	90lm/W
30W	3000K	2740lm	100lm/W
30W	4000K	2836lm	100lm/W

This projector provides an adjustable square and rectangular light output for precision illumination.

Different shapes are made through shuttering down, while the adjustable lens allows controls the size.

Available in multiple outputs and colour temperatures.



TECHNICAL SPECIFICATIONS

IP rating	IP20
CRI	>90
Lamp Life	50,000 hours
Light Source	COB LEDs
Voltage	240V
Driver	Integrated high efficiency
LED Warranty	5 Years

HOUSING

Material	Aluminium
Finish	Powder coated
Protection Rating	Class 1
Optics	Adjustable
Weight	2.58kg
Mounting	Track adapter / Ceiling plate

Framing Projector



the
Gobo
Projector
range



A specialised luminaire for the Gallery and Museum sectors, offering the highest light quality with its impressive full spectrum technology and high CRI of 98.



Product Family		Mounting		Housing Colour		CCT & Output		Suffix
S18389	Gobo Projector	SP	Spot	.05	White	00	3000K 30W	.8
		FL	Flood	.04	Black	01	3700K 30W	
		WFL	Wide flood	.21	Silver	02	4000K 30W	
						03	5000K 30W	
						04	3000K 60W	
						05	3700K 60W	
						06	4000K 60W	
						07	5000K 60W	


Dimmable and control options available.
See page 268 for details.

Gobo Projector

Track / Ceiling

An elegant and powerful surface or track mounted projector, with adjustable framing fingers for focusing and high quality lens to ensure optimum light quality.

Available in a range of outputs, beam angles and colour temperatures. Main housing come in white as standard, but also available in any BS/RAL colours. Gobo to be ordered separately (Size E).



TECHNICAL SPECIFICATIONS

IP rating	IP20
CRI	>80
Lamp Life	50,000 hours
Light Source	LED
Colour Temp	3000K / 3700K / 4000K / 5000K
Lumen Output	3000 ~ 4000K
Beam	15° / 25° / 35°
Voltage	240V
Driver	Integrated high efficiency
LED Warranty	5 Years

HOUSING

Material	Aluminium
Finish	Powder coated
Protection Rating	Class 1
Optics	Adjustable glass lens
Weight	2.5kg
Mounting	Track / surface mounted

Gobo Projector




Projectors

the
Art
Spotlight
range

A specialised luminaire for the Gallery and Museum sectors, offering the highest light quality with its impressive full spectrum technology and high CRI of 98.

Art Spotlight



Standard Spotlight





Product Family		Beam		Mounting		Housing Colour		CCT & Version		Suffix
S18369	Art Spotlight	SP	Spot	/TR	Track adapter	/05	White	00	3000K Shallow	.8
		FL	Flood	/CP	Ceiling Plate	/04	Black	01	4000K Shallow	
		WFL	Wide Flood			/21	Silver	02	3000K Vertical	
								03	4000K Vertical	

Dimmable and control options available.
See page 268 for details.

Art Spotlight

Track / Ceiling


LIGHT DETAILS

Wattage	CCT	Lumens	Efficacy
16.8W	3000K	2000lm	119lm/W
16.8W	4000K	2000lm	119lm/W



The Sovereign ART LED Spotlight offeris the highest light quality with its impressive full spectrum technology and high CRI of 98. Far outperforming standard spotlights in its colour rendering ability, the ART LED Spotlight is an ideal choice for artwork and exhibit illumination, as well as for use in the retail sector.

Manufactured in our own Hampshire factory to exacting standards, the Sovereign ART LED Spotlight uses high quality extruded aluminium profile with machined heatsink for optimum heat dissipation and longevity. Integral high performance LED driver is fitted as standard.

Available in both vertical and shallow versions, and with 3-circuit track adaptor or ceiling plate. Also available with optional built in dimming control.



PHOTOMETRY




TECHNICAL SPECIFICATIONS

IP rating	IP20
CRI	98
Lamp Life	50,000 hours
Light Source	Tridonic SLE ART EXC
Beam	15° / 25° / 40°
Voltage	240V
Driver	High efficiency
LED Warranty	5 Years

HOUSING

Material	Aluminium
Finish	Powder coated
Protection Rating	Class 1
Optics	Reflector
Weight	0.6kg
Mounting	Track / surface mounted



the
48V
Projector
range

Our smallest projector range, offering high quality illumination from the most compact of luminaires.

The adjustable lens allows for 15°-45° beam angles, with an impressive colour rendering of 90Ra.





Product Family		Mounting		Housing Colour		CCT & Output		Suffix
S18375	6W 48V	.TR48	48V Track	.05	White	00	2700K	.8
S18376	10W 48V			.04	Black	01	3000K	
						02	4000K	

Dimmable and control options available.
See page 268 for details.

48V Projector

Adjustable Track Mounted


LIGHT DETAILS

Wattage	CCT	Lumens	Efficacy
6W	2700K	660lm	110lm/W
6W	3000K	660lm	110lm/W
6W	4000K	660lm	110lm/W
10W	2700K	1100lm	110lm/W
10W	3000K	1100lm	110lm/W
10W	4000K	1100lm	110m/W



The Sovereign 48V Track Projector is our smallest projector range, offering high quality illumination from the most compact of luminaires.

The adjustable lens allows for 15°-45° beam angles, with an impressive colour rendering of 90Ra.mounted on 48V track available in a range of lengths.

Available in two sizes, along with a range of colour temperatures and housing colours.



PHOTOMETRY



TECHNICAL SPECIFICATIONS

IP rating	IP40
CRI	>90
Lamp Life	50,000 hours
Light Source	CREE COB LEDs
Beam	15°-45°
Voltage	240V
Driver	High efficiency
LED Warranty	5 Years

HOUSING

Material	Aluminium
Finish	Powder coated
Protection Rating	Class 1
Optics	Adjustable
Weight	0.6kg
Mounting	48V Track mounted
Dimensions	Ø45xH90 @6W Ø55xH110 @10W

48V Projector



the
Soloflood
Projector
range

A powerful and flexible projector, used successfully in a range of applications, from churches to retail.





Product Family		Mounting		Housing Colour		CCT		Suffix
S18394	Soloflood		Stirrup only	.05	Textured white	00	3000K	.8
		TR	Track adapter	.04	Textured black	01	4000K	
		CP	Ceiling plate	.21	Textured silver			

Dimmable and control options available.
See page 268 for details.

Soloflood

Track / Ceiling Projector


LIGHT DETAILS

Wattage	CCT	Lumens	Efficacy
25.5W	3000K	4060lm	159lm/W
25.41W	4000K	4240lm	167lm/W

Our Soloflood LED projector is the perfect solution for any interior project requiring a high level of illumination over larger areas including churches, large retail outlets etc.

Manufactured in the UK using our own aluminium extruded housing with aluminium end plates and designed around the very latest generation of Tridonic LED components for optimum performance and longevity.

Supplied as standard with high efficiency non dimming driver but also available with a range of dimming options and power output. Standard colours black, white, and silver as standard with other BS/RAL colours to order.



TECHNICAL SPECIFICATIONS

IP rating	IP20
CRI	>90
Lamp Life	50,000 hours
Light Source	Tridonic LLE LED
Voltage	240V
Driver	Integrated high efficiency
LED Warranty	5 Years


HOUSING

Material	Die-cast Aluminium
Finish	Powder coated
Protection Rating	Class 1
Optics	Opal tubes diffuser
Weight	2.8.kg
Mounting	Surface /Track mounting

Soloflood Projector



Projectors



Ceiling
Downlights



A comprehensive range of interior ceiling downlights. From miniature 2W display downlights to high power luminaires for suitable for large indoor spaces.

Perfect for new installations or as an ideal replacement for existing metal halide units.

the
**Fixed
Downlight**
ranges






Product Family		Housing Colour		CCT		Suffix
S98911	20W	.05	White	01	3000K	.8
S98912	25W	.04	Black	02	4000K	
S98913	30W	.21	Silver			
S98914	35W					


EM and dimmable options available - see page 268 for ordering info.

Maxi Fixed


Interior Downlight




Wattage	CCT	Lumens	Efficacy
20W	3000K	2000lm	100lm/W
20W	4000K	2200lm	110lm/W




Wattage	CCT	Lumens	Efficacy
25W	3000K	2500lm	100lm/W
25W	4000K	2750lm	110lm/W



Wattage	CCT	Lumens	Efficacy
30W	3000K	3000lm	100lm/W
30W	4000K	3300lm	110lm/W



Wattage	CCT	Lumens	Efficacy
35W	3000K	2500lm	100lm/W
35W	4000K	3850lm	110lm/W



TECHNICAL SPECIFICATIONS

IP rating	IP20
CRI	>80
Lamp Life	50,000 hours
Light Source	CREE LED
Voltage	240V
Driver	High efficiency
LED Warranty	5 Years

HOUSING

Material	Aluminium
Finish	Powder coated
Protection Rating	Class 1
Optics	Clear Glass
Weight	1.4kg
Mounting	Ceiling recessed

Maxi Fixed



Ceiling Downlights

Offering impressive lumen packages with exceptional LOR, the Maxi Fixed units are an ideal replacement for metal halide and compact fluorescent downlights.

Available in four sizes and outputs, as well as our usual customisation options including EM and dimmable control.




Product Family		Bezel Colour		CCT & Output		Suffix
S18154	Standard	.05	White	07	3000K 12.62W	.8
S18174	Drop glass	.04	Black	08	4000K 12.62W	
S18254	Under canopy	.21	Silver	02	3000K 18.42W	
				03	4000K 18.42W	
				04	3000K 26.44W	
				05	4000K 26.44W	
				33	3000K 34.34W	
				34	4000K 34.34W	

EM and dimmable options available - see page 268 for ordering info.

Midi Fixed

Interior Downlight




LIGHT DETAILS

Wattage	CCT	Lumens	Efficacy
12.62W	3000K	1932lm	153lm/W
12.62W	4000K	1987lm	157lm/W
18.42W	3000K	2740lm	149lm/W
18.42W	4000K	2836lm	154lm/W
26.44W	3000K	3726lm	141lm/W
26.44W	4000K	3833lm	145lm/W
34.34W	3000K	4941lm	144lm/W
34.34W	4000K	5152lm	150lm/W

One of our most successful UK produced downlights, the Sovereign MIDI Fixed Downlight is a powerful luminaire capable of over 5000lm with impressive efficiency.

Available in different housing styles to suit a range of applications, the Midi Fixed is offered with four different outputs as well as our usual customisable options.

DIMENSIONS



TECHNICAL SPECIFICATIONS

IP rating	IP40
CRI	>80
Lamp Life	50,000 hours
Light Source	Tridonic SLE G7
Voltage	240V
Driver	High efficiency
LED Warranty	5 Years

HOUSING

Material	Aluminium
Finish	Powder coated
Protection Rating	Class 1
Weight	0.85kg
Mounting	Ceiling Recessed

Midi Fixed



Ceiling Downlights



Product Family		Insert		Beam		Bezel Colour		CCT		Suffix
S18153	Standard	D	Darklight	SP	Spot	.05	White	00	3000K	.8
S18173	Drop glass		Standard	FL	Flood	.04	Black	08	4000K	
S18253	Under canopy			WFL	Wide Flood	.21	Silver			


EM and dimmable options available - see page 268 for ordering info.

Mini Fixed

Interior Downlight

LIGHT DETAILS


Wattage	CCT	Lumens	Efficacy
9.4W	3000K	1346lm	143lm/W
9.4W	4000K	1423lm	151lm/W



A high quality miniature LED downlight designed and produced in the UK as a realistic replacement for existing MR16 Halogen units. Incorporating the latest Tridonic LES10 LED array, this is an exceptionally efficient LED, providing up to a genuine 151lm/W including driver losses.

Includes passive heat-sink technology, built-in clear lens for glare reduction, a high performance faceted reflector, and a number of customisable options.

DIMENSIONS



TECHNICAL SPECIFICATIONS

IP rating	IP40
CRI	>80
Lamp Life	50,000 hours
Light Source	Tridonic SLE LED
Voltage	240V
Driver	High efficiency
Beam	15° / 25° / 45°
LED Warranty	5 Years


HOUSING

Material	Aluminium
Finish	Powder coated
Protection Rating	Class 1
Optics	Clear acrylic
Weight	0.38kg
Mounting	Ceiling recessed

Mini Fixed



Ceiling Downlights




Product Family		Beam		Bezel Colour		CCT		Suffix
S18120	2W	SP	Spot	.05	White	10	2700K	.8
S18121	3W	FL	Flood	.04	Black	11	3000K	
S18122	5W	WFL	Wide Flood	.21	Silver	12	4000K	
S18123	8W							
S18124	12W							

EM and dimmable options available - see page 268 for ordering info.


Mini Darklight

Display Downlight


CAT no. S18120




CAT no. S18121




CAT no. S18122



CAT no. S18123



CAT no. S18124



LIGHT DETAILS

Wattage	CCT	Lumens	Efficacy
2W	3000K	210lm	105lm/W
2W	4000K	220lm	110lm/W

Wattage	CCT	Lumens	Efficacy
3W	3000K	315lm	105lm/W
3W	4000K	330lm	110lm/W

Wattage	CCT	Lumens	Efficacy
5W	3000K	525lm	105lm/W
5W	4000K	550lm	110lm/W

Wattage	CCT	Lumens	Efficacy
8W	3000K	840lm	105lm/W
8W	4000K	880lm	110lm/W

Wattage	CCT	Lumens	Efficacy
12W	3000K	1260lm	105lm/W
12W	4000K	1320lm	110lm/W

The Sovereign Mini Darklight is a range of high quality fixed LED downlights with built in anti-glare baffle to provide a high level of comfort and efficiency.

All versions supplied complete with carefully matched remote drivers designed to pass through the cut-out, even on the tiny 2W version with its 25mm diameter (one of the smallest downlights on the market).

Simple plug & socket system between driver and head for ease of installation.

TECHNICAL SPECIFICATIONS

IP rating	IP40
CRI	>80
Lamp Life	50,000 hours
Light Source	CREE COB
Voltage	240V
Driver	High efficiency
LED Warranty	5 Years

HOUSING

Material	Aluminium
Finish	Powder coated
Protection Rating	Class 1
Optics	Anti glare baffle
Weight	0.2kg
Mounting	Ceiling Recessed

Mini Darklight




Ceiling Downlights





the
**Adjustable
Downlight**
ranges

For applications requiring variable beam angles, such as for wall displays. Ideal for retail, hospitality and office environments.



Product Family		Beam		Bezel Colour		CCT & Output		Suffix
S18151	20W	SP	Spot	.05	White	10	3000K 20W	.8
S18155	28W	FL	Flood	.04	Black	11	4000K 20W	
		WFL	Wide Flood	.21	Silver	02	3000K 28W	
						03	4000K 28W	

EM and dimmable options available - see page 268 for ordering info.



Maxi Gimbal

Interior Downlight

LIGHT DETAILS

Wattage	CCT	Lumens	Efficacy
20W	3000K	2179lm	108lm/W
20W	4000K	2311lm	115lm/W
28W	3000K	2959lm	106lm/W
28W	4000K	3137lm	112lm/W

PHOTOMETRY



TECHNICAL SPECIFICATIONS

IP rating	IP40
CRI	>90
Lamp Life	50,000 hours
Light Source	Osram PL-Core
Tilt	30°
Voltage	240V
Driver	High efficiency
Beam	Spot / Flood / Wide Flood
LED Warranty	5 Years

HOUSING

Material	Aluminium
Finish	Powder coated
Protection Rating	Class 1
Optics	Clear glass
Weight	0.6kg
Mounting	Ceiling recessed


The Sovereign Maxi Gimbal Downlight pairs an impressive light output with the flexibility of a gimbal fixture. Ideal for retail applications.

Incorporating the latest Osram PL-CORE LED modules which are coupled with a high efficiency, low flicker LED driver for optimum life and efficiency.

Fixed output drivers are supplied as standard but dimmable options are available to suit any dimming protocol.

Maxi Gimbal





die-cast aluminium housing

independently adjustable

Product Family		Beam		Bezel Colour		CCT & Output		Suffix
S18151/2	20W Twin	SP	Spot	.05	White	10	3000K 20W	.8
S18155/2	28W Twin	FL	Flood	.04	Black	11	4000K 20W	
		WFL	Wide Flood	.21	Silver	02	3000K 28W	
						03	4000K 28W	

EM and dimmable options available - see page 268 for ordering info.

Maxi Twin Gimbal

Interior Downlight



LIGHT DETAILS

Wattage	CCT	Lumens	Efficacy
20W	3000K	2179lm	108lm/W
20W	4000K	2311lm	115lm/W
28W	3000K	2959lm	106lm/W
28W	4000K	3137lm	112lm/W

This twin version of the Maxi Gimbal allows for great directional flexibility. Independently adjustable, the two light sources allow for precise illumination.

Available with different beam options and outputs, as well as optional EM and dimmable control.

PHOTOMETRY




TECHNICAL SPECIFICATIONS

IP rating	IP40
CRI	>90
Lamp Life	50,000 hours
Light Source	Osram PL-Core
Tilt	30°
Voltage	240V
Driver	High efficiency
Beam	Spot / Flood / Wide Flood
LED Warranty	5 Years

HOUSING

Material	Aluminium
Finish	Powder coated
Protection Rating	Class 1
Optics	Clear glass
Weight	0.6kg
Mounting	Ceiling recessed

Maxi Twin Gimbal





spot / flood / wide flood

Product Family		Beam		Bezel Colour		CCT & Output			Suffix
S18151	Midi Gimbal	SP	Spot	.05	White	20	3000K	18W	.8
		FL	Flood	.04	Black	21	4000K	18W	
		WFL	Wide Flood	.21	Silver	22	3000K	24W	
						23	4000K	24W	

EM and dimmable options available - see page 268 for ordering info.

Midi Gimbal

Interior Downlight


LIGHT DETAILS

Wattage	CCT	Lumens	Efficacy
18W	3000K	1627lm	90lm/W
18W	4000K	1633lm	90lm/W
24W	3000K	2575lm	107lm/W
24W	4000K	2730lm	113lm/W

A beautifully compact high performance adjustable gimbal downlight, resulting in highly efficient light output in a fitting of just 140mm total diameter. Successfully used in major retail stores.

Available in a choice of outputs and colour temperature options. Supplied complete with high efficiency LED driver for optimum life and efficiency.

Main bezel and lamp housing of die-cast aluminium, with powder coated finish for durability. Standard colours white or black with other BS/ RAL colours to order.



TECHNICAL SPECIFICATIONS

IP rating	IP40
CRI	>90
Lamp Life	50,000 hours
Light Source	Tridonic SLE
Tilt	30°
Voltage	240V
Driver	High efficiency
LED Warranty	5 Years

HOUSING

Material	Die-cast aluminium
Finish	Powder coated
Protection Rating	Class 1
Optics	Clear acrylic
Weight	0.6kg
Mounting	Ceiling Recessed

Midi Gimbal



Ceiling Downlights



Product Family		Bezel Colour		CCT		Suffix
S18156	Scoop	.05	White	10	2700K	.8
		.04	Black	11	3000K	
		.21	Silver	12	4000K	



EM and dimmable options available - see page 268 for ordering info.

Scoop

Interior Downlight

LIGHT DETAILS

Wattage	CCT	Lumens	Efficacy
18W	3000K	2083lm	115lm/W
18W	4000K	2083lm	115lm/W
28W	3000K	3137lm	112lm/W
28W	4000K	3137lm	112lm/W



A high quality fully adjustable recessed downlight, allowing a 360° rotation and 45° tilt. An updated version of a mainstay of the Sovereign range, the Scoop utilises the most up-to-date LED technology to ensure optimum efficiency and light quality.

Available in any BS / RAL colour, with dimmable and emergency variants available. Offered with either 3000K or 4000k colour temperature

TECHNICAL SPECIFICATIONS

IP rating	IP40
CRI	>90
Lamp Life	50,000 hours
Light Source	Osram LED
Tilt	45°
Rotation	360°
Voltage	240V
Driver	High efficiency


HOUSING

Material	Aluminium
Finish	Powder coated
Protection Rating	Class 1
Optics	Clear glass
Weight	0.6kg
Mounting	Ceiling Recessed

Scoop



Ceiling Downlights





Interior
Pendants

the
Broadline
Suspended
ranges



A sleek, minimalist form designed to accentuate the bold simplicity of the geometric profile.

For the ultimate clean aesthetic, choose blind end caps when specifying the Broadline Suspended range, and the remote driver option with the Broadline Cylindrical.

As well as our standard colour, output and CCT options, the standard Broadline Suspended can be cut in a range of angles and shapes to provide limitless geometric designs. Perfect for more dramatic, feature lighting solutions.







Product Family		Housing Colour		CCT		Suffix
S18620	584mm direct	/X5	Textured white	00	3000K	.8
S18622	1144mm direct	/X4	Textured black	01	4000K	
S18623	1424mm direct	/X2	Textured silver			
S18624	1704mm direct					
S18625	584mm direct/indirect					
S18627	1144mm direct/indirect					
S18628	1424mm direct/indirect					
S18629	1704mm direct/indirect					

EM, dimmable and control options available.
See page 268 for details.

Broadline

Suspended



LIGHT DETAILS - DIRECT

Length	CCT	Wattage	Lumens	Efficacy
584mm	3000K	15W	2350lm	161lm/W
584mm	4000K	15W	2470lm	169lm/W
1144mm	3000K	29W	4700lm	161lm/W
1144mm	4000K	29W	4940lm	169lm/W
1424mm	3000K	37W	5870lm	161lm/W
1424mm	4000K	37W	6170lm	169lm/W
1704mm	3000K	44W	7045lm	161lm/W
1704mm	4000K	44W	7410lm	169lm/W

A beautifully elegant linear profile system designed around the latest high performance Tridonic LLE LED modules.

Produced in high quality aluminium extruded profile, the Broadline Suspended luminaire can be supplied in standard lengths, or custom cut to suit. Also available as individual pendants or joined via plug & socket connection to provide "continuous" runs as required.

Supplied with standard or blind end caps (illustrated opposite), as well as an alternative prismatic diffuser. Get in touch to discuss full customisation options, including custom shapes and angles.

LIGHT DETAILS - DIRECT/INDIRECT

Length	CCT	Wattage	Lumens	Efficacy
584mm	3000K	22W	2350lm + 1174lm	161lm/W
584mm	4000K	22W	2470lm + 1235lm	169lm/W
1144mm	3000K	44W	4700lm + 2350lm	161lm/W
1144mm	4000K	44W	4940lm + 2470lm	169lm/W
1424mm	3000K	58W	5870lm + 3525lm	161lm/W
1424mm	4000K	58W	6170lm + 3705lm	169lm/W
1704mm	3000K	73W	7045lm + 4700lm	161lm/W
1704mm	4000K	73W	7410lm + 4940lm	169lm/W

Note: bespoke lengths available

TECHNICAL SPECIFICATIONS

IP rating	IP20
CRI	>80
Lamp Life	50,000 hours
Light Source	Tridonic LLE LED
Voltage	240V
Driver	Integrated high efficiency
LED Warranty	5 Years

HOUSING

Material	Extruded aluminium
Style	Standard / Blind end caps
Finish	Powder coated
Protection Rating	Class 1
Optics	Opal diffuser
Weight	2.5kg @ 600mm
Mounting	Wire suspension kit

Broadline Suspended



Pendants



Product Family		Housing Colour		CCT		Suffix
S18620IP	594mm direct	/X5	Textured white	00	3000K	.8
S18622IP	1154mm direct	/X4	Textured black	01	4000K	
S18623IP	1434mm direct	/X2	Textured silver			
S18624IP	1714mm direct					

EM, dimmable and control options available.
See page 268 for details.



Broadline IP65

Suspended

LIGHT DETAILS

Length	CCT	Wattage	Lumens	Efficacy
594mm	3000K	15W	2350lm	161lm/W
594mm	4000K	15W	2470lm	169lm/W
1154mm	3000K	29W	4700lm	161lm/W
1154mm	4000K	29W	4940lm	169lm/W
1434mm	3000K	37W	5870lm	161lm/W
1434mm	4000K	37W	6170lm	169lm/W
1714mm	3000K	44W	7045lm	161lm/W
1714mm	4000K	44W	7410lm	169lm/W

Note: bespoke lengths up to 2m available



TECHNICAL SPECIFICATIONS

IP rating	IP65
CRI	>80
Lamp Life	50,000 hours
Light Source	Tridonic LLE LED
Voltage	240V
Driver	Integrated high efficiency
LED Warranty	5 Years

HOUSING

Material	Extruded aluminium
Finish	Powder coated
Protection Rating	Class 1
Optics	Opal diffuser
Weight	2.5kg @ 600mm
Mounting	Wire suspension kit


Matching the elegance of the Broadline Suspended, the Broadline IP65 Suspended extends the range to allow for exterior installations.

Produced in high quality aluminium extruded profile, the Broadline IP65 Suspended can be supplied in standard lengths, or custom cut to suit. Supplied c/w adjustable 3mtr wire suspension set.

Broadline IP65 Suspended



Pendants




EM, dimmable and control options available.
See page 268 for details.

Product Family		Driver		Housing Colour		CCT		Suffix
S18672	594mm		Integrated	/00	Silver	00	3000K	.8
S18673	1154mm	R	Remote			01	4000K	
S18674	1434mm							
S18675	1714mm							

Broadline Cylindrical


Suspended

LIGHT DETAILS



Length	CCT	Wattage	Lumens	Efficacy
584mm	3000K	15W	2350lm	161lm/W
584mm	4000K	15W	2470lm	169lm/W
1144mm	3000K	29W	4700lm	161lm/W
1144mm	4000K	29W	4940lm	169lm/W
1424mm	3000K	37W	5870lm	161lm/W
1424mm	4000K	37W	6170lm	169lm/W
1704mm	3000K	44W	7045lm	161lm/W
1704mm	4000K	44W	7410lm	169lm/W

Note: bespoke lengths available



TECHNICAL SPECIFICATIONS

IP rating	IP40
CRI	>80
Lamp Life	50,000 hours
Light Source	Tridonic LLE LED
Voltage	240V
Driver	High efficiency
LED Warranty	5 Years

HOUSING

Material	Extruded aluminium
Style	Remote / Integrated Driver
Finish	Powder coated
Protection Rating	Class 1
Optics	Polycarbonate diffuser
Weight	2.5kg @ 600mm
Mounting	Wire suspension kit

A beautifully stylish tubular luminaire, the Broadline Cylindrical range offers virtually all round illumination thanks to the wrap around diffuser design. Extending to 310° the diffusers allows the Tridonic LLE boards to provide high quality, even illumination.

Main spine and gear housing produced in high quality extruded & anodised aluminium with high transmission polycarbonate diffuser.

A choice of standard lengths are available with bespoke lengths up to 2.5mts also available to order. Standard versions fitted with integral high efficiency driver located within rear mounted aluminium housing, and can also be supplied with remote driver for a cleaner aesthetic line. Supplied c/w adjustable 3mtr wire suspension set.

Broadline Cylindrical

Pendants

the
Globe
Pendant
range



Effortlessly suspended, the Sovereign Globe Pendant range provides a dramatic sense of weightlessness to interior environments.

Available in three sizes, these minimalist luminaires are ideal for a range of lighting designs; from discrete ambient illumination to dramatic, feature lighting with countless configurations.




Product Family		Size		Housing Colour		Version		Suffix
S98674	Globe Pendant	/280	Size 1	/05	White	00	3000K 280mm	.8
		/380	Size 2			01	4000K 280mm	
		/550	Size 3			02	3000K 380mm	
						03	4000K 380mm	
						04	3000K 550mm	
						05	4000K 550mm	

EM, dimmable and control options available.
See page 268 for details.

Globe

Pendant


LIGHT DETAILS



Size	CCT	Wattage	Lumens	Efficacy
Ø280mm	3000K	22W	3166lm	144lm/W
Ø280mm	4000K	22W	3396lm	154lm/W
Ø380mm	3000K	35W	4840lm	138lm/W
Ø380mm	4000K	35W	5040lm	144lm/W
Ø550mm	3000K	52W	7530lm	146lm/W
Ø550mm	4000K	52W	7947lm	153lm/W

This sleek and minimal opal LED luminaire boasts a multi facettted geartray design, ensuring optimum uniformity throughout while maintaining the pure globe form.

The Sovereign Globe Pendant is available in three sizes and uses the latest in LED technology for optimum efficiency and illumination.



TECHNICAL SPECIFICATIONS

IP rating	IP40
CRI	>80
Lamp Life	50,000 hours
Light Source	Tridonic LLE + CLE
Voltage	240V
Driver	High efficiency
LED Warranty	5 Years

HOUSING

Material	Polyethylene / aluminium
Finish	Matt
Protection Rating	Class 1
Optics	Opal diffuser
Weight	Size 1 2.5KG / Size 2 3.5KG / Size 3 7KG
Mounting	Wire suspension kit

Globe Pendant



Pendants

the
High Bay
Pendant
range

A high performance decorative high bay, balancing a robust industrial-style housing with a delicate lightness provided by the prismatic shade.






Product Family		Housing Colour		Version		Suffix
S18332	High Bay	/05	White	22	3000K 20W	.8
		/04	Black	23	4000K 20W	
		/21	Silver	24	3000K 40W	
				25	4000K 40W	

EM, dimmable and control options available.
See page 268 for details.

High Bay

Pendant


LIGHT DETAILS



CCT	Wattage	Lumens	Efficacy
3000K	20W	2000lm	100lm/W
4000K	20W	2200lm	110lm/W
3000K	40W	4000lm	100lm/W
4000K	40W	4400lm	110lm/W

A high performance decorative high bay, incorporating a genuine Lexalite prismatic shade with extruded aluminium gear housing.

Utilising the very latest Tridonic/ Philips SLE LED module with passive heatsink, the Prismatic Pendant provides an aesthetic contrast between shade and gear housing.




TECHNICAL SPECIFICATIONS

IP rating	IP20
CRI	>80
Lamp Life	50,000 hours
Light Source	CREE COB
Voltage	240V
Driver	High efficiency
LED Warranty	5 Years

HOUSING

Material	Aluminium
Finish	Powder coated
Protection Rating	Class 1
Optics	Acrylic prismatic
Weight	3.5KG
Mounting	Wire suspension kit



Pendants

the
**Round
Suspended**
range

Taking the successful LED Panel concept to an exciting new level, these exceptionally slim circular units provide high levels of illumination with a pleasingly soft appearance.

With a main housing depth of just 25mm rising to a maximum of only 50mm for the discrete gear housing, these units give a “floating” appearance when suspended as pendants on our standard wire suspension system.





Product Family		Housing Colour		CCT		Suffix
S18636	Round Size 1	/05	White	00	3000K	.8
S18637	Round Size 2	/04	Black	01	4000K	
S18638	Round Size 3	/21	Silver			
S18639	Round Size 4					



EM, dimmable and control options available.
See page 268 for details.

Round

Suspended

LIGHT DETAILS

Size	CCT	Wattage	Lumens	Efficacy
Ø400mm	3000K	30W	2500lm	93lm/W
Ø400mm	4000K	30W	2700lm	90lm/W
Ø500mm	3000K	40W	3600lm	90lm/W
Ø500mm	4000K	40W	3800lm	90lm/W
Ø600mm	3000K	48W	4500lm	94lm/W
Ø600mm	4000K	48W	4800lm	100lm/W
Ø780mm	3000K	60W	5300lm	89lm/W
Ø780mm	4000K	60W	5400lm	90lm/W




IP rating	IP40
CRI	>80
Lamp Life	50,000 hours
Light Source	Side Emitting SMD
Voltage	240V
Driver	High efficiency
LED Warranty	5 Years

HOUSING

Material	Spun aluminium
Finish	Powder coated
Protection Rating	Class 1
Optics	Opal diffuser
Weight	3.5kg - 6kg
Mounting	Wire suspension kit


Available in four sizes and outputs, the Sovereign Round Suspended range is supplied complete with standard high efficiency driver, but can also be specified with dimmable drivers to suit any dimming protocol.

EM versions also available, with all components located within the spun aluminium rear gear housing for ease of installation.



the
Ecoblade
Pendant
range

The Sovereign Ecoblade range is the result of extensive research and development by Commercial Lighting Systems. Matching a minimalist style with impressive efficiency and illumination makes the Ecoblade ideal for office environments.



Available also in Wall Mounted and Free Standing versions, the Ecoblade pendant is available as an uplight only or with an additional downlight option.




Product Family		Housing Colour		CCT		Suffix
S18641	Ecoblade Pendant	.X5	Textured white	00	3000K Uplight	.8
S18642	Ecoblade Slot Pendant	.X4	Textured black	01	4000K Uplight	
		.X2	Textured silver	02	3000K Up/Down	
				03	4000K Up/Down	

EM, dimmable and control options available.
See page 268 for details.

Ecoblade


Pendant

LIGHT DETAILS - UP




CCT	Wattage	Lumens	Efficacy
3000K	52W	8100lm	156lm/W
4000K	52W	8500lm	163lm/W

LIGHT DETAILS - UP/DOWN



CCT	Wattage	Lumens	Efficacy
3000K	66W	10126lm	153lm/W
4000K	66W	10600lm	161lm/W



TECHNICAL SPECIFICATIONS

IP rating	IP40
CRI	>80
Lamp Life	50,000 hours
Light Source	Tridonic LLE LED
Voltage	240V
Driver	High efficiency
LED Warranty	5 Years

HOUSING

Material	Extruded aluminium
Style	Integrated Driver
Finish	Powder coated
Protection Rating	Class 1
Optics	Opal / Microprism
Weight	11.05kg
Mounting	Ceiling plate

An exceptionally high performance range of top quality pendant uplighters specifically designed around the latest high efficiency LED modules from Tridonic/ Osram, offering superb performance up to 163lm/W. Also available with illuminated slot to front of main housing as shown.

Main housing produced from extruded aluminium with integral passive thermal management. All versions supplied with Microprism diffuser for optimum light transmission and visual comfort.

Finished in textured polyester powder coat with standard finishes; White (.X5), Black (.X4), Anthracite (.X3), Silver (.X2) with other BS/RAL colours available to order.



Pendants

the
Opal Bowl
range

A careful balance of contemporary and classic design. The vintage style perfectly suits historic and ornate environments such as museums, heritage buildings and churches.






Product Family		Housing Colour		Version		Suffix
S99239	Opal Bowl Pendant	/05	White	26	3000K 130W	.8
		/04	Black	27	4000K 130W	
		/21	Silver	28	3000K 156W	
				29	4000K 156W	
				24	3000K 182W	
				25	4000K 182W	

EM, dimmable and control options available.
See page 268 for details.

Opal Bowl

Pendant



LIGHT DETAILS



CCT	Wattage	Lumens	Efficacy
3000K	130W	11430lm + 7620lm	146lm/W
4000K	130W	12000lm + 8000lm	154lm/W
3000K	156W	1525lm + 7620lm	146lm/W
4000K	156W	16000lm + 8000lm	154lm/W
3000K	182W	19050lm + 7620lm	146lm/W
4000K	182W	20000lm + 8000lm	154lm/W

A modern chandelier-style pendant, providing both direct and indirect illumination. This classic design has been recently updated to the latest LED technology, ensuring the highest quality and efficiency on the market.

Optional spill-light facility to edge of upper housing with colour gel option (as shown).



TECHNICAL SPECIFICATIONS

IP rating	IP40
CRI	>80
Lamp Life	50,000 hours
Light Source	Tridonic LLE LED
Voltage	240V
Driver	Integrated high efficiency
LED Warranty	5 Years

HOUSING

Material	Opal acrylic and aluminium
Style	Remote / Integrated Driver
Finish	Powder coated
Protection Rating	Class 1
Optics	Opal acrylic
Weight	5KG
Mounting	Wire suspension kit

Opal Bowl Pendant




Pendants

the
Ring
Suspended
range



A dramatic pendant available in four sizes, the Ring Suspended brings attention to architectural space. Ideal for retail, hospitality and lobby areas.




Product Family		Housing Colour		Version		Suffix
S18660	Ring Size 1	.05	White	00	3000K Direct	.8
S18661	Ring Size 2	.04	Black	01	4000K Direct	
S18662	Ring Size 3	.21	Silver	02	3000K Direct/Indirect	
S18663	Ring Size 4			03	4000K Direct/Indirect	

EM, dimmable and control options available.
See page 268 for details.

Ring
Suspended

LIGHT DETAILS - DIRECT




Size	CCT	Wattage	Lumens	Efficacy
Ø600mm	3000K	38W	3391lm	89lm/W
Ø600mm	4000K	38W	3391lm	90lm/W
Ø800mm	3000K	52W	5642lm	89lm/W
Ø800mm	4000K	52W	5652lm	89lm/W
Ø1100mm	3000K	79W	6782lm	90lm/W
Ø1100mm	4000K	79W	6782lm	90lm/W
Ø1450mm	3000K	99W	8478lm	90lm/W
Ø1450mm	4000K	99W	8478lm	90lm/W


The Sovereign Suspended Ring is a sleek new range of suspended downlights and up/downlights. Housed in extruded aluminium, these high quality luminaires are matched by their beautifully uniform emission, utilising the latest LED technology.

Available in a range of sizes and outputs, as well as either Direct or Direct / Indirect.

LIGHT DETAILS - DIRECT/INDIRECT



Size	CCT	Wattage	Lumens	Efficacy
Ø600mm	3000K	38W + 19W	3391lm + 1695lm	89lm/W
Ø600mm	4000K	38W + 19W	3391lm + 1695lm	90lm/W
Ø800mm	3000K	63W + 31.5W	5642lm + 2826lm	89lm/W
Ø800mm	4000K	63W + 31.5W	5652lm + 2826lm	89lm/W
Ø1100mm	3000K	75W + 37.5W	6782lm + 3391lm	90lm/W
Ø1100mm	4000K	75W + 37.5W	6782lm + 3391lm	90lm/W
Ø1450mm	3000K	94W + 47W	8478lm + 4286lm	90lm/W
Ø1450mm	4000K	94W + 47W	8478lm + 4286lm	90lm/W




- Size 1**
ØA = 600mm
ØB = 450mm
C Direct = 80mm,
C Direct/Indirect = 120mm
- Size 2**
ØA = 800mm
ØB = 650mm
C Direct = 80mm,
C Direct/Indirect = 120mm
- Size 3**
ØA = 1100mm
ØB = 950mm
C Direct = 80mm,
C Direct/Indirect = 120mm
- Size 4**
ØA = 1450mm
ØB = 1300mm
C Direct = 80mm,
C Direct/Indirect = 120mm

HOUSING

Material	Extruded aluminium
Finish	Powder coated
Protection Rating	Class 1
Optics	Opal acrylic
Weight	5KG - 15KG
Mounting	Wire suspension kit

TECHNICAL SPECIFICATIONS

IP rating	IP20
CRI	>80
Lamp Life	50,000 hours
Light Source	OSRAM 2835
Voltage	240V
Driver	High efficiency
LED Warranty	5 Years



Pendants

the
**Shallow
Drum**
range



An ideal pendant for providing uniform high output illumination in interior environments, particularly effective in high ceiling spaces. Available in five sizes to suit a range of applications.




Product Family		Housing Colour		CCT		Suffix
S18666	Shallow Drum Direct	.05	White	00	3000K 400mm	.8
S18667	Shallow Drum Direct/Indirect	.04	Black	01	4000K 400mm	
		.21	Silver	02	3000K 600mm	
				03	4000K 600mm	
				04	3000K 800mm	
				05	4000K 800mm	
				06	3000K 1000mm	
				07	4000K 1000mm	
				08	3000K 1200mm	
				09	4000K 1200mm	

EM, dimmable and control options available.
See page 268 for details.

Shallow Drum

Suspended




LIGHT DETAILS - DIRECT

Size	Wattage	Lumens	Efficacy
Ø400mm	28W	2400lm	86lm/W
Ø600mm	50W	4250lm	85lm/W
Ø800mm	78W	6630lm	85lm/W
Ø1000mm	89W	8160lm	92lm/W
Ø1200mm	120W	10200lm	85lm/W


The Sovereign Suspended Shallow Drum is a sleek new range of suspended downlights. Housed in extruded aluminium, these high quality luminaires are matched by their beautifully uniform emission, utilising the latest LED technology and an opal diffuser.

Available in a range of sizes and outputs, as well as either Direct or Direct / Indirect.



LIGHT DETAILS - DIRECT/INDIRECT

Size	Wattage	Lumens	Efficacy
Ø400mm	28W + 28W	4800lm	86lm/W
Ø600mm	50W + 50W	8500lm	86lm/W
Ø800mm	78W + 78W	13260lm	85lm/W
Ø1000mm	89W + 89W	16320lm	92lm/W
Ø1200mm	120W + 120W	20400lm	85lm/W



TECHNICAL SPECIFICATIONS

HOUSING	Material	Extruded aluminium	IP rating	IP20
	Finish	Powder coated	CRI	>80
	Protection Rating	Class 1	Lamp Life	50,000 hours
	Optics	Opal PMMA	Light Source	OSRAM 2835
	Weight	5KG-10KG	CCT	3000K / 4000K
Mounting	Wire suspension kit		Voltage	240V
			Driver	Integrated high efficiency
			LED Warranty	5 Years

Shallow Drum



Pendants



Surface &
Recessed

the
Broadline
ranges

A highly flexible, minimalist range of linear systems, available in surface and recessed variants.

Perfect for clean, elegant lines of illumination, as well as more dramatic shapes and designs thanks to the Broadline's incredibly versatile design.






Product Family		Housing Colour		CCT		Suffix
S18620S	584mm	/X5	Textured white	00	3000K	.8
S18622S	1144mm	/X4	Textured black	01	4000K	
S18623S	1424mm	/X2	Textured silver			
S18624S	1704mm					

EM and dimmable options available - see page 268 for ordering info.

Broadline

Surface Mounted

LIGHT DETAILS



Length	CCT	Wattage	Lumens	Efficacy
584mm	3000K	15W	2350lm	161lm/W
584mm	4000K	15W	2470lm	169lm/W
1144mm	3000K	29W	4700lm	161lm/W
1144mm	4000K	29W	4940lm	169lm/W
1424mm	3000K	37W	5870lm	161lm/W
1424mm	4000K	37W	6170lm	169lm/W
1704mm	3000K	44W	7045lm	161lm/W
1704mm	4000K	44W	7410lm	169lm/W

Note: bespoke lengths available



A beautifully elegant surface mounted linear system, designed around the latest high performance Tridonic LLE LED modules.

Produced in high quality aluminium extruded profile, the Broadline Surface luminaire can be supplied in standard lengths, or custom cut to suit. Also available as individual lengths or joined via plug & socket connection to provide “continuous” runs as required.

Supplied with standard or blind end caps (illustrated opposite), as well as an alternative prismatic diffuser. Get in touch to discuss full customisation options, including custom shapes and angles.

TECHNICAL SPECIFICATIONS

IP rating	IP20
CRI	>80
Lamp Life	50,000 hours
Light Source	Tridonic LLE LED
Voltage	240V
Driver	Integrated high efficiency
LED Warranty	5 Years


HOUSING

Material	Extruded aluminium
Finish	Powder coated
Protection Rating	Class 1
Optics	Opal / Prismatic diffuser
Weight	2.5kg @ 600mm
Mounting	Surface mounting clips

Broadline Surface



Surface & Recessed




Product Family		Housing Colour		CCT		Suffix
S18620IPS	584mm	/X5	Textured white	00	3000K	.8
S18622IPS	1144mm	/X4	Textured black	01	4000K	
S18623IPS	1424mm	/X2		Textured silver		
S18624IPS	1704mm					

EM and dimmable options available - see page 268 for ordering info.

Broadline IP65

Surface Mounted

LIGHT DETAILS



Length	CCT	Wattage	Lumens	Efficacy
584mm	3000K	15W	2350lm	161lm/W
584mm	4000K	15W	2470lm	169lm/W
1144mm	3000K	29W	4700lm	161lm/W
1144mm	4000K	29W	4940lm	169lm/W
1424mm	3000K	37W	5870lm	161lm/W
1424mm	4000K	37W	6170lm	169lm/W
1704mm	3000K	44W	7045lm	161lm/W
1704mm	4000K	44W	7410lm	169lm/W

Note: bespoke lengths available



This IP65 version of the Broadline Surface Mounted allows for installation in exterior environments.

Produced in high quality aluminium extruded profile, the Broadline IP65 Surface luminaire can be supplied in standard lengths, or custom cut to suit.

Can be supplied with an alternative prismatic diffuser. Get in touch to discuss full customisation options.


TECHNICAL SPECIFICATIONS

IP rating	IP65
CRI	>80
Lamp Life	50,000 hours
Light Source	Tridonic LLE LED
Voltage	240V
Driver	Integrated high efficiency
LED Warranty	5 Years


HOUSING

Material	Extruded aluminium
Finish	Powder coated
Protection Rating	Class 1
Optics	Opal / Prismatic diffuser
Weight	2.5kg @ 600mm
Mounting	Surface mounting clips

Broadline IP65 Surface



Surface & Recessed



Product Family		Housing Colour		CCT		Suffix
S18620R	584mm	/X5	Textured white	00	3000K	.8
S18622R	1144mm	/X4	Textured black	01	4000K	
S18623R	1424mm	/X2	Textured silver			
S18624R	1704mm					

EM and dimmable options available - see page 268 for ordering info.



Broadline

Recessed

LIGHT DETAILS

Length	CCT	Wattage	Lumens	Efficacy
584mm	3000K	15W	2350lm	161lm/W
584mm	4000K	15W	2470lm	169lm/W
1144mm	3000K	29W	4700lm	161lm/W
1144mm	4000K	29W	4940lm	169lm/W
1424mm	3000K	37W	5870lm	161lm/W
1424mm	4000K	37W	6170lm	169lm/W
1704mm	3000K	44W	7045lm	161lm/W
1704mm	4000K	44W	7410lm	169lm/W

Note: bespoke lengths available



TECHNICAL SPECIFICATIONS

IP rating	IP20
CRI	>80
Lamp Life	50,000 hours
Light Source	Tridonic LLE LED
Voltage	240V
Driver	Integrated high efficiency
LED Warranty	5 Years

HOUSING


Material	Extruded aluminium
Finish	Powder coated
Protection Rating	Class 1
Optics	Opal / Prismatic diffuser
Weight	2.5kg @ 600mm
Mounting	Wall / Ceiling recessed

The Broadline Recessed allows this linear system to be inset within walls and ceilings, providing a beautifully discrete lighting solution.


Produced in high quality aluminium extruded profile, the Sovereign Broadline Recessed luminaire can be installed individually or joined via plug & socket connection to provide “continuous” runs as required.

A choice of lengths available, including bespoke individual lengths, and cut to custom angles and lengths to match corners or provide dramatic shapes.

Broadline Recessed



Surface & Recessed



Product Family		Housing Colour		CCT		Suffix
S18620IPR	584mm	/X5	Textured white	00	3000K	.8
S18622IPR	1144mm	/X4	Textured black	01	4000K	
S18623IPR	1424mm	/X2 Textured silver				
S18624IPR	1704mm					

EM and dimmable options available - see page 268 for ordering info.



Broadline IP65

Recessed

LIGHT DETAILS

Length	CCT	Wattage	Lumens	Efficacy
584mm	3000K	15W	2350lm	161lm/W
584mm	4000K	15W	2470lm	169lm/W
1144mm	3000K	29W	4700lm	161lm/W
1144mm	4000K	29W	4940lm	169lm/W
1424mm	3000K	37W	5870lm	161lm/W
1424mm	4000K	37W	6170lm	169lm/W
1704mm	3000K	44W	7045lm	161lm/W
1704mm	4000K	44W	7410lm	169lm/W

Note: bespoke lengths available



TECHNICAL SPECIFICATIONS

IP rating	IP65
CRI	>80
Lamp Life	50,000 hours
Light Source	Tridonic LLE LED
Voltage	240V
Driver	Integrated high efficiency
LED Warranty	5 Years

HOUSING

Material	Extruded aluminium
Finish	Powder coated
Protection Rating	Class 1
Optics	Opal / Prismatic diffuser
Weight	2.5kg @ 600mm
Mounting	Ceiling/ wall recessed

The Broadline IP65 Recessed can be installed in exterior environments thanks to the weatherproof design.

Produced in high quality aluminium extruded profile, the Sovereign Broadline IP65 Recessed luminaire is available in a choice of lengths available, including bespoke individual lengths of up to 2mts.





Fire exit

EAST WING



INTERCOM

the
Drum
Downlight
range



Surface mounted downlights available in four sizes. Ideal of retail, commerce and hospitality settings.



Family Code		Beam Angle		Housing Colour		CCT & Output			Suffix
S98609	Drum Downlight	M	Medium 36°	.05	White	02	3000K	24W Size 3	.8
		W	Wide 60°	.04	Black	04	4000K	24W Size 3	
				.21	Silver	05	3000K	40W Size 3	
						06	4000K	40W Size 3	
						10	3000K	12W Size 1	
						11	4000K	12W Size 1	
						12	3000K	15W Size 2	
						13	4000K	15W Size 2	
						21	3000K	10W Size 1	
						22	4000K	10W Size 1	

EM and dimmable options available - see page 268 for ordering info.

Drum Downlight

Surface Downlight

Size 1

Size 2

Size 3

Size 4

CCT	Wattage	Lumens	Efficacy
3000K	10W	820lm	82lm/W
4000K	10W	880lm	88lm/W

CCT	Wattage	Lumens	Efficacy
3000K	15W	1520lm	103lm/W
4000K	15W	1520lm	103lm/W

CCT	Wattage	Lumens	Efficacy
3000K	12W	1380lm	115lm/W
4000K	12W	1380lm	115lm/W

CCT	Wattage	Lumens	Efficacy
3000K	24W	2260lm	94lm/W
4000K	24W	2420lm	101lm/W
3000K	40W	3840lm	96lm/W
4000K	40W	4120lm	103lm/W

TECHNICAL SPECIFICATIONS

IP rating	IP40
CRI	>80
Lamp Life	50,000 hours
Light Source	CREE LED
Voltage	240V
Driver	High efficiency
LED Warranty	5 Years

HOUSING

Material	Aluminium
Finish	Powder coated
Protection Rating	Class 1
Optics	Clear glass
Weight	0.4kg - 2.46kg
Mounting	Surface mounted

LIGHT DETAILS

A high performance range of surface mounted drum luminaires, incorporating the latest CREE LED modules with high efficiency driver for optimum performance and longevity.

Offering impressive lumen packages up to 4120lm and a choice of Warm White or Cool White LED colour temperature. Die-cast aluminium main housing with high purity aluminium faceted reflector system for added aesthetic appeal.

All 15W-40W versions are supplied complete with high efficiency driver as standard, with dimming & Remote Emergency options also available. Smaller 10W and 12W versions are supplied with remote driver.

Drum Downlight




Surface & Recessed

the
Round
ranges



Versatile luminaires available in recessed and surface mounted designs. Ideal alternative for ceiling panels or even as surface mounted wall lights.




Product Family		Housing Colour		CCT		Suffix
S18636	Round Size 1	.05	White	06	3000K	.8
S18637	Round Size 2	.04	Black	07	4000K	
S18638	Round Size 3	.21	Silver			

EM and dimmable options available - see page 268 for ordering info.


Round

Surface Downlight



LIGHT DETAILS

Size	Wattage	CCT	Lumens	Efficacy
400mm	30W	3000K	2500lm	83lm/W
400mm	30W	4000K	2700lm	90lm/W
500mm	40W	3000K	3600lm	90lm/W
500mm	40W	4000K	3800lm	95lm/W
600mm	48W	3000K	4500lm	94lm/W
600mm	48W	4000K	4800lm	100lm/W



These exceptionally slim circular units provide high levels of illumination with a pleasingly soft appearance. With its minimally elegant design, the Round Surface Panels offer a discrete yet distinctive solution for both ceiling downlighting and as wall mounted luminaires.

Supplied complete with standard high efficiency driver, but can also be specified with dimmable drivers to suit any dimming protocol. EM versions also available, with all components located within the spun aluminium rear gear housing for ease of installation.

TECHNICAL SPECIFICATIONS

IP rating	IP40
CRI	>80
Lamp Life	50,000 hours
Light Source	Side Emitting SMD
Voltage	240V
Driver	High efficiency
LED Warranty	5 Years

HOUSING

Material	Spun aluminium
Finish	Powder coated
Protection Rating	Class 1
Optics	Opal diffuser
Weight	3.5kg - 5.8kg
Mounting	Surface mounted

Round Surface



Surface & Recessed




Product Family		Housing Colour		CCT		Suffix
S18636	Round Size 1	.05	White	04	3000K	.8
S18637	Round Size 2	.04	Black	05	4000K	
S18638	Round Size 3	.21	Silver			

EM and dimmable options available - see page 268 for ordering info.


Round

Recessed Downlight

LIGHT DETAILS



Size	Wattage	CCT	Lumens	Efficacy
400mm	30W	3000K	2500lm	83lm/W
400mm	30W	4000K	2700lm	90lm/W
500mm	40W	3000K	3600lm	90lm/W
500mm	40W	4000K	3800lm	95lm/W
600mm	48W	3000K	4500lm	94lm/W
600mm	48W	4000K	4800lm	100lm/W



TECHNICAL SPECIFICATIONS

IP rating	IP40
CRI	>80
Lamp Life	50,000 hours
Light Source	Side Emitting SMD
Voltage	240V
Driver	High efficiency
LED Warranty	5 Years

HOUSING

Material	Spun aluminium
Finish	Powder coated
Protection Rating	Class 1
Optics	Opal diffuser
Weight	3.5kg - 5.8kg
Mounting	Recessed with springs

With its minimally elegant design, the Round Recessed Panels offer a discrete yet distinctive solution for ceiling downlighting, as well as a great alternative to the classic square panels in panelled ceiling structures.

Supplied complete with standard high efficiency driver, but can also be specified with dimmable drivers to suit any dimming protocol. EM versions also available, with all components located within the spun aluminium rear gear housing for ease of installation.

Round Recessed



Surface & Recessed

the
**Shallow
Drum**
range



A clean, subtle luminaire providing a soft and uniform down lighting function. Ideal for retail, office and hospitality applications.




Product Family		Housing Colour		CCT		Suffix
S18666S	Shallow Drum	.05	Textured white	00	3000K 400mm	.8
		.04	Textured black	01	4000K 400mm	
		.21	Textured silver	02	3000K 600mm	
				03	4000K 600mm	
				04	3000K 800mm	
				05	4000K 800mm	
				06	3000K 1000mm	
				07	4000K 1000mm	
				08	3000K 1200mm	
				09	4000K 1200mm	

EM and dimmable options available - see page 268 for ordering info.

Shallow Drum

Surface Downlight




LIGHT DETAILS

Size	Wattage	Lumens	Efficacy
Ø400mm	28W	2400lm	86lm/W
Ø600mm	50W	4250lm	85lm/W
Ø800mm	78W	6630lm	85lm/W
Ø1000mm	89W	8160lm	92lm/W
Ø1200mm	120W	10200lm	85lm/W

The Sovereign Shallow Drum Surface is a sleek new range of surface mounted downlights. Housed in extruded aluminium, these high quality luminaires are matched by their beautifully uniform emission, utilising the latest LED technology and an opal diffuser.

Available in a range of sizes and outputs.



TECHNICAL SPECIFICATIONS

IP rating	IP20
CRI	>80
Lamp Life	50,000 hours
Light Source	OSRAM 2835
CCT	3000K / 4000K
Voltage	240V
Driver	Integrated high efficiency
LED Warranty	5 Years


HOUSING

Material	Extruded aluminium
Finish	Powder coated
Protection Rating	Class 1
Optics	Opal diffuser
Weight	5KG-10KG
Mounting	Surface mounted


Shallow Drum Surface

Surface & Recessed

the
**Universal
Panel**
range



A perfect replacement for fluorescent modular luminaires of a much higher wattage, thus creating the opportunity for even greater energy savings.



Product Family		Housing Colour		Version		Suffix
S18333	Universal	.05	White	11	4200K	.8
		.04	Black			
		.21	Silver			



EM and dimmable options available - see page 268 for ordering info.

Universal Panel

Recessed Downlight

LIGHT DETAILS

Wattage	CCT	Lumens	Efficacy
36W	4200K	3600lm	100lm/W



An ultra slim and highly efficient LED panel using the latest 2835 SMD LED's and high quality optical lens to provide exceptionally even illumination.

Supplied with high efficiency remote power supply with simple plug & play connection. May be specified with dimmable driver to suit DALI, 1-10V etc and can also be supplied with remote emergency pack.

Ultra slim frame in anodised extruded aluminium, powder coated in white finish as standard.

TECHNICAL SPECIFICATIONS

IP rating	IP40
CRI	>80
Lamp Life	50,000 hours
Light Source	2835 SMD
Voltage	240V
Driver	High efficiency
LED Warranty	5 Years


HOUSING

Material	Aluminium
Finish	Powder coated
Protection Rating	Class 1
Optics	Opalised diffuser
Weight	0.6kg
Mounting	Ceiling Recessed

Universal Panel

Surface & Recessed






Interior
Wall Lights

the
Linear
wall light ranges

Beautiful, elegant wall lights providing high quality illumination. Available as an uplight or downlight, or as an up/downlight.






Product Family		Housing Colour		CCT		Suffix
S18510	150mm	/X5	Textured white	00	3000K	.8
S18511	300mm	/X4	Textured black	01	4000K	
S18512	450mm	/X2	Textured silver			
S18513	600mm					


EM and dimmable options available - see page 268 for ordering info.

Linear Mono

Wall Light



Size	Wattage	CCT	Lumens	Efficacy
150mm	4.3W	3000K	692lm	160lm/W
150mm	4.3W	4000K	728lm	167lm/W
300mm	8.6W	3000K	1384lm	160lm/W
300mm	8.6W	4000K	1455lm	167lm/W
450mm	13W	3000K	2076lm	160lm/W
450mm	13W	4000K	2182lm	167lm/W
600mm	17.3W	3000K	2768lm	160lm/W
600mm	17.3W	4000K	2910lm	167lm/W



TECHNICAL SPECIFICATIONS

IP rating	IP40
CRI	>80
Lamp Life	50,000 hours
Light Source	Tridonic LLE
Voltage	240V
Driver	High efficiency
LED Warranty	5 Years

HOUSING

Material	Extruded aluminium
Finish	Powder coated
Protection Rating	Class 1
Optics	Opal diffuser
Weight	1.5kg
Mounting	Surface Mounted


The Sovereign Linear Mono Wall Light borrows the beautifully sleek, minimal design of the Sovereign Broadline range. Utilising the latest LED technology ensures the highest quality and efficiency on the market.

Available in a range of sizes and outputs. Providing either uplighting or downlighting, the Wall Light is also available as an up/downlight under the Sovereign Duo Profile Wall Light range.

Fitted with integral electronic control gear as standard, with dimming & EM versions (remote) also available.

Linear Mono






Product Family		Housing Colour		CCT		Suffix
S18514	150mm	/X5	Textured white	00	3000K	.8
S18515	300mm	/X4	Textured black	01	4000K	
S18516	450mm	/X2		Textured silver		
S18517	600mm					


Remote EM and dimmable options available - see page 268 for ordering info.

Linear Duo

Wall Light



Size	Wattage	CCT	Lumens	Efficacy
150mm	10W	3000K	692 + 692lm	160lm/W
150mm	10W	4000K	727 + 727lm	167lm/W
300mm	17.3W	3000K	1384 1384lm	160lm/W
300mm	17.3W	4000K	1455 + 1455lm	167lm/W
450mm	26W	3000K	2076 2076lm	160lm/W
450mm	26W	4000K	2182 2182lm	167lm/W
600mm	33.1W	3000K	2624 + 2624lm	160lm/W
600mm	33.1W	4000K	2760 + 276lm	167lm/W



TECHNICAL SPECIFICATIONS

IP rating	IP40
CRI	>80
Lamp Life	50,000 hours
Light Source	Tridonic LLE
Voltage	240V
Driver	High efficiency
LED Warranty	5 Years

HOUSING

Material	Extruded aluminium
Finish	Powder coated
Protection Rating	Class 1
Optics	Opal diffuser
Weight	1.5kg
Mounting	Surface Mounted


The Sovereign Linear Duo Wall Light borrows the beautifully sleek, minimal design of the Sovereign Broadline design.

Utilising the latest LED technology ensures the highest quality and efficiency on the market. Available in a range of sizes and outputs.

Providing both up and downlighting, the Wall Light is also available as either an up or downlight under the Sovereign Linear Mono range. Fitted with integral electronic control gear as standard, with dimming & EM versions (remote) also available.

Linear Duo






Product Family		Housing Colour		Version		Suffix
S98612	Slim Uplight	.05	White	00	3000K Up/down	.8
		.04	Black	01	4000K Up/down	
		.21	Silver	02	3000K Uplight	
				03	4000K Uplight	

EM and dimmable options available - see page 268 for ordering info.


Slim Uplight

Wall Light




LIGHT DETAILS

Wattage	CCT	Lumens	Efficacy
39W	3000K	5968lm	154lm/W
39W	4000K	6245lm	161lm/W



Wattage	CCT	Lumens	Efficacy
49W	3000K	5968 + 1326lm	154lm/W + 134lm/W
39W	4000K	6245 + 1388lm	161lm/W + 140lm/W



TECHNICAL SPECIFICATIONS

IP rating	IP40
CRI	>80
Lamp Life	50,000 hours
Light Source	Tridonic LLE
Voltage	240V
Driver	High efficiency
LED Warranty	5 Years

HOUSING


Material	Spun aluminium
Finish	Powder coated
Protection Rating	Class 1
Optics	Microprism
Weight	2.1kg
Mounting	Surface mounted

Taking our highly successful Slim Profile range into the future by completely re-designing the internal structure and incorporating the very latest Tridonic LLE range of high performance LED modules & drivers offering efficiency of over 140 lm/W.

Available in either uplight only or also available with downlight facility provided by separate LLE module located within the wall box. Emergency versions of the downlight version are also available.

All versions incorporate integral high efficiency non-dimmable drivers as standard, but can also be specified in any dimmable format.





the
Cube
Wall Light
range

High output wall light with a classic design.
Ideal for larger interior applications.





Family		Beam		Housing Colour		Version		Suffix
S98864	Cube Up/Down	FLFL	Flood up & down	.05	White	01	3000K 25.24W	.8
		SPFL	Spot up / flood down	.04	Black	02	4000K 25.24W	
				.21	Silver	03	3000K 36.84W	
						04	4000K 36.84W	

EM and dimmable options available - see page 268 for ordering info.


Cube Up/Down

Wall Light

Wattage	CCT	Lumens	Efficacy
25.24W	3000K	1932lm x 2	153lm/W
25.24W	4000K	1932lm x 2	157lm/W
36.84W	3000K	2745lm x 2	149lm/W
36.84W	4000K	2837lm x 2	154lm/W

Designed to complement our existing ranges of wall lights, this Cube Up/Downlight is the LED version of our popular classic CFL design, perfect for larger interior projects including churches, community halls etc.

Available in 3000K or 4000K, and in a range of outputs. Also available as up or downlight on request.



TECHNICAL SPECIFICATIONS

IP rating	IP20
CRI	>80
Lamp Life	50,000 hours
Light Source	SLE
Voltage	240V
Driver	High efficiency
LED Warranty	5 Years

HOUSING

Material	Aluminium
Finish	Powder coated
Protection Rating	Class 1
Optics	Glass
Weight	4.75kg
Mounting	Surface Mounted

Cube Up/Down




Wall Lights

the
Ecoblade
wall light ranges

The Sovereign Ecoblade range is the result of extensive research and development by Commercial Lighting Systems. Matching a minimalist style with impressive efficiency and illumination makes the Ecoblade ideal for office environments.





Product Family		Housing Colour		CCT & Output		Suffix
S18541	Ecoblade Uplight	.X5	Textured White	04S	3000K 300mm	.8
S18542	Ecoblade Slot Uplight	.X4	Textured Black	05S	4000K 300mm	
		.X2	Textured Silver	04	3000K 400mm	
				05	4000K 400mm	
				00	3000K 600mm	
				01	4000K 600mm	
				08	3000K 900mm	
				09	4000K 900mm	



EM and dimmable options available - see page 268 for ordering info.

Ecoblade Uplight

Wall Light

LIGHT DETAILS

Size	Wattage	CCT	Lumens	Efficacy
300mm	13W	3000K	2030lm	156lm/W
300mm	13W	4000K	2120lm	163lm/W
400mm	13W	3000K	2030lm	156lm/W
400mm	13W	4000K	2120lm	163lm/W
600mm	26W	3000K	4050lm	156lm/W
600mm	26W	4000K	4240lm	163lm/W
900mm	39W	3000K	6080lm	156lm/W
900mm	39W	4000K	6360lm	163lm/W



TECHNICAL SPECIFICATIONS

IP rating	IP40
CRI	>80
Lamp Life	50,000 hours
Light Source	Tridonic LLE
Voltage	240V
Driver	High efficiency
LED Warranty	5 Years

HOUSING


Material	Extruded aluminium
Finish	Textured powder coated
Protection Rating	Class 1
Optics	Microprism
Weight	2.5kg - 5.4kg
Mounting	Surface mounted


A range of exceptionally high performance, top quality wall mounted uplighters, specifically designed around the latest high efficiency Tridonic LLE modules, offering superb performance of up to 163lm/W. Available in a range of styles with an additional front

Main housing produced from extruded aluminium with integral passive thermal management. All versions supplied with Microprism diffuser for optimum light transmission and visual comfort.

Finished in textured polyester powder coat with standard finishes in white, black and silver, with other BS/RAL colours available to order.

Ecoblade Uplight





Product Family		Housing Colour		CCT & Output		Suffix
S18541	Ecoblade	.X5	Textured White	06	3000K 400mm	.8
S18542	Ecoblade Slot	.X4	Textured Black	07	4000K 400mm	
		.X2	Textured Silver	02	3000K 600mm	
				03	4000K 600mm	
				10	3000K 900mm	
				11	4000K 900mm	



EM and dimmable options available - see page 268 for ordering info.

Ecoblade Up/Down

Wall Light

LIGHT DETAILS

Size	Wattage	CCT	Lumens	Efficacy
400mm	20W	3000K	3043lm	152lm/W
400mm	20W	4000K	3180lm	159lm/W
600mm	33W	3000K	5063lm	153lm/W
600mm	33W	4000K	5300lm	161lm/W
900mm	52W	3000K	8105lm	156lm/W
900mm	52W	4000K	8479lm	163lm/W



TECHNICAL SPECIFICATIONS

IP rating	IP40
CRI	>80
Lamp Life	50,000 hours
Light Source	Tridonic LLE
Voltage	240V
Driver	High efficiency
LED Warranty	5 Years

HOUSING

Material	Extruded aluminium
Finish	Textured powder coated
Protection Rating	Class 1
Optics	Microprism
Weight	2.5 - 5.4kg
Mounting	Surface mounted


A range of exceptionally high performance, top quality wall mounted uplighters, specifically designed around the latest high efficiency Tridonic LLE modules, offering superb performance of up to 163lm/W. Available in a range of styles including uplight only or up/downlight.

Main housing produced from extruded aluminium with integral passive thermal management. All versions supplied with Microprism diffuser for optimum light transmission and visual comfort.

Finished in textured polyester powder coat with standard finishes in white, black and silver, with other BS/RAL colours available to order.



Wall Lights




Product Family		Housing Colour		CCT & Output		Suffix
S18540	Ecoblade Wedge	.X5	Textured White	04S	3000K 300mm Uplight	.8
			Textured Black	05S	4000K 300mm Uplight	
			Textured Silver	04	3000K 400mm Uplight	
		.X4		05	4000K 400mm Uplight	
				00	3000K 600mm Uplight	
				01	4000K 600mm Uplight	
		.X2		08	3000K 900mm Uplight	
				09	4000K 900mm Uplight	
				06	3000K 400mm Up/Down	
		.X1		07	4000K 400mm Up/Down	
				02	3000K 600mm Up/Down	
				03	4000K 600mm Up/Down	
		.X0		10	3000K 900mm Up/Down	
				11	4000K 900mm Up/Down	

EM and dimmable options available - see page 268 for ordering info.


Ecoblade Wedge

Wall Light


LIGHT DETAILS



Size	Wattage	CCT	Lumens	Efficacy
300mm	13W	3000K	2030lm	156lm/W
300mm	13W	4000K	2120lm	163lm/W
400mm	13W	3000K	2030lm	156lm/W
400mm	13W	4000K	2120lm	163lm/W
600mm	26W	3000K	4050lm	156lm/W
600mm	26W	4000K	4240lm	163lm/W
900mm	39W	3000K	6080lm	156lm/W
900mm	39W	4000K	6360lm	163lm/W



Size	Wattage	CCT	Lumens	Efficacy
400mm	20W	3000K	3043lm	152lm/W
400mm	20W	4000K	3180lm	159lm/W
600mm	33W	3000K	5063lm	153lm/W
600mm	33W	4000K	5300lm	161lm/W
900mm	52W	3000K	8105lm	156lm/W
900mm	52W	4000K	8479lm	163lm/W



TECHNICAL SPECIFICATIONS

IP rating	IP40
CRI	>80
Lamp Life	50,000 hours
Light Source	Tridonic LLE
Voltage	240V
Driver	High efficiency
LED Warranty	5 Years

HOUSING

Material	Extruded aluminium
Finish	Textured powder coated
Protection Rating	Class 1
Optics	Microprism
Weight	2.5 - 5.4kg
Mounting	Surface mounted

A range of exceptionally high performance, top quality wall mounted uplighters, specifically designed around the latest high efficiency Tridonic LLE modules, offering superb performance of up to 163lm/W. Available in a range of styles including uplight only or up/ downlight.

Main housing produced from extruded aluminium with integral passive thermal management. All versions supplied with Microprism diffuser for optimum light transmission and visual comfort.


Finished in textured polyester powder coat with standard finishes in white, black and silver, with other BS/RAL colours available to order.



the
**Slimline
Square**
range

An elegant wall or ceiling surface mounted luminaire, providing soft even light through the two oval diffusers.





Product Family		Housing Colour		CCT		Suffix
S98955	Slimline Square	.05	White	00	3000K	.8
		.04	Black	01	4000K	
		.21	Silver			

EM and dimmable options available - see page 268 for ordering info.

Slimline Square

Wall Light


LIGHT DETAILS

Wattage	CCT	Lumens	Efficacy
12.5W	3000K	1600lm	133lm/W
12.5W	4000K	1730lm	138lm/W

Our Sovereign Slimline Square is an ideal product for both interior ceiling and wall-mounted applications. Utilising the latest Tridonic QLE LED modules, the Slimline Square offers competitive LED efficacy and the most up-to-date specifications. It's clean and elegant steel design is a statement of quality and durability, with the subtle polycarbonate opal diffusers providing a soft and even light.

The Sovereign Slimline Square is supplied with an integrated high efficiency driver as standard, but can also be specified with dimmable drivers to suit any dimming protocol.

EM versions and corridor functions are also available, while the housing can be powder-coated to any colour, with black, white and silver as standard.




TECHNICAL SPECIFICATIONS

IP rating	IP40
CRI	>80
Lamp Life	50,000 hours
Light Source	Tridonic QLE
Voltage	240V
Driver	High efficiency
LED Warranty	5 Years

HOUSING

Material	Steel
Finish	Powder coated
Style	Alternative front cover options
Protection Rating	Class 1
Optics	Opal diffuser
Weight	5.5kg
Mounting	Surface mounted

Slimline Square



Wall Lights

the
Round
wall light ranges

A beautiful, minimal luminaire available in surface and recessed versions. Our Pizza range offers alternative designs with more subtle illumination outputs.





Product Family		Housing Colour		CCT		Suffix
S18636	Round Size 1	.05	White	06	3000K	.8
S18637	Round Size 2	.04	Black	07	4000K	
S18638	Round Size 3	.21	Silver			



EM and dimmable options available - see page 268 for ordering info.

Round Surface

Wall Light

LIGHT DETAILS

Size	Wattage	CCT	Lumens	Efficacy
405mm	30W	3000K	2500lm	83lm/W
405mm	30W	4000K	2700lm	90lm/W
493mm	40W	3000K	3600lm	90lm/W
493mm	40W	4000K	3800lm	95lm/W
600mm	48W	3000K	4500lm	94lm/W
600mm	48W	4000K	4800lm	100lm/W



TECHNICAL SPECIFICATIONS

IP rating	IP40
CRI	>80
Lamp Life	50,000 hours
Light Source	Side Emitting SMD
Voltage	240V
Driver	High efficiency
LED Warranty	5 Years

HOUSING

Material	Spun aluminium
Finish	Powder coated
Protection Rating	Class 1
Optics	Opal diffuser
Weight	3.5kg - 5.8kg
Mounting	Surface mounted

These exceptionally slim circular units provide high levels of illumination with a pleasingly soft appearance. With its minimally elegant design, the Round Surface Panels offer a discrete yet distinctive solution for both ceiling downlighting and as wall mounted luminaires.

Supplied complete with standard high efficiency driver, but can also be specified with dimmable drivers to suit any dimming protocol. EM versions also available, with all components located within the spun aluminium rear gear housing for ease of installation.

Round Surface



Wall Lights



Product Family		Bezel Colour		CCT		Suffix
S18820	Pizza	.05	White	00	Size 1 3000K	.8
		.04	Black	01	Size 1 4000K	
		.21	Silver	02	Size 2 3000K	
				03	Size 2 4000K	


EM and dimmable options available - see page 268 for ordering info.

Pizza Surface

Wall Light


LIGHT DETAILS - DIRECT

Wattage	CCT	Lumens	Efficacy
9.5W	3000K	1535lm	161lm/W
9.5W	4000K	1606lm	168lm/W
15W	3000K	2477lm	165lm/W
15W	4000K	2592lm	173lm/W



A traditionally designed and produced circular luminaire available in two sizes and designs.

The spun aluminium housing incorporates an integrated metal geartray for optimal heat dissipation, with the polycarbonate front diffuser providing a balanced indirect light output. Larger version featuring a frameless full diameter injection-moulded polycarbonate housing.



TECHNICAL SPECIFICATIONS

IP rating	IP40
CRI	>80
Lamp Life	50,000 hours
Light Source	Tridonic CLE
Voltage	240V
Driver	High efficiency
LED Warranty	5 Years

HOUSING

Material	Spun aluminium (size 1) / polycarb (size 2)
Finish	Powder coated
Protection Rating	Class 1
Optics	Opal diffuser
Weight	1.4kg (size 1) / 2kg (size 2)
Mounting	Surface mounted

Pizza Surface



Wall Lights

the
**Exterior
Bulkhead**
range

An attractive and robust solution for walkway, tunnel, car park and storage area illumination.





Product Family		Bezel Colour		Style		Suffix
S78336	Exterior Bulkhead	.05	White	00	9.5W 3000K Plain	.8
		.04	Black	01	9.5W 4000K Plain	
				02	17W 3000K Plain	
				03	9.5W 3000K Plain	
				04	9.5W 3000K Eyelid	
				05	9.5W 4000K Eyelid	
				06	17W 3000K Eyelid	
				07	17W 4000K Eyelid	



EM and dimmable options available - see page 268 for ordering info.

Exterior Bulkhead

Wall Light

LIGHT DETAILS

Wattage	CCT	Lumens	Efficacy
9.5W	3000K	1530lm	160lm/W
9.5W	4000K	1600lm	169lm/W
17W	3000K	2540lm	158lm/W
17W	4000K	2660lm	158lm/W



TECHNICAL SPECIFICATIONS

IP rating	IP65
CRI	>80
Lamp Life	50,000 hours
Light Source	Tridonic SLE
Voltage	240V
Driver	High efficiency
LED Warranty	5 Years

HOUSING

Material	Die-cast aluminium
Style	Plain / eyelid
Finish	Textured powder coated
Protection Rating	Class 1
Optics	Polycarbonate opal diffuser
Weight	2.5kg - 5.4kg
Mounting	Surface mounted

With its IP65 rating the Bulkhead is ideal for exterior applications. Available in various outputs and colour temperatures.

Available in both a standard and eyelid design.

Exterior Bulkhead



Wall Lights

the
Spun Aluminium
wall light ranges

Our classic spun aluminium wall light ranges have maintained their prominent place in the Sovereign catalogue through constant updates. Utilising the latest technology, these timeless designs provide high quality illumination with excellent efficiency.





Product Family		Housing Colour		Version		Suffix
S18506	Saturn	.05	White	00	3000K 56W	.8
		.04	Black	01	4000K 56W	
		.21	Silver	02	3000K 84W	
				03	4000K 84W	



EM and dimmable options available - see page 268 for ordering info.

Saturn

Wall Light

LIGHT DETAILS - DIRECT

Wattage	CCT	Lumens	Efficacy
56W	3000K	7640 + 640lm	146lm/W
56W	4000K	8000 + 670lm	154lm/W
84W	3000K	11460 + 640lm	146lm/W
84W	4000K	1200 + 670lm	154lm/W



A classic Sovereign design updated to the latest LED technology, the Sovereign Saturn Up/Downlight provides high quality, energy efficient lighting for interior environments.

Subtly offset from the wall, the Saturn's design offers both the main uplighting, as well as a downlight facility from a secondary light source integrated within the wall box.

The Saturn's microprism diffuser generates a pleasingly soft and uniform spread, while the high-purity aluminium spun housing ensures quality and product longevity. Integral control gear as standard.

TECHNICAL SPECIFICATIONS

IP rating	IP20
CRI	>80
Lamp Life	50,000 hours
Light Source	Tridonic LLE
Voltage	240V
Driver	High efficiency
LED Warranty	5 Years

HOUSING

Material	Spun aluminium
Finish	Powder coated
Protection Rating	Class 1
Optics	Microprism
Weight	2.1kg
Mounting	Surface mounted

Saturn

Wall Lights



Product Family		Housing Colour		CCT		Suffix
S18552	Mini QS Up	.05	White	00	3000K	.8
		.04	Black	01	4000K	
		.21	Silver			


EM and dimmable options available - see page 268 for ordering info.

Mini QS Uplight

Wall Light


LIGHT DETAILS

Wattage	CCT	Lumens	Efficacy
8.7W	3000K	1280lm	147lm/W
8.7W	4000K	1340lm	153lm/W



A classic design updated to the latest LED technology, this Sovereign Mini Quartersphere provides uplight illumination with the microprism diffuser generating a pleasingly uniform spread. Main housing produced from high purity aluminium with integral control gear fitted as standard.

The Sovereign Mini Quartersphere is also available as an up/downlight (Product Code S18552), see next page for details.



TECHNICAL SPECIFICATIONS

IP rating	IP20
CRI	>80
Lamp Life	50,000 hours
Light Source	Tridonice LLE
Voltage	240V
Driver	High efficiency
LED Warranty	5 Years

HOUSING

Material	Spun aluminium
Finish	Powder coated
Protection Rating	Class 1
Optics	Microprism
Weight	1.2kg
Mounting	Surface mounted

Mini QS Uplight

Wall Lights



Product Family		Housing Colour		CCT		Suffix
S18551	Mini QS Up/down	.05	White	00	3000K	.8
		.04	Black	01	4000K	
		.21	Silver			


EM and dimmable options available - see page 268 for ordering info.

Mini QS Up/Down

Wall Light


LIGHT DETAILS

Wattage	CCT	Lumens	Efficacy
10.9W	3000K	1280lm + 320lm	147lm/W
10.9W	4000K	1340lm + 330lm	153lm/W



A classic design updated to the latest LED technology, this Sovereign Mini Quartersphere provides up and downlight illumination with the microprism diffuser generating a pleasingly uniform spread. Main housing produced from high purity aluminium with integral control gear fitted as standard.

The Sovereign Mini Quartersphere is also available as an uplight only (Product Code S18550), see previous page for more details.



TECHNICAL SPECIFICATIONS

IP rating	IP20
CRI	>80
Lamp Life	50,000 hours
Light Source	Tridonice LLE
Voltage	240V
Driver	High efficiency
LED Warranty	5 Years

HOUSING

Material	Spun aluminium
Finish	Powder coated
Protection Rating	Class 1
Optics	Microprism
Weight	1.2kg
Mounting	Surface mounted



Wall Lights



Product Family		Housing Colour		Version		Suffix
S18500	Quarter Sphere	.05	White	00	3000K 26.2W	.8
		.04	Black	01	4000K 26W	
		.21	Silver	02	3000K 39.2W	
				03	4000K 39W	


EM and dimmable options available - see page 268 for ordering info.

Quarter Sphere

Wall Light


LIGHT DETAILS

Wattage	CCT	Lumens	Efficacy
26.2W	3000K	3820lm	146lm/W
26W	4000K	4000lm	154lm/W
39.2W	3000K	5730lm	146lm/W
39W	4000K	6000lm	154lm/W



A high quality fully adjustable recessed downlight, allowing a 360° rotation and 45° tilt. An updated version of a mainstay of the Sovereign range, the Scoop utilises the most up-to-date LED technology to ensure optimum efficiency and light quality.

Available in any BS / RAL colour, with dimmable and emergency variants available. Offered with either 3000K or 4000k colour temperature



TECHNICAL SPECIFICATIONS

IP rating	IP20
CRI	>80
Lamp Life	50,000 hours
Light Source	Tridonic LLE
Voltage	240V
Driver	High efficiency
LED Warranty	5 Years

HOUSING

Material	Spun aluminium
Finish	Powder coated
Protection Rating	Class 1
Optics	Microprism
Weight	2.1 kg
Mounting	Surface mounted

Quarter Sphere



Wall Lights



Interior

Free Standing



Product Family		Housing Colour		CCT		Suffix
S18741	Ecoblade Freestanding	/X5	Textured white	00	3000K 52W UPLIGHT	.8
		/X4	Textured black	01	4000K 52W UPLIGHT	
		/X2	Textured silver	02	3000K 66W UP / DOWN	
				03	4000K 66W UP/DOWN	

EM and dimmable options available - see page 268 for ordering info.

Ecoblade


Free Standing Light

LIGHT DETAILS - UP




CCT	Wattage	Lumens	Efficacy
3000K	52W	8100lm	156lm/W
4000K	52W	8500lm	163lm/W

LIGHT DETAILS - UP/DOWN



CCT	Wattage	Lumens	Efficacy
3000K	66W	10126lm	153lm/W
4000K	66W	10600lm	161lm/W




TECHNICAL SPECIFICATIONS	
IP rating	IP40
CRI	>80
Lamp Life	50,000 hours
Light Source	Tridonic LLE LED
Voltage	240V
Driver	High efficiency
LED Warranty	5 Years

HOUSING	
Material	Extruded aluminium
Style	Integrated Driver
Finish	Powder coated
Protection Rating	Class 1
Optics	Microprism
Weight	24kg
Mounting	Free standing

Main housing produced from extruded aluminium with integral passive thermal management. All versions supplied with Nano/Microprism diffuser for optimum light transmission and visual comfort.

Finished in textured polyester powder coat with standard finishes; White (.X5), Black (.X4), Anthracite (.X3), Silver (.X2) with other BS/RAL colours available to order.





Product Family		Housing Colour		CCT		Suffix
S18742	Ecoblade Slot	/X5	Textured white	00	3000K 52W UPLIGHT	.8
		/X4	Textured black	01	4000K 52W UPLIGHT	
		/X2	Textured silver	02	3000K 66W UP / DOWN	
				03	4000K 66W UP/DOWN	

EM and dimmable options available - see page 268 for ordering info.

Ecoblade Slot


Free Standing Light

LIGHT DETAILS - UP




CCT	Wattage	Lumens	Efficacy
3000K	52W	8100lm	156lm/W
4000K	52W	8500lm	163lm/W

LIGHT DETAILS - UP/DOWN



CCT	Wattage	Lumens	Efficacy
3000K	66W	10126lm	153lm/W
4000K	66W	10600lm	161lm/W



TECHNICAL SPECIFICATIONS	
IP rating	IP40
CRI	>80
Lamp Life	50,000 hours
Light Source	Tridonic LLE LED
Voltage	240V
Driver	High efficiency
LED Warranty	5 Years

HOUSING	
Material	Extruded aluminium
Style	Integrated Driver
Finish	Powder coated
Protection Rating	Class 1
Optics	Microprism
Weight	24kg
Mounting	Free standing

Main housing produced from extruded aluminium with integral passive thermal management. All versions supplied with Nano/Microprism diffuser for optimum light transmission and visual comfort.

Finished in textured polyester powder coat with standard finishes; White (/X5), Black (/X4), Anthracite (/X3), Silver (/X2) with other BS/RAL colours available to order.






Product Family		Housing Colour		CCT		Suffix
S18740	Ecoblade Wedge	/X5	Textured white	00	3000K 52W UPLIGHT	.8
		/X4	Textured black	01	4000K 52W UPLIGHT	
		/X2	Textured silver	02	3000K 66W UP / DOWN	
				03	4000K 66W UP/DOWN	

EM and dimmable options available - see page 268 for ordering info.


Ecoblade Wedge

Free Standing Light




LIGHT DETAILS - UP

CCT	Wattage	Lumens	Efficacy
3000K	52W	8100lm	156lm/W
4000K	52W	8500lm	163lm/W



LIGHT DETAILS - UP/DOWN

CCT	Wattage	Lumens	Efficacy
3000K	66W	10126lm	153lm/W
4000K	66W	10600lm	161lm/W



TECHNICAL SPECIFICATIONS

IP rating	IP40
CRI	>80
Lamp Life	50,000 hours
Light Source	Tridonic LLE LED
Voltage	240V
Driver	High efficiency
LED Warranty	5 Years


HOUSING

Material	Extruded aluminium
Style	Integrated Driver
Finish	Powder coated
Protection Rating	Class 1
Optics	Microprism
Weight	24kg
Mounting	Free standing

Ecoblade Wedge Freestanding



Free Standing



Product Family		Housing Colour		CCT		Suffix
S18707	Saturn Freestanding	/05	White	00	3000K 52W	.8
		/04	Black	01	4000K 52W	
		/21	Silver	02	3000K 90W	
				03	4000K 90W	

EM and dimmable options available - see page 268 for ordering info.

Saturn

Free Standing Light


LIGHT DETAILS

CCT	Wattage	Lumens	Efficacy
3000K	52W	8156lm	157lm/W
4000K	52W	8576lm	165lm/W
3000K	90W	14034lm	156lm/W
4000K	90W	14757lm	164lm/W

Originally designed around high power metal halide light sources, our Saturn style free standing uplighter has been a popular choice with its timeless design, and has now been completely updated using the very latest LED technology.

Available as standard in a choice of two outputs, with the lower output version ideal for ceiling heights up to 2.8mts.

All versions supplied with lead and standard 13A moulded plug with pole mounted on/off switch for added convenience.




TECHNICAL SPECIFICATIONS

IP rating	IP40
CRI	>80
Lamp Life	50,000 hours
Light Source	Tridonic LLE LED
Voltage	240V
Driver	High efficiency
LED Warranty	5 Years

HOUSING

Material	Spun aluminium
Style	Integrated Driver
Finish	Powder coated
Protection Rating	Class 1
Optics	Opal diffuser
Weight	11KG
Mounting	Free standing





Interior & Exterior
Linear Systems

the
Broadline
ranges

A highly flexible, minimalist range of linear systems, available in surface, recessed and suspended variants.

Perfect for clean, elegant lines of illumination, as well as more dramatic shapes and designs thanks to the Broadline's incredibly versatile design.







Product Family		Housing Colour		CCT		Suffix
S18620S	584mm	/X5	Textured white	00	3000K	.8
S18622S	1144mm	/X4	Textured black	01	4000K	
S18623S	1424mm	/X2	Textured silver			
S18624S	1704mm					

EM and dimmable options available - see page 268 for ordering info.

Broadline

Surface Mounted

LIGHT DETAILS



Length	CCT	Wattage	Lumens	Efficacy
584mm	3000K	15W	2350lm	161lm/W
584mm	4000K	15W	2470lm	169lm/W
1144mm	3000K	29W	4700lm	161lm/W
1144mm	4000K	29W	4940lm	169lm/W
1424mm	3000K	37W	5870lm	161lm/W
1424mm	4000K	37W	6170lm	169lm/W
1704mm	3000K	44W	7045lm	161lm/W
1704mm	4000K	44W	7410lm	169lm/W

Note: bespoke lengths available



TECHNICAL SPECIFICATIONS

IP rating	IP20
CRI	>80
Lamp Life	50,000 hours
Light Source	Tridonic LLE LED
Voltage	240V
Driver	Integrated high efficiency
LED Warranty	5 Years

HOUSING


Material	Extruded aluminium
Finish	Powder coated
Protection Rating	Class 1
Optics	Opal/ Prismatic diffuser
Weight	2.5kg @ 600mm
Mounting	Surface mounting clips


A beautifully elegant surface mounted linear system, designed around the latest high performance Tridonic LLE LED modules.

Produced in high quality aluminium extruded profile, the Broadline Surface luminaire can be supplied in standard lengths, or custom cut to suit. Also available as individual lengths or joined via plug & socket connection to provide “continuous” runs as required.

Supplied with standard or blind end caps (illustrated opposite), as well as an alternative prismatic diffuser. Get in touch to discuss full customisation options, including custom shapes and angles.

Broadline Surface







Product Family		Housing Colour		CCT		Suffix
S18620IPS	584mm	/X5	Textured white	00	3000K	.8
S18622IPS	1144mm	/X4	Textured black	01	4000K	
S18623IPS	1424mm	/X2 Textured silver				
S18624IPS	1704mm					

EM and dimmable options available - see page 268 for ordering info.

Broadline IP65

Surface Mounted

LIGHT DETAILS



Length	CCT	Wattage	Lumens	Efficacy
584mm	3000K	15W	2350lm	161lm/W
584mm	4000K	15W	2470lm	169lm/W
1144mm	3000K	29W	4700lm	161lm/W
1144mm	4000K	29W	4940lm	169lm/W
1424mm	3000K	37W	5870lm	161lm/W
1424mm	4000K	37W	6170lm	169lm/W
1704mm	3000K	44W	7045lm	161lm/W
1704mm	4000K	44W	7410lm	169lm/W

Note: bespoke lengths available



TECHNICAL SPECIFICATIONS

IP rating	IP65
CRI	>80
Lamp Life	50,000 hours
Light Source	Tridonic LLE LED
Voltage	240V
Driver	Integrated high efficiency
LED Warranty	5 Years

HOUSING

Material	Extruded aluminium
Finish	Powder coated
Protection Rating	Class 1
Optics	Opal / Prismatic diffuser
Weight	2.5kg @ 600mm
Mounting	Wall / ceiling recessed


This IP65 version of the Broadline Surface Mounted allows for installation in exterior environments.

Produced in high quality aluminium extruded profile, the Broadline IP65 Surface luminaire can be supplied in standard lengths, or custom cut to suit.

Can be supplied with an alternative prismatic diffuser. Get in touch to discuss full customisation options.

Broadline IP65 Surface





Product Family		Housing Colour		CCT		Suffix
S18620R	584mm	/X5	Textured white	00	3000K	.8
S18622R	1144mm	/X4	Textured black	01	4000K	
S18623R	1424mm	/X2	Textured silver			
S18624R	1704mm					

EM and dimmable options available - see page 268 for ordering info.



Broadline

Recessed

LIGHT DETAILS

Length	CCT	Wattage	Lumens	Efficacy
584mm	3000K	15W	2350lm	161lm/W
584mm	4000K	15W	2470lm	169lm/W
1144mm	3000K	29W	4700lm	161lm/W
1144mm	4000K	29W	4940lm	169lm/W
1424mm	3000K	37W	5870lm	161lm/W
1424mm	4000K	37W	6170lm	169lm/W
1704mm	3000K	44W	7045lm	161lm/W
1704mm	4000K	44W	7410lm	169lm/W

Note: bespoke lengths available



TECHNICAL SPECIFICATIONS

IP rating	IP20
CRI	>80
Lamp Life	50,000 hours
Light Source	Tridonic LLE LED
Voltage	240V
Driver	Integrated high efficiency
LED Warranty	5 Years

HOUSING

Material	Extruded aluminium
Finish	Powder coated
Protection Rating	Class 1
Optics	Opal / Prismatic diffuser
Weight	2.5kg @ 600mm
Mounting	Wall / Ceiling recessed


The Broadline Recessed allows this linear system to be inset within walls and ceilings, providing a beautifully discrete lighting solution.

Produced in high quality aluminium extruded profile, the Sovereign Broadline Recessed luminaire can be installed individually or joined via plug & socket connection to provide "continuous" runs as required.

A choice of lengths available, including bespoke individual lengths, and cut to custom angles and lengths to match corners or provide dramatic shapes.

Broadline Recessed

Linear Systems



Product Family		Housing Colour		CCT		Suffix
S18620IPR	584mm	/X5	Textured white	00	3000K	.8
S18622IPR	1144mm	/X4	Textured black	01	4000K	
S18623IPR	1424mm	/X2 Textured silver				
S18624IPR	1704mm					

EM and dimmable options available - see page 268 for ordering info.



Broadline IP65

Recessed

LIGHT DETAILS

Length	CCT	Wattage	Lumens	Efficacy
584mm	3000K	15W	2350lm	161lm/W
584mm	4000K	15W	2470lm	169lm/W
1144mm	3000K	29W	4700lm	161lm/W
1144mm	4000K	29W	4940lm	169lm/W
1424mm	3000K	37W	5870lm	161lm/W
1424mm	4000K	37W	6170lm	169lm/W
1704mm	3000K	44W	7045lm	161lm/W
1704mm	4000K	44W	7410lm	169lm/W

Note: bespoke lengths available



TECHNICAL SPECIFICATIONS

IP rating	IP65
CRI	>80
Lamp Life	50,000 hours
Light Source	Tridonic LLE LED
Voltage	240V
Driver	Integrated high efficiency
LED Warranty	5 Years


HOUSING

Material	Extruded aluminium
Finish	Powder coated
Protection Rating	Class 1
Optics	Opal / Prismatic diffuser
Weight	2.5kg @ 600mm
Mounting	Wall / Ceiling recessed

The Broadline IP65 Recessed can be installed in exterior environments thanks to the weatherproof design.

Produced in high quality aluminium extruded profile, the Sovereign Broadline IP65 Recessed luminaire is available in a choice of lengths available, including bespoke individual lengths of up to 2mts.

Broadline IP65 Recessed





Product Family		Housing Colour		CCT		Suffix
S18620	584mm direct	/X5	Textured white	00	3000K	.8
S18622	1144mm direct	/X4	Textured black	01	4000K	
S18623	1424mm direct	/X2	Textured silver			
S18624	1704mm direct					
S18625	584mm direct/indirect					
S18627	1144mm direct/indirect					
S18628	1424mm direct/indirect					
S18629	1704mm direct/indirect					



EM, dimmable and control options available.
See page 268 for details.

Broadline

Suspended

LIGHT DETAILS - DIRECT

Length	CCT	Wattage	Lumens	Efficacy
584mm	3000K	15W	2350lm	161lm/W
584mm	4000K	15W	2470lm	169lm/W
1144mm	3000K	29W	4700lm	161lm/W
1144mm	4000K	29W	4940lm	169lm/W
1424mm	3000K	37W	5870lm	161lm/W
1424mm	4000K	37W	6170lm	169lm/W
1704mm	3000K	44W	7045lm	161lm/W
1704mm	4000K	44W	7410lm	169lm/W



LIGHT DETAILS - DIRECT/INDIRECT

Length	CCT	Wattage	Lumens	Efficacy
584mm	3000K	22W	2350lm + 1174lm	161lm/W
584mm	4000K	22W	2470lm + 1235lm	169lm/W
1144mm	3000K	44W	4700lm + 2350lm	161lm/W
1144mm	4000K	44W	4940lm + 2470lm	169lm/W
1424mm	3000K	58W	5870lm + 3525lm	161lm/W
1424mm	4000K	58W	6170lm + 3705lm	169lm/W
1704mm	3000K	73W	7045lm + 4700lm	161lm/W
1704mm	4000K	73W	7410lm + 4940lm	169lm/W

Note: bespoke lengths available

TECHNICAL SPECIFICATIONS

IP rating	IP20
CRI	>80
Lamp Life	50,000 hours
Light Source	Tridonic LLE LED
Voltage	240V
Driver	Integrated high efficiency
LED Warranty	5 Years

HOUSING

Material	Extruded aluminium
Style	Standard / Blind end caps
Finish	Powder coated
Protection Rating	Class 1
Optics	Opal diffuser
Weight	2.5kg @ 600mm
Mounting	Wire suspension kit

A beautifully elegant linear profile system designed around the latest high performance Tridonic LLE LED modules.

Produced in high quality aluminium extruded profile, the Broadline Suspended luminaire can be supplied in standard lengths, or custom cut to suit. Also available as individual pendants or joined via plug & socket connection to provide "continuous" runs as required.

Supplied with standard or blind end caps (illustrated opposite), as well as an alternative prismatic diffuser. Get in touch to discuss full customisation options, including custom shapes and angles.

Broadline Suspended





Product Family		Housing Colour		CCT		Suffix
S18620IP	594mm direct	/X5	Textured white	00	3000K	.8
S18622IP	1154mm direct	/X4	Textured black	01	4000K	
S18623IP	1434mm direct	/X2	Textured silver			
S18624IP	1714mm direct					

EM, dimmable and control options available.
See page 268 for details.



Broadline IP65

Suspended

LIGHT DETAILS

Length	CCT	Wattage	Lumens	Efficacy
594mm	3000K	15W	2350lm	161lm/W
594mm	4000K	15W	2470lm	169lm/W
1154mm	3000K	29W	4700lm	161lm/W
1154mm	4000K	29W	4940lm	169lm/W
1434mm	3000K	37W	5870lm	161lm/W
1434mm	4000K	37W	6170lm	169lm/W
1714mm	3000K	44W	7045lm	161lm/W
1714mm	4000K	44W	7410lm	169lm/W

Note: bespoke lengths up to 2m available



TECHNICAL SPECIFICATIONS


IP rating	IP65
CRI	>80
Lamp Life	50,000 hours
Light Source	Tridonic LLE LED
Voltage	240V
Driver	Integrated high efficiency
LED Warranty	5 Years

HOUSING

Material	Extruded aluminium
Finish	Powder coated
Protection Rating	Class 1
Optics	Opal diffuser
Weight	2.5kg @ 600mm
Mounting	Wire suspension kit

Broadline IP65






EM, dimmable and control options available.
See page 268 for details.

Broadline Cylindrical


Suspended

Product Family		Driver		Housing Colour		CCT		Suffix
S18672	594mm		Integrated	/00	Silver	00	3000K	.8
S18673	1154mm	R	Remote			01	4000K	
S18674	1434mm							
S18675	1714mm							



Length	CCT	Wattage	Lumens	Efficacy
584mm	3000K	15W	2350lm	161lm/W
584mm	4000K	15W	2470lm	169lm/W
1144mm	3000K	29W	4700lm	161lm/W
1144mm	4000K	29W	4940lm	169lm/W
1424mm	3000K	37W	5870lm	161lm/W
1424mm	4000K	37W	6170lm	169lm/W
1704mm	3000K	44W	7045lm	161lm/W
1704mm	4000K	44W	7410lm	169lm/W

Note: bespoke lengths available



TECHNICAL SPECIFICATIONS

IP rating	IP40
CRI	>80
Lamp Life	50,000 hours
Light Source	Tridonic LLE LED
Voltage	240V
Driver	High efficiency
LED Warranty	5 Years


HOUSING

Material	Extruded aluminium
Style	Remote / Integrated Driver
Finish	Powder coated
Protection Rating	Class 1
Optics	Polycarbonate diffuser
Weight	2.5kg @ 600mm
Mounting	Wire suspension kit

A beautifully stylish tubular luminaire, the Broadline Cylindrical range offers virtually all round illumination thanks to the wrap around diffuser design. Extending to 310° the diffusers allows the Tridonic LLE boards to provide high quality, even illumination.

Main spine and gear housing produced in high quality extruded & anodised aluminium with high transmission polycarbonate diffuser.

A choice of standard lengths are available with bespoke lengths up to 2.5mts also available to order. Standard versions fitted with integral high efficiency driver located within rear mounted aluminium housing, and can also be supplied with remote driver for a cleaner aesthetic line. Supplied c/w adjustable 3mtr wire suspension set.



Linear Systems




type A

Linear Systems

Our most versatile Sovereign products, the type **A** Linear Systems are available in a comprehensive range of fixed, variable, colour and white light options.

Offered in surface, recessed and angled variants, the Sovereign Linear Systems can be supplied as straight profiles in any length up to 2mtr as standard, or custom designed to wrap around corners of any angle for more architectural solutions.

Perfect for many interior lighting applications; from subtle, concealed illumination to dramatic, feature lighting designs.



TECHNICAL SPECIFICATIONS

IP rating	IP20
CRI	>70-80
Lamp Life	50,000 hours
Voltage	12V DC / 24V DC
Driver	Fixed and Dimmable options
LED Warranty	5 Years
Material	Extruded aluminium
Finish	Anodised / any BS/RAL
Diffuser	Clear / Frosted / Semi-Frosted
Protection Rating	Class 1
Accessories	Surface mounting clips / End caps

type A

Variable Light

Perfect for providing instantly changeable colour options to suit different atmospheres or changing displays.



Adjustable Colour Temperature

Our adjustable colour temperature option allows excellent flexibility of 2500K-7000K. By using a dual chip, a seamless colour appearance is achieved, even on surfaces in close proximity. Colour appearance can be changed almost instantly to suit changing displays or to help give the area a different atmospheric feel.


Cat No.	Wattage	CCT	Lumen Output	Voltage	LEDs/mtr
S18350A	19.2W/mtr	2500-7000K	1500lm/mtr	24V DC	120 LEDs



Adjustable RGB +

Providing full spectrum RGB control with a choice of colour temperature white. Ideal for maximum colour flexibility, allowing complete transformation of atmosphere with ease.

Cat No.	Wattage	CCT	Voltage	LEDs/mtr
S18353A	19.2W/mtr	RGB + Amber	24V DC	60 LEDs
S18353P	19.2W/mtr	RGB + 6000K	24V DC	60 LEDs
S18353N	19.2W/mtr	RGB + 4000K	24V DC	60 LEDs
S18353W	19.2W/mtr	RGB + 2500K	24V DC	60 LEDs



Adjustable RGB

A truly versatile product which can provide anything from basic colour change using our inexpensive RGB controllers, right up to a full DMX control system. Supplied in 24V DC although 12V DC is available for specific projects where required.

Cat No.	Wattage	CCT	Voltage	LEDs/mtr
S18353	14.4/mtr	RGB	24V DC	60 LEDs

type A

Fixed Light

Best suited when single colour illumination is desired, providing excellent quality illumination with high energy efficiency.

Low Power Fixed White

These Low Power light options are ideal for providing subtle lighting effects with a considerable reduction in energy consumption.

Cat No.	Wattage	CCT	Lumen Output	Voltage	LEDs/mtr
S18350UL	4.8W/mtr	3000-3500K	360lm/mtr	24V DC	60 LEDs
S18350L	7.2W/mtr	3000-3500K	540lm/mtr	24V DC	30 LEDs



Medium Power Fixed White

For specifications requiring greater lumen output, as well as higher colour temperature options.


Cat No.	Wattage	CCT	Lumen Output	Voltage	LEDs/mtr
S18350W	14.4W/mtr	2700K	1000lm/mtr	24V DC	60 LEDs
S18350	14.4W/mtr	2800-3200K	1050lm/mtr	24V DC	60 LEDs
S18350N	14.4W/mtr	4000-4500K	1100lm/mtr	24V DC	60 LEDs
S18351	14.4W/mtr	5500-6500K	1150lm/mtr	24V DC	60 LEDs
S18352	14.4W/mtr	6500-7500K	1200lm/mtr	24V DC	60 LEDs



High Power Single Colour

Perfect for adding a touch of pure colour to an installation, these light options are based on our most popular High Power 5050 LED module. An excellent combination of high light output with a strong colour to provide outstanding results.

Cat No.	Wattage	CCT	Lumen Output	Voltage	LEDs/mtr
S18360	14.4W/mtr	Blue (465-470nm)	320lm/mtr	24V DC	60 LEDs
S18361	14.4W/mtr	Amber (590nm)	360lm/mtr	24V DC	60 LEDs
S18362	14.4W/mtr	Red (620-625nm)	360lm/mtr	24V DC	60 LEDs
S18363	14.4W/mtr	Green (520-525nm)	810lm/mtr	24V DC	60 LEDs



type **A**
Profiles


A range of profiles designed to house type **A** light outputs.



Slimline Surface
AL7

- Our most versatile linear system
- Surface mounted with clips



EC-SL7-H1	End Cap Plain
EC-SL7-H2	End Cap + cable hole
LP-MC-SL7	Mounting clip



Slimline Recessed
ALR7

- Our most popular recessed linear system.
- Interior wall or ceiling recessed

EC-RSL7-H1	End Cap Plain
EC-RSL7-H2	End Cap + cable hole




- Greater concealment of the LEDs, providing a more even spread illumination.
- Surface mounted with clips

EC-SL15-H1	End Cap Plain
EC-SL157-H2	End Cap + cable hole
LP-MC-SL15	Mounting clip



Deep Surface
AL15




- More concealed illumination by recessing the light source further within the wall.
- Interior wall or ceiling recessed

EC-RSL15-H1	End Cap Plain
EC-RSL15-H2	End Cap + cable hole



Deep Recessed
ALR15



- Ideal for corner applications, providing a 45° illumination.
- Surface mounted with clips

EC-D1	End Cap Plain
EC-D2	End Cap + cable hole
LP-MC-D1	Mounting clip



Angled Surface
ALA

Build your linear system

Complete the order system opposite using the codes for your chosen Type **A** Light Source and Profile options. We will advise on the ideal driver for each Linear solution to fit the specific requirements.

If you would like advice or require a bespoke linear system, such as more complex angles and shapes, get in touch with our team and we can develop the best solution for you.


Light Source		Length		Family Code		Diffuser		Suffix
S****	Choose from Type A light options	/1000/	1000mm	AL7	Slimline Surface	C	Clear	.8
		/2000/	2000mm	ALR7	Slimline Recessed	F	Frosted	
		/****/	[Custom]	AL15	Deep Surface	F50	Semi-frosted	
				ALR15	Deep Recessed			
				ALA	Angled Surface			

/****/ State length required in mm (we will provide relevant couplers & terminations to suit each project).

type *B*

Linear Systems

Introduced for use in those areas requiring higher light levels whilst still requiring a flexible & discreet light source.



TECHNICAL SPECIFICATIONS

IP rating	IP20
CRI	>70-80
Lamp Life	50,000 hours
Voltage	12V DC / 24V DC
Driver	Fixed and Dimmable options
LED Warranty	5 Years
Material	Extruded aluminium
Finish	Anodised / any BS/RAL
Diffuser	Clear / Frosted / Semi-Frosted
Protection Rating	Class 1
Accessories	Surface mounting clips / End caps

type *B*

Light Output

While the Type *B* profiles can accommodate any of the Type *A* light options, they are best utilised with higher power light sources which take advantage of the enhanced heatsink capabilities.




High Power Fixed White

The colour temperature options provide up to an impressive 2500lm/mtr, ideal for applications requiring more illumination.

Cat No.	Wattage	CCT	Lumen Output	Voltage	LEDs/mtr
S18350X	22W/mtr	2900-3100K	2300lm/mtr	24V DC	126 LEDs
S18350NX	22W/mtr	4000-4500K	2400lm/mtr	24V DC	126 LEDs
S18352X	22W/mtr	6000-7000K	2500lm/mtr	24V DC	126 LEDs


type *B*

Profiles




- Heatsink design for higher outupt light options.
- Surface mounted with clips.

EC-SL17-H1	End Cap Plain
EC-SL17-H2	End Cap + cable hole
LP-MC-SL17	Mounting clip



Slimline High Output

AL17



- Heatsink design for higher outupt light options.
- Surface mounted with clips, attached to extrusion

EC-SL62-H1	End Cap Plain
EC-SL62-H2	End Cap + cable hole



Curved Surface

ALC

Build your linear system

Complete the order system opposite using the codes for your chosen Type *A* or *B* Light Source and Type *B* Housing option from the following pages. We will advise on the ideal driver for each Linear solution to fit the specific requirements.

If you would like advice or require a bespoke linear system, get in touch with our team and we can develop the best solution for you.


Light Source		Length		Profile		Diffuser		Suffix
S*****	Choose from Type A & B light options	/1000/	1000mm	AL17	Slimline High Output	C	Clear	.8
		/2000/	2000mm	ALC	Curved Surface	F	Frosted	
		/****/	[Custom]			F50	Semi-frosted	

/****/ State length required in mm (we will provide relevant couplers & terminations to suit each project).

type C

Linear Systems

For a more prominent, conspicuous solution to the Type **A** linear systems, the Type **C** solutions provide a wider, thicker lines of illumination. This also allows for increased light output thanks to the double row LED light sources.



TECHNICAL SPECIFICATIONS

IP rating	IP20
CRI	>70-80
Lamp Life	50,000 hours
Voltage	12V DC / 24V DC
Driver	Fixed and Dimmable options
LED Warranty	5 Years
Material	Extruded aluminium
Finish	Anodised / any BS/RAL
Diffuser	Clear / Frosted / Semi-Frosted
Protection Rating	Class 1
Accessories	Surface mounting clips / End caps

type C

Light Options

While the Type **C** profiles can accommodate any of the Type **A** light options, they are best utilised with double row light sources which take advantage of the greater profile width.


Wide Fixed White

This double row version offers increased light levels compared to traditional single row strips. Supplied in 24V DC as standard to reduce volt drop to a minimum.

Cat No.	Wattage	CCT	Lumen Output	Voltage	LEDs/mtr
S18350D	19.2W/mtr	2700K	1200lm/mtr	24V DC	120 LEDs

type C

Linear Profiles




- Greater concealment of the LEDs, providing a more even spread illumination.
- Surface mounted with clips

EC-SLW8-H1	End Cap Plain
EC-SLW8-H2	End Cap + cable hole
LP-MC-SLW8	Mounting clip



Wide Surface
ALW8




- More concealed illumination by recessing the light source further within the wall.
- Interior wall or ceiling recessed

EC-RSL15-H1	End Cap Plain
EC-RSL15-H2	End Cap + cable hole




Wide Recessed
ALRW8



- Recessed and over-plastered

EC-SL71-H1	End Cap Plain
EC-SL71-H2	End Cap + cable hole



Wide Trimless
ALP71

Build your linear system

Complete the order system opposite using the codes for your chosen Type **A** or **C** Light Source and Type **C** Profile option. We will advise on the ideal driver for each Linear solution to fit the specific requirements.

If you would like advice or require a bespoke linear system, get in touch with our team and we can develop the best solution for you.


Light Source		Length		Profile		Diffuser		Suffix
S****	Choose from Type A & C light options	/1000/	1000mm	ALW8	Wide Surface	C	Clear	.8
		/2000/	2000mm	ALRW8	Wide Recessed	F	Frosted	
		/****/	[Custom]	ALP71	Wide Trimless	F50	Semi-frosted	

/****/ State length required in mm (we will provide relevant couplers & terminations to suit each project).

Nano, High Output & Twist



Linear Systems

These additional systems complement our standard options at both ends of the scale. The Nano Surface is our most discrete system, while the Wide High Output provides the largest and most powerful lighting.



The Sovereign Linear Nano is our thinnest profile, perfect for the most subtle of illumination. This surface-mounted system combines a quality aluminium profile with a 24V DC high CRI 90 light source, resulting in a system providing pinpoint high quality illumination.

It is available with a choice of three different quality UV resistant, snap-in diffusers; frosted, semi-frosted and transparent. The fully frosted diffuser transforms the individual LEDs into a smooth, soft illumination.



TECHNICAL SPECIFICATIONS

IP rating	IP20
CRI	>90
Lamp Life	50,000 hours
Voltage	12V DC / 24V DC
Driver	Fixed and Dimmable options
Viewing Angle	120°
LED Warranty	5 Years
Material	Extruded aluminium
Finish	Anodised / any BS/RAL
Diffuser	Clear / Frosted / Semi-Frosted
Protection Rating	Class 1
Accessories	Surface mounting clips / End caps

LIGHT SOURCE

Cat No.	Wattage	CCT	Lumen Output	Voltage	LEDs/mtr
S98895	9.6W/mtr	2500-2700K	700-750lm/mtr	24V DC	120 LEDs
S98896	9.6W/mtr	3000-3500K	800-850lm/mtr	24V DC	120 LEDs
S98897	9.6W/mtr	4000-4500K	850-900lm/mtr	24V DC	120 LEDs

Light Source		Length		Profile		Diffuser		Suffix
S98883	9.6W 2700K	/1000/	1000mm	ALN	Nano Surface	C	Clear	.8
S98883W	9.6W 3000K	/2000/	2000mm			F	Frosted	
S98883N	9.6W 4000K	/****/	[Custom]			F50	Semi-frosted	

/****/ State length required in mm (we will provide relevant couplers & terminations to suit each project).

Nano Surface
Linear System

TECHNICAL SPECIFICATIONS

IP rating	IP20
CRI	>90
Lamp Life	50,000 hours
Voltage	12V DC / 24V DC
Driver	Fixed and Dimmable options
Viewing Angle	120°
LED Warranty	5 Years
Material	Extruded aluminium
Finish	Anodised / any BS/RAL
Diffuser	Clear / Frosted / Semi-Frosted
Protection Rating	Class 1
Accessories	End caps



The Sovereign Linear Trimless Narrow is the most subtle of all our linear systems, combining one of the thinnest profiles with the most concealed installation type.

This plaster-over design means edges are completely hidden within the plasterboard. Ideal for the most minimal and clean lighting solutions, in areas where aesthetic beauty and design is of high priority.

Low Power Fixed White

Cat No.	Wattage	CCT	Lumen Output	Voltage	LEDs/mtr
S18350UL	4.8W/mtr	3000-3500K	360lm/mtr	24V DC	60 LEDs

High Power Fixed White

Cat No.	Wattage	CCT	Lumen Output	Voltage	LEDs/mtr
S98895	9.6W/mtr	2500-2700K	700-750lm/mtr	24V DC	120 LEDs
S98896	9.6W/mtr	3000-3500K	800-850lm/mtr	24V DC	120 LEDs
S98897	9.6W/mtr	4000-4500K	850-900lm/mtr	24V DC	120 LEDs


Light Source		Length		Profile		Diffuser		Suffix
S98895	9.6W 2700K	/1000/	1000mm	ALTN	Narrow Trimless	C	Clear	.8
S98896	9.6W 3000K	/2000/	2000mm			F	Frosted	
S98897	9.6W 4000K	/****/	[Custom]			F50	Semi-frosted	
S18350UL	4.8W/mtr							

/****/ State length required in mm (we will provide relevant couplers & terminations to suit each project).

Narrow Trimless
Linear System

The Sovereign Wide High Output linear system provides our highest output linear system until the Sovereign Broadline range.

Perfect for general illumination and architectural accent for kitchens, offices, hospitality, retail, residences, libraries, hallways and bath/vanity, where extra illumination is required.



LIGHT DETAILS

Cat No.	Wattage	CCT	Lumen Output	Voltage	LEDS/mtr
S18350DH	28.8W/mtr	3000K	2100lm/mtr	24V DC	120 LEDs

Light Source		Length		Profile		Diffuser		Suffix
S18350DH	28.8W/mtr	/1000/	1000mm	AL23	Wide High Output	C	Clear	.8
		/2000/	2000mm			F	Frosted	
		/****/	[Custom]			F50	Semi-frosted	


/****/ State length required in mm (we will provide relevant couplers & terminations to suit each project).

Wide High Output

Linear System

TECHNICAL SPECIFICATIONS

IP rating	IP67
CRI	>80
Lamp Life	50,000 hours
Light Source	2835 LED Module
Voltage	24V DC
Viewing Angle	120°
Driver	High efficiency
Protection Rating	Class 1
Style	Side bend & Top bend available
LED Warranty	5 Years



The Sovereign Linear Twist is a fully malleable linear system. Simultaneously bendable horizontally and vertically, this is one of the most flexible systems on the market.

Housed in a IP67 rated enclosure, the Sovereign Linear Twist can be used for both interior and exterior applications. A perfect replacement for neon tube lighting, building and signage illumination, bathroom lighting, cove and general lighting.

Available in any length up to 20 metres, with lengths over 10m supplied with feed from both ends. Mounted in profile lengths with mounting clips. Available in a range of colour temperatures.

ACCESSORIES

18398.0001	Transparent PC clips for indoor applications
18398.0002	AL profile for outdoor application 1mtr + clips
18398.0003	AL profile for outdoor application 50mm + clips
18398.0004	Stainless steel chain: 1m length

LIGHT DETAILS

Wattage	CCT	CCT Range	Voltage	Efficacy
12W/mtr	2700K	2600-2800K	24V DC	500lm/mtr
12W/mtr	3000K	2850-3150K	24V DC	550lm/mtr
12W/mtr	4000K	3830-4170K	24V DC	550lm/mtr
12W/mtr	5000K	4750-5250K	24V DC	550lm/mtr

Family Code		CCT		Length		Mains Feed		Suffix
S18397	Linear Twist	/2.7K	2700K	/1000	1000mm	/E	End	.8
		/3K	3000K	/2000	2000mm	/S	Side	
		/4K	4000K	/3000	3000mm	/R	Rear	
		/5K	5000K	/****	[Custom]			

/****/ State length required in mm (we will provide relevant couplers & terminations to suit each project).

Linear Twist

Linear System



Tape Only

Linear Systems

While we recommend developing a complete linear system with our lighting specialists, we can supply lengths of linear tape if required.

All linear tape should be housed within an appropriate profile system for installation.



Adjustable Colour Temperature

Cat No.	Wattage	CCT	Lumen Output	Voltage	LEDS/mtr
S18350A	19.2W/mtr	2500-7000K	1500lm/mtr	24V DC	120 LEDs

Adjustable RGB + W

Cat No.	Wattage	CCT	Voltage	LEDS/mtr
S18353A	19.2W/mtr	RGB + Amber	24V DC	60 LEDs
S18353P	19.2W/mtr	RGB + 6000K	24V DC	60 LEDs
S18353N	19.2W/mtr	RGB + 4000K	24V DC	60 LEDs
S18353W	19.2W/mtr	RGB + 2500K	24V DC	60 LEDs

Adjustable RGB

Cat No.	Wattage	CCT	Voltage	LEDS/mtr
S18353	19.2W/mtr	RGB	12V DC	60 LEDs

Low Power Fixed White

Cat No.	Wattage	CCT	Lumen Output	Voltage	LEDS/mtr
S18350UL	4.8W/mtr	3000-3500K	360lm/mtr	12V DC	60 LEDs
S18350L	7.2W/mtr	3000-3500K	540lm/mtr	12V DC	30 LEDs

Medium Power Fixed White

Cat No.	Wattage	CCT	Lumen Output	Voltage	LEDS/mtr
S98895	9.6W/mtr	2500-2700K	700-750lm/mtr	24V DC	120 LEDs
S98896	9.6W/mtr	3000-3500K	800-850lm/mtr	24V DC	120 LEDs
S98897	9.6W/mtr	4000-4500K	850-900lm/mtr	24V DC	120 LEDs
S18350W	14.4W/mtr	2700K	1000lm/mtr	24V DC	60 LEDs
S18350	14.4W/mtr	2800-3200K	1050lm/mtr	24V DC	60 LEDs
S18350N	14.4W/mtr	4000-4500K	1100lm/mtr	24V DC	60 LEDs
S18351	14.4W/mtr	5500-6500K	1150lm/mtr	24V DC	60 LEDs
S18352	14.4W/mtr	6500-7500K	1200lm/mtr	24V DC	60 LEDs

High Power White

Cat No.	Wattage	CCT	Lumen Output	Voltage	LEDS/mtr
S18350X	22W/mtr	2900-3100K	2300lm/mtr	24V DC	126 LEDs
S18350NX	22W/mtr	4000-4500K	2400lm/mtr	24V DC	126 LEDs
S18352X	22W/mtr	6000-7000K	2500lm/mtr	24V DC	126 LEDs
S18350DH	28.8W/mtr	3000K	2100lm/mtr	24V DC	120 LEDs

Medium Power Single Colour

Cat No.	Wattage	CCT	Lumen Output	Voltage	LEDS/mtr
S18360	14.4W/mtr	Blue (465-470nm)	320lm/mtr	12V DC	60 LEDs
S18361	14.4W/mtr	Amber (590nm)	360lm/mtr	12V DC	60 LEDs
S18362	14.4W/mtr	Red (620-625nm)	360lm/mtr	12V DC	60 LEDs
S18363	14.4W/mtr	Green (520-525nm)	810lm/mtr	12V DC	60 LEDs

Dimming, Emergency & Lighting Control

All of our Sovereign luminaires are available with a full range of EM and lighting control options. To specify products with our most popular lighting controls, insert the relevant code between the main product code and the suffix.

For products that require remote drivers (i.e. Ceiling Downlights), use the Remote EM & Lighting Control insert.

When specifying control options without Emergency lighting options, include /10 (/20 for remote) under the Emergency selection (do not leave blank).


Product code	EM & Lighting Control Insert		Suffix
	Emergency	Control	
	/10 Non-EM	0 On / off	.8
	/11 Non maintained EM	1 1-10V dimming	
	/14 Maintained 3HR EM	2 DALI dimming	
	/16 DALI self test EM	5 Switch dim	
		6 DMX	
		7 Bluetooth	

Example: **S98612.2100/106.8**
Slim Uplight / Silver / 3000K Up/down / Non EM / DMX control

Product code	Remote EM & Lighting Control Insert		Suffix
	Emergency	Control	
	/20 Non-EM	0 On / off	.8
	/21 Non maintained EM	1 1-10V dimming	
	/24 Maintained 3HR EM	2 DALI dimming	
	/26 DALI self test EM	5 Switch dim	
		6 DMX	
		7 Bluetooth	

Example: **S18156.0510/202.8**
Scoop Downlight / White / 2700K / Non EM / DALI dimming

For more information about our control options,
just get in touch with our team.



Bespoke Design

Product Modification

This catalogue lists only some of the options our Sovereign products offer. Commercial Lighting has extensive experience creating custom adaptations for our clients.

Need a specific housing colour, light source or bespoke colour rendering index? We can help.

Custom Product Design

Need a unique feature pendant, a specific housing design, or a solution no currently offered in our Sovereign range? Get in touch.

Many of our Sovereign products began as custom designs made in collaboration with clients

Lighting Solutions

Our facilities include a dedicated in-house design team, metal workshop, in-house powder coating plant, and a team of experienced electrical assemblers.

This enables us to develop completely bespoke lighting solutions for any project.




the
ReVive
service


Our ReVive service puts sustainability at the heart.

Utilising 20+ years experience in sensitive restoration and refurbishment, Commercial Lighting gives old products new life, bringing them in line with the very latest standards, efficiency and performance.

The ReVive process:


1	Assessment	We'll discuss all details of the current system with you to assess viability. We might ask for a sample or arrange collection via a site visit.
2	Proposal	Our technical team will create a full proposal, identifying the best solution for your project. This will comparison between current and proposed new fittings.
3	First-off	Our in house specialist production team will produce a sample for approval before full production. Depending on complexity, the conversions can be done in our manufacturing facilities, or custom upgrade kits can be sent for conversion on site.
4	Refurbish	We refurbish and upgrade all your products and apply rigorous testing procedures.
5	Installation	Your products are returned and re-installed using existing fixings for minimal disruption. Your fittings will be covered by our 5 year comprehensive warranty.






ReVive


Updating older luminaires
with the latest LED technology




Cheaper than
buying new




Less
carbon impact




Less
waste



Improved
efficiency



Better
illumination



Extended
lifetime

About us

Commercial Lighting Systems Ltd was established in Hampshire in 1991. The company is dedicated to offering the best quality, energy-efficient lighting to the UK market.

Our business is client-led, and made up of three divisions: reputable product ranges, bespoke design, and our flagship ReVive service for restoring and updating older lighting systems.

With almost 30 employees, many working here for over 20 years, our size lets us handle projects of any size. This allows us to maintain a personal approach to business, particularly advantageous for projects with unique specifications.

Our Values

How we do business is just as important as the end product. Our approach is built around quality, honesty, and sustainability.

We continually invest in technologies that help us minimise our environmental impact. From solar panels and full EV fleet to our minimal waste policy, we ensure every stage of our operations is considered for its impact on the environment.





The signature range from
Commercial Lighting Systems Ltd