

## Spectrum S154 LED Pro Spotlights









**Spectrum LED Pro** display spotlights incorporate a single high power LED that is carefully constructed into a high quality, hard wearing and reliable contemporary luminaire. The design ensures that the spotlights are as unobtrusive as possible so that your products are illuminated to their full potential without obstruction.

- Integrated LED.
- Specialised focused lighting for museum and retail showcases.
- Low heat illumination.
- No ultraviolet light so does not fade materials.
- Unobtrusive.
- Bespoke product manufactured to your specification.
- Reduces heat emissions and heat build-up in store.
- Reduces energy bills by up to 80%.
- Dimmable

## Technical Specifications

<b>Head Diameter:</b>	25mm
<b>Height:</b>	<1000mm (visible height)
<b>Material/s:</b>	Aluminium/Brass
<b>Electrical Connection:</b>	In Series Connections - Plug & Play or Hard Wired (1000mm tails as standard)
<b>CCT (Lumens):</b>	<b>VWW - 2700K</b> (105lm @ 350mA) <b>WW - 3000K</b> (105lm @ 350mA) <b>NW - 4000K</b> (144lm @ 350mA) <b>CW - 5000K</b> (150lm @ 350mA)
<b>Watts:</b>	1W @ 350mA (integrated non-user replaceable LED) 1.6W @ 500mA (integrated non-user replaceable LED)
<b>UV:</b>	0.2 microwatts/m2
<b>Fixings:</b>	6 fixing options available (see page 2)
<b>CRI Rating:</b>	CRI90>
<b>Class:</b>	III
<b>IP Rating:</b>	IP20
<b>Rotation   Tilt:</b>	350 Degrees   90 Degrees
<b>Finishes:</b>	<b>01</b> - White <b>02</b> - Black <b>03</b> - Chrome <b>04</b> - Gold <b>05</b> - Brushed Chrome <b>06</b> - Antique Brass <b>07</b> - Polished Nickel <b>08</b> - Brushed Nickel <b>15</b> - Brushed Brass <b>16</b> - Rose Gold <b>XXX</b> - RAL Colours
<b>Tube Support Diameter:</b>	6.50mm
<b>Forward Voltage:</b>	3.2Vf
<b>Beam Angles:</b>	<b>10</b>   <b>25</b>   <b>40</b>   <b>60</b> Degrees
<b>Warranty:</b>	5 Years
<b>Dimming:</b>	<b>ON/OFF</b>   <b>1-10V</b>   <b>TRIAC</b>   <b>DALI</b>   <b>DMX</b>   <b>Bluetooth</b>
<b>Ordering:</b>	7 step order code (see page 3)

## Spectrum S154 LED Pro Spotlights



### RF Rear Fixing

<b>Diameter:</b>	20mm
<b>Height:</b>	25mm
<b>Fixing:</b>	M10 x 50mm Metric Fine Thread with Nut & Washer
<b>Cutout Diameter:</b>	11mm
<b>Material:</b>	Brass
<b>Mounting:</b>	Vertical or Horizontal

### FF Face Fixing (*Hidden Bezel*)

<b>Diameter:</b>	30mm
<b>Height:</b>	25mm
<b>Fixing:</b>	Screw Fix
<b>Cutout Diameter:</b>	7mm
<b>Material:</b>	Brass
<b>Mounting:</b>	Vertical or Horizontal

### RFS Small Rear Fixing

<b>Diameter:</b>	20mm
<b>Height:</b>	25mm
<b>Fixing:</b>	M8 x 20mm Metric Fine Thread with Nut & Washer
<b>Cutout Diameter:</b>	9mm
<b>Material:</b>	Brass
<b>Mounting:</b>	Vertical or Horizontal

### HF Hidden Fixing (*Floating Cover*)

<b>Diameter:</b>	30mm
<b>Height:</b>	25mm
<b>Fixing:</b>	Screw Fix
<b>Cutout Diameter:</b>	7mm
<b>Material:</b>	Brass
<b>Mounting:</b>	Vertical

### HFB Hidden Fixing Bezel



<b>Diameter:</b>	27mm
<b>Height:</b>	12mm
<b>Fixing:</b>	Screw Fix ( <i>Underside</i> )
<b>Cutout Diameter:</b>	7mm
<b>Material:</b>	Brass
<b>Mounting:</b>	Vertical or Horizontal

### SM 60 Degree Surface Mount Bracket

<b>Width:</b>	25mm
<b>Height:</b>	26mm
<b>Fixing:</b>	Screw Fix
<b>Cutout Diameter:</b>	N/A
<b>Material:</b>	1.5mm Steel
<b>Mounting:</b>	Vertical or Horizontal

## Spectrum S154 LED Pro Spotlights

### POWER & DIMMING OPTIONS

- P&P** Plug & Play - Standard On/Off Driver (2m mains lead & UK plug)
- P&P/BT:** Plug & Play -  Bluetooth Controllable Driver (no mains lead)  
[Casambi App available for IOS on App Store & Android on Google Play Store](#)
- P&P/DA:** Plug & Play - 1-10V Dimmable Driver (no mains lead)
- P&P/DAP:** Plug & Play - 1-10V Dimmable Driver with Pot Dimmer (2m mains lead & UK plug)
- P&P/DD:** Plug & Play -  Dimmable Driver (no mains lead)
- P&P/DT:** Plug & Play - Mains (TRIAC) Dimmable Driver (no mains lead)
- X:** Driver or Dimmer not required (not recommended)

### SEVEN STEP ORDERING

	1	2	3	4	5	6	7
MODEL	HEIGHT	CCT	FIXING	BEAM ANGLE	FINISH	PER SET	POWER
S154	< 1000mm	CW	RF	10	01	X1	P&P
		NW	FF	25	02	X2	P&P/BT
		WW	RFS	40	03	X3	P&P/DA
		VWW	HF	60	04	X4	P&P/DAP
			HFB		05	X5	P&P/DD
			SM		06	X6	P&P/DT
					07	X7	X
					08	X8	
					15	X9	
					16	X10	
					XXX (RAL)		

Example Order Code: S154.300.WW.FF.25.03.X4.P&P

### NOTES:

