



Spectrum MR11 LV Pro display spotlights from Display Lighting are reliable contemporary luminaires constructed from solid brass to ensure a high quality hard wearing finishes.

The design ensures that the spotlights are as unobtrusive as possible so that your products are illuminated to their full potential without obstruction.

- Accept MR11 LED lamps.
- Specialised focused lighting for retail and exhibition showcases.
- Low heat illumination.
- No ultraviolet light so does not fade materials.
- Unobtrusive.
- Bespoke product manufactured to specification.
- Reduces heat emissions and heat build-up in store.
- Reduces energy bills by up to 80%.
- Choice of finishes & fixings.

Technical Specifications

Height: <1000mm (visible height)

Electrical Connection: Plug & Play | Hard Wired (1000mm tails as standard, length can be specified)

Lamp: MR11 LED

Material/s: Aluminium/Brass

Colour Temperature/s: WW (3000K)

CW (4000K) DL (6500K)

Watts: 4W (max')

Fixings: 6 fixing options available (see page 2)

CRI Rating: See LED lamp data

Class: III
IP Rating: IP20
Finishes: 01 - White

02 - Black **03** - Chrome

04 - Polished Brass (Lacquered)

05 - Brushed Chrome

06 - Antique Brass (Lacquered)

07 - Polished Nickel **08** - Brushed Nickel

15 - Brushed Brass (Lacquered)16 - Rose Gold (Lacquered)

XXX - RAL Colours

Tube Support Diameter: 6.50mm

Input Voltage: 12V AC/DC
Beam Angles: 38 Degrees
Warranty: 5 Years
Dimming: Not dimmable

Ordering: 6 step order code (see page 3)





S111 Cowled Lamp

Diameter: 40mm

Adjustment: 90 Degrees (Upwards Facing)

Tilt: 350 Degrees

Material: Brass

Mounting: Vertical or Horizontal

Cap: GU4
Lamp: MR11
Voltage: 12VAC/DC



S112

Diameter: 25mm

Adjustment: 90 Degrees (Upwards Facing)

Tilt: 350 Degrees

Material: Brass

Mounting: Vertical or Horizontal

Cap: GU4
Lamp: MR11
Voltage: 12VAC/DC



S113 Cowled Lamp

Diameter: 40mm

Adjustment: 90 Degrees (Downwards Facing)

Tilt: 350 Degrees

Material: Brass

Mounting: Vertical or Horizontal

Cap: GU4
Lamp: MR11
Voltage: 12VAC/DC



S114

Diameter: 25mm

Adjustment: 90 Degrees (Downwards Facing)


Tilt: 350 Degrees


Material: Brass


Mounting: Vertical or Horizontal


Cap: GU4
Lamp: MR11
Voltage: 12VAC/DC











RF Rear Fixing

Diameter: 20mm **Height:** 25mm

Fixing: M10 x 50mm Metric Fine Thread with Nut & Washer

Cutout Diameter: 11mm

Material: Brass

Mounting: Vertical or Horizontal

FF Face Fixing (Hidden Bezel)

Diameter: 30mm
Height: 25mm
Fixing: Screw Fix
Cutout Diameter: 7mm

Material: Brass

Mounting: Vertical or Horizontal

RFS Small Rear Fixing

Diameter: 20mm **Height:** 25mm

Fixing: M8 x 20mm Metric Fine Thread with Nut & Washer

Cutout Diameter: 9mm
Material: Brass

Mounting: Vertical or Horizontal

HF Hidden Fixing (Floating Cover)

Diameter: 30mm
Height: 25mm
Fixing: Screw Fix
Cutout Diameter: 7mm
Material: Brass
Mounting: Vertical

HFB Hidden Fixing Bezel

Diameter: 27mm **Height:** 12mm

Fixing: Screw Fix (Underside)

Cutout Diameter: 7mm
Material: Brass

Mounting: Vertical or Horizontal

SM 60 Degree Surface Mount Bracket

Width: 25mm
Height: 26mm
Fixing: Screw Fix
Cutout Diameter: N/A

. . .

Material: 1.5mm Steel

Mounting: Vertical or Horizontal



POWER OPTIONS

P&P Plug & Play - Standard On/Off Driver (2m mains lead & UK plug)

X: Driver or Dimmer not required (not recommended)

SIX STEP ORDERING						
	1	2	3	4	5	6
MODEL	OVERALL HEIGHT	FIXING	FINISH	LED LAMP CCT	SPOTS PER SET	POWER
S111 S112 S113 S114	< 1000mm	RF FF RFS HF HFB SM	01 02 03 04 05 06 07 08 15 16 XXX (RAL)	WW CW DL	X1 X2 X3 X4 X5 X6 X7 X8 X9 X10	P&P X

Example Order Code: \$114.450.FF.02.DL.X4.P&I

NOTES:

