

Two Position Waterproof Keyswitch

S1709WP

Flush fitting stainless steel two position WATERPROOF keyswitch. Supplied with WG1 weather gasket and 1 x N/O and 1 x N/C contact.

Specification	S1709WP
Led Current	N/A
Switch Contacts	1 x N/O and 1 x N/C both 500mA @30vdc
Visual Indication	N/A
Integral Sounder Level	N/A
Tamper	N/A
Material	316 Grade Stainless Steel
Dimensions	86mm x 86mm x 2mm (Facia) 47mm galvanised back box
Weight	0.28kg
IP Rating	IP65 front side contact area. To maintain the IP rating a suitable sealant or gasket for the rear of the plate is required
Approvals	UKCA and CE marked, ROHS compliant

Available as:

S1709SM	Two position momentary action keyswitch
S1709ST0	Two position keyswitch trapped in the OFF position
S1709ST1	Two position keyswitch trapped in the ON position
S1709S	Two position keyswitch Stainless steel
S1709STS	Two position keyswitch Stainless Steel with Tamper

Above models are not waterproof

Benefits and Features

- Brushed Stainless Steel
- Supplied with 47mm deep galvanised mounting box for flush fitting
- IP Rated
- Customised versions available on request
- Surface mount using S0610-50

**Dimensions (mm)**