

- L** LABORATORY
- P** PROCESS
- S** SOFTWARE
- A** AUTOMATION

# iPR FS

## EHEDG Certified Inline Process Refractometer

With its certified hygienic design it is suitable for  
almost all applications in food and beverage production



## SPECIFICATIONS

## iPR FS (Food Safety)

Measuring scales	Refractive Index (RI), Sucrose (Brix) (already included) Up to 4 scales freely definable
Measuring range	1.32000 - 1.52000 RI / 0 - 85 Brix
Resolution	0.00001 RI / 0.01 Brix
Accuracy	$\pm 0,00014$ RI* / $\pm 0.1$ Brix*
Reproducibility	$\pm 0.00014$ RI / $\pm 0.1\%$ Brix
Ambient temperature	- 10°C to + 50°C
Sample temperature	0°C to + 90°C
Temperature measurement	NTC sensor for measurement of sample temperature placed inside the prism
Interfaces	2 insulated 4 - 20 mA analog outputs 2 digital output switch (up to 1 A) 1 serial output (RS232, alternatively RS485 or USB)
Power supply	24 V DC
Prism	Sapphire
Light source / wavelength	589 nm, LED
Process pressure (max.)	MPa (145 psi, 10 bar)
Process contact material	Sapphire, Stainless steel
Mounting accessories	VariVent (Tuchenhagen) or APV

\* Standard conditions (589 nm, 20°C)

### Food safety requires certification according to European standard EHEDG. This is comparable to AAA.

- Hygienic design
- Rounded edges
- No slotted screws
- CIP/SIP possible (60 min max.)
- Material in contact with media: stainlesssteel, sapphire, PEEK
- Determination of dry substance
- Determination of mass percent
- Brix measurement
- Standard scales (Brix, Oechsle, Zeiss, Fat, Honey)
- with automatic temperature compensation

### Typical applications of the model

- Sugar industry
- Beverages
- Food (oil from palm, corn, sunflower, soya)
- Essential oil in aroma
- Sweets and chocolate



**SCHMIDT  
HAENSCH**

### Schmidt + Haensch GmbH & Co.

Waldstraße 80-81, 13403 Berlin, Germany  
Tel.: +49 (0 30) 417073-0 Fax: +49 (0 30) 417073-99



SCHMIDT + HAENSCH reserved all rights over texts and as Subject to modification without notice 07/24