

SQUIRREL 450 / 850 SERIES

Eltek
SPECIALIST
DATA LOGGERS

The Squirrel 450/850 series is a cost effective portable data logger with a maximum of 4 or 8 universal inputs.

Easy to use customised data loggers

In common with its bigger brother, the Squirrel 1000 series data logger, it is equipped with impressive specifications, long battery life and a three year guarantee. Models 451 and 851 have 4 or 8 universal inputs respectively, configurable for voltage, current and temperature for both thermocouple and thermistor sensors. In addition a serial interface is available for special applications, including Vaisala weather sensors WMT52 & WXT520.

Key Features

- Modular construction
- Battery or mains operated and easily portable
- Configuration and Metering by:
 - Panel controls and display
 - Locally connected PC (using Darca Software)
 - Remotely connected PC (using Darca Software) via GSM, Ethernet, landline or radio modem
- Multi language set up menu
- Non volatile internal memory providing up 250,000 readings of secure data, with options to expand to 2,000,000 readings
- Readings can be scaled into appropriate units (e.g. m/sec, p.p.m.)
- Low power consumption for long term unattended use/portable operation
- Clearly labelled connector panel for quick on-site installation
- LAN Network adaptor for Ethernet connection
- Optional Text message on alarm using and /or remote access, external GSM modem

452 / 852



Vaisala weather Sensors



Common Features

- Highly accurate: $\pm(0.1\%$ of reading, $+0.2\%$ of range span)
- 12 bit resolution
- Standard internal memory for 250 000 readings
- Sensor power outputs
- External triggers can start and stop the logger
- Environmental: -30 to $+65^{\circ}\text{C}$, 0 to 95° RH non-condensing
- External power supply: 9 to 14V DC (internal battery: 9V)
- Communications via RS232C with auto-baud detect
- Rapid memory download at 38400 baud

Optional Features

- Wall bracket
- AC Power supply MP12U ($110/250\text{AC}$) to 12VDC
- Alarms and threshold can be set for all channels
- Internal memory expandable to 2,080,000 readings
- Outdoor enclosure

Accessories

- Moxa De-311 Serial to Ethernet Convertor
- GSM Modem Kit, for SMS and/or remote access
- Comprehensive range of sensors including RH and temperature probe, thermocouple / thermistor probes, current clamps, pH electrode etc.

*images reproduced with kind permission from Vaisala Ltd. (UK)

Available Models

Model	Inputs	Features	Application
451 / 851	4 / 8 universal	Each channel configurable for temperature, voltage or current input	
451T / 851T	4 / 8 universal	0.1sec Interval (Fast Recording)	
451pH	4 universal (inc. pH)	Supports up to 2 x external pH adaptor modules type *pH-int	
452 / 852	4 / 8 pulse only		
453	1 Event + 8 pulse	Plus 1 x pulse and 1 x event input	
451L / 851L	4 / 8 V/C + 1 thermistor	Includes +/- 10mV range, for use with Hukseflux HFP01 heat flux sensor	Solar radiation
451/851 WXT/WMT	4 / 8 universal + 1 serial	As above, plus serial input for Vaisala WXT520 / WMT52 weather sensor* ¹	Weather (inc. solar radiation)

*¹Weather:

The Vaisala weather sensors are:

WMT52 - wind speed and wind velocity

WXT520 - as WMT52, with rainfall, barometric pressure, RH and temperature.

Vaisala sensors can be powered by the logger batteries/supply. Eltek can supply the Vaisala sensors if required.

* indicates to be ordered separately

System Specification

Logging Modes

Interval / average / event / externally triggered

Log / Scan Interval

1 sec to 24 hours
Optional: 0.1 sec minimum

Analogue Inputs

Accuracy: ±(0.1% of reading, +0.2% of range span)
Common mode range: 15V
Input Impedance: 1MW

Analogue Input Types & Ranges

see tables below

Sensor Excitation

5V / supply voltage - internally selectable

Data memory

Internal memory: 250,000 readings
Option: 2 million readings or PC slot with SRAM card (2 million readings)
Memory modes: stop when full or continuous

Scaling Data

Readings scaled as engineering units

Configuration

Panel controls and display and/or Darca Lite or Darca Plus (PC Software)

Display

2 line, 32-character display for local status monitoring, configuration and stored readings

Communications

RS232 half duplex - 2400 to 38.4K Baud
Modem compatible protocol

Darca Software

Darca Plus for control, download and export, plus graphing and analysis tools

Power supply

Internal: 6 x AA Alkaline batteries
External: 9 to 14 VDC (1.4 watts)
Mains adapter: 12 VDC 6 watts

Battery Life: sampling 8 channels every 5 minutes provides typically 6 months operation

Case

Scratch resistant Nextel coated ABS
width 180mm, height 120mm,
depth - see table below

Operating Environment

Temperature range: -30 to 65°C
Humidity: 95% non condensing.
For harsh environments an optional IP67 enclosure is available

Range specification

Each channel can be individually set to any of the following ranges:

Temperature:

Input type	Range °C	Resolution °C
U thermistor	-50 to 150	0.1 (-25 to 100)
		0.2 (-40 to 125)
		0.4 (-50 to 100)
K: thermocouple	0 to 900 -200 to 450	0.5
		0.2
T: thermocouple	-200 to 350	0.2

Voltage/Current:

Each V/C channel can be set to any of the 18 voltage or 2 current ranges.

50µV Resolution	0.5mV Resolution	5mV Resolution
0 to 50mV	0 to 500mV	0 to 5V
-25 to 25mV	-250 to 250mV	-2.5 to 2.5V
0 to 100mV	0 to 1V	0 to 10V
-50 to 50mV	-500 to 500 mV	-5 to 5V
0 to 200mV	0 to 2V	0 to 20V
-100 to 100mV	-1 to 1V	-10 to 10V

Pulse:

Maximum frequency: 5Hz
Maximum pulses counted per logging interval: 65,000

10mV Hukseflux range	Resolution	Range	Resolution
± 10mV	5µV	0 to 20mA 4 to 20mA*	10µA 0.05%

* displayed as 0-100%

CE **Guarantee:** Equipment manufactured by Eltek is guaranteed against faulty materials or workmanship for three years. For repairs carried out under guarantee, no charge is made for labour, materials or return carriage.

Eltek

Specialist Data Loggers
Eltek Ltd, 35 Barton Road, Haslingfield
Cambridge, CB23 1LL, England
Tel: +44 (0) 1223 872111
Fax: +44 (0) 1223 872521
email: sales@eltekdataloggers.co.uk
http://www.eltekdataloggers.co.uk