



## Cibes A4000


The mini-sized platform lift

The platform lift to improve your home and make every day life easier!

- Especially designed for private homes and small spaces
- A wide range of finishes, accessories and options
- Safe, reliable and easy to use
- Simple installation and maintenance
- A certified quality product







# Our mini-sized platform lift: Cibes A4000 is especially designed for private homes and apartment buildings. With a wide range of options and accessories the lift will not only blend into your home, it will compliment it!

For almost any living space where you need freedom and increased accessibility, Cibes A4000 is a great solution. Choose Cibes A4000 to improve your quality of life and to increase the value of your home. Tailor made your lift solutions thanks to our variety of accessories and options, choose among different lightnings, door openers, or from hundreds of RAL colours.

- Shaft with steel panels in traffic white RAL 9016, as standard
- Steel doors finished in traffic white RAL 9016 with panoramic window as standard

#### Comfortable & easy to use

Simply press the hold-to-run button on the platform and the lift will take you to another level. Silent, easy to use and well integrated.

### High quality & safety

Safety edges, emergency lighting and an alarm button guarantees that you feel completely safe. In case of emergency an electric lowering system is included as standard.

#### Simple installation

Installation is done by our worldwide network of distibutors within a few days thanks to the preprepared construction kit. No pit is necessary and the lift can be floor mounted without causing any damage to your home.

TECHNICAL FACTS - CIBES A4000	
Rated load	300 kg
Rated speed	0.15 m/sec (9 m/min)
Travel	max 4 m landings, 13 meters
Platform dimensions	830×800 (w × d, mm)
Footprint dimensions	993×1200 (w × d, mm)
Shaft Option	Steel panels finished in traffic white RAL 9016 Glass panels with aluminium profile
Door configuration	Single-entry, open through (A, B & C-side)*
Doors	Single hinged doors Steel door fronts finished traffic white RAL 9016.
Options	Aluminium door made in natural anodized aluminium (on A, C-side) Fire resistant doors El60, according to EN 81-58 Gates (on A, C-side)
Door dimensions	700×2000 mm
Gate dimensions	700 x 1100 mm (lifting height <3 m)
Control system	Micro computer based
Power supply	400 V, 3-phase 50/60 Hz, 16 A starting current Soft start and stop as option: 220-240 V 1-phase frequency converter 380-400 V 3-phase frequency converter
Motor power	2,2 kW
Options	Telephones, locking systems, concealed automatic door openers, elbow buttons, IR-control, automatic shaft lighting, arrival bells, level indicator etc
Directives and Norms MD2006/42/EG, EN 81-41	

<sup>\*</sup> Only A20 and A10 apply for B-side

