


## Technical Specification

# Folding Sliding Door System



Designed for both the domestic and commercial market our Folding Sliding Door System is made to bespoke requirements in numerous design configurations.

Features include multipoint locking and shoot bolts as standard, and units will accept toughened or laminated safety glass in thicknesses of 24mm-32mm. A low threshold option with a 13mm step can be specified. A choice of slimline handle styles is also available to ensure neat door stacking and effective use of space.

Utilising the popular bottom-hung arrangement for efficient operation, hardware options include nylon or stainless-steel wheels ensuring smooth and consistent operation.

### Configurations

- All even/even and even/odd combinations can be specified
- Open in or open out
- Open left, right or split
- Floating external corner
- Floating mullion

### Design Features


- Single or dual colour powder coating
- Will accept double or triple glazing
- Flush or rebate track
- Bead design options
- Cill size options
- Hardware options\*

*\*Heavy duty hardware only PAS24 accredited.*

## TECHNICAL SPECIFICATION

Application	Residential new build, refurbishment and light commercial
Maximum door leaf width	1000mm
Maximum door leaf height	2300mm with standard lock
Maximum door leaf height	2700mm with tall door lock KAS538-TDL
Maximum door leaf weight	100kg
Joining	Mechanical
Glazing options	Will accept double or triple IGU and infill panels 24 -32mm thick
Beading	Internal
Cills	Design coordinated to rest of residential range
Thermal performance	Polyamide thermally broken profiles - Document L1A, L1B/L2A, L2B compliant
U-Value	1.6W/m <sup>2</sup> K
Security	Multi-point dead latch and bolt and lever/lever handset
Finishes	Mill finish. Etched and anodised Silver AA25 or colours on request. Polyester powder coat paint. See separate list for standard colour range available.
Single or dual colour profiles	Option
Design standards	BS EN 12020-2:2001 <i>Aluminium and aluminium alloys, extruded precision profiles.</i> BS 3987:1991 <i>Specification for anodic oxide coatings.</i> BS EN 12206-1:2021 <i>Paints and varnishes, coating of aluminium and aluminium alloys.</i> BS 4873:2016 <i>Specification for aluminium alloy windows and doorsets.</i> BS EN 14351-1:2006+A2:2016 <i>Windows and doors, performance characteristics.</i> BS EN ISO 10077-2:2017 <i>Thermal performance of windows, doors and shutters.</i> PAS 24:2016 <i>Enhanced security performance requirements for doorsets and windows.</i>

Configurations (Typical combinations shown. All even/even and even/odd combinations can be specified.)



**KESTREL**  
ALUMINIUM SYSTEMS

**Kestrel Aluminium Systems Ltd.,** 180 Rupert Street, Aston, Birmingham, B7 5DT

Tel: **0121 333 3575** • Fax: **0121 333 5335** • Email: **info@kestrelaluminium.co.uk** • **www.kestrelaluminium.co.uk**



We operate a continuous development programme and we reserve the right to amend specification without prior notification. Please contact the technical department for further information.  
All copyright, trademarks and registered design rights for the products detailed in this brochure are the property of Kestrel Aluminium Systems Ltd.

