



High Value Added Series - The most versatile and user-friendly pad printer



Automatic PAD CLEAN J

on ink cup model only

OPTIONAL



Open ink tray



2-4 color Conveyor



2-4 color Pneumatic Shuttle

SPECIFICATIONS

Ink cup:	Ø 60, 70, 90, 130 mm
Ink cup plate size:	100 x 250, 150 x 300 mm
Ink tray plate size:	150 x 150 mm - 450mm
Max. speed: (dry cycle)*	1,200 Cycles / hr.
Max. pad pressure:	1,870N at 6 Bar / 100 PSI
Power:	110/220V 50/60Hz 30W
Air consumption:	230 Litre / Min. (Approx.)
Size: L x W x H	890 x 740 x 1,510 mm
Weight:	150 Kg (Approx.)

Please note that actual output may be affected by print requirement, ink drying condition, load/unload arrangement, pad stroke speed, pad hardness, production setup, product quality and production control.







Oriel House, Block F, Sunbury Business Centre Brooklands Close, Sunbury on Thames, TW16 7DX TEL: 01784 460500 FAX: 01784 460505 EMAIL: info@tampo.co.uk www.tampo.co.uk

FEATURES

- Single or multi-color automatic pad printer
- Rigid aluminum casting machine frame
- Use sealed ink cup or open ink tray setup
- Compatible with long life, economy of Green plate, 10 mm steel plate, thin steel plate and polymer plate
- Dead-on printing plate registration for quick job change
- Microprocessor with membrane switch control panel
- Automatic pad clean with programmable cleaning cycle (on ink cup model only)
- Special functions: double ink / print cycles, dwell and delay before print
- Digital pad stroke (DPS) for variable printing depths
- Newly improved MS-150 machine stand enhances stability
- Hardened ground steel shaft with impregnated bushing ensure friction-free movement
- High speed and smooth machine operations