

# KCNC

A fully computerised pad-printing machine. Designed for complex, multicolor, multi-position, high precision printing jobs. Ideal for no-man operation.





Ideal for complex jobs, multi-positions large/ long products

\* In relate to various different printing movement, parameter, extra fee may be needed to be involved. Need process under monitoring with the guideline of experienced Kent Technician.

Features you only can find at the KENT-KCNC pad printing machine

### **FEATURES**

- A true CNC pad printing machine
- PLC control with touch panel interface
- 3-axis servo motor drive
- Sealed ink cup system
- Large printing area 350 mm x 750 mm
- Programmable print sequence
- Unlimited job memory by PC \*
- · Laser beam pad positioning
- Dead-on printing plate registration
- Auto pad height measure
- Auto pad stroke control
- Auto pad change
- Auto pad cleaning
- Affordable price
- Safety light beam curtain
- Enclose cabinate with air filter inlet & exhaust fan
- Product in/out slide or rotary table (optional)

### **SPECIFICATIONS**

#### X movement 1,200 mm pad across

Y movement 550 mm pad in/out

#### Z movement 200 mm pad up/down

Speed: 1 meter/sec. movement speed 2.5-3 sec./dry cycle, actual speed depends on image size

Accuracty: +/- 0.025 mm Repeatability: +/- 0.02 mm

Max. no. of pad:

No. of image: Programmable Programmable

No. of prints:

No. of color:

Max. pad diameter: 145 mm Max. pad height: 120 mm

165 mm Max. ink cup size:

Max. no. of cups: TCIC-165 x 5 pcs.

Power: 220V 3 phase Weight: Approx. 1,300 kgs

Measure (LxWxH): 1,900 x 1,500 x 1,950 mm













# KCNC

User-friendly: to set up a complex printing job is as easy as setting up any ordinary KENT single color printer.

## **FEATURES**




Auto pad change



Two Auto pad cleaning attachment



Safety light beam curtain



Laser beam detect image center



PLC control with touch screen interface



Move along X,Y,Z axis by CNC robot



Innovative auto adjustable tilting jig for multi-angle printing



Air filter









