

7402/IP LCC Vandal resistant coded panel



Rock Inox 7402/IP LCC - stainless steel, digital IP panel.

The fascia is manufactured in 2.5mm thick, ANSI 304 stainless steel boasting a 5mm thick polycarbonate camera window and TFT protector, 3.5" colour TFT LCD, stainless steel keypad with blue illumination and a reserved space for the easy addition of a proximity reader.







Q 020 8368 1935

(f) /GolmarSystemsUK

www.golmarsystems.com

⋈ sales@golmarsystems.com



- Acoustic acknowledgement signal and text message on the display of the door panel confirming the call is in progress or the system is busy.
- Calls can be transferred to a selectable IP address if the apartment unit called does not reply or during a set period of time.
- Dedicated button for direct call to concierge.
- One hundred access control codes of up to six digits each.
- Two potential free relay outputs, for the connection of lock releases, with selectable lock activation time from 1 to 59 seconds.
- The maximum number of units inside the same apartments is eight.

Key Features:

- Server less system not requiring a computer connected to the network.
- 640 x 480 VGA camera with **120**° wide angle lens and LED for night vision.
- Video streaming at 25 fps, with adjustable bandwidth from 1Mb to 7 Mb.
- Audio level and microphone sensitivity regulation.
- Panel identity, to be shown on the monitor during call reception, video spy and auto switch-on functions and picture memory.

Dimensions: 155(W) x 370(H)mm.



Compatible with:

Nhea Hands free IP audio unit Beoview4 Hands free,4.3" colour IP monitor Beoview7 Hands free, 7" colour IP monitor

Select mounting preference:

CE-7402 embedding box

Dimensions: 137(W) x 352(H) x 50(D)mm

7874/IP Surface box with integrated rainshield.

Dimensions: 160(W) x 375(H) x 55 - 70(D)mm



2 133 High Road, New Southgate, London N11 1PP

02083681935

()/GolmarSystemsUK

(a) www.golmarsystems.com

☑ sales@golmarsystems.com