

TYPE 1 MUGA

- 120 SURFACING FOR MULTI SPORTS AREA
- Type: Open Textured Porous Macadam MUGAs
 - Performance: To BS 7044-4
 - Class: Sport England MUGA, Construction of Multi Use Games Areas
 - Anticipated usage: to be confirmed
 - Priority of activities: 1. 5-a-side football, 2. Athletics, 3. Basketball, 4. Tennis
 - Standard of play: Recreational
- 125 COATED MACADAM PAVING – TYPE 1 MULTI USE GAMES AREA
- Sub-base: Base Course Macadam
 - Thickness: 200mm Type 1 MOT
 - Thickness: 50mm Open Textured 20mm aggregate binder course macadam
 - Thickness: 25mm Open Textured 6mm aggregate wearing course macadam
 - Manufacturer: Sports & Safety Surfaces, Tel: 01625 445766
 - Performance: To BS 7044-4
 - Class: Sport England MUGA, Construction of Multi Use Games Areas
 - Anticipated usage: to be confirmed
 - Priority of activities: 1. 5-a-side football, 2. Athletics, 3. Basketball, 4. Tennis
 - Standard of play: Recreational
- 232 COATED MACADAM ACRYLIC ANTI SLIP COATING
- Wearing Course: Open Textured Porous Macadam with acrylic anti-slip coating
 - Manufacturer: Soft Surfaces Ltd, 35 Water Lane, Wilmslow, SK9 5AR
 - Tel: 01625 445760, Fax: 01625 525619
 - Email: info@softsurfaces.co.uk Website: www.softsurfaces.co.uk
 - Description: [Acrylic Colour Coating](#)
 - Product Details: Anti Slip Paint contains silica to achieve a slip resistance of 60 TRRL
 - Colour: From standard colour range
 - Health and Safety: CHAS accredited, API accredited, CONSTRUCTIONLINE accredited
 - Ignitability: The surface, when tested to BS 4790, must not be ignited or damaged enough to cause a ball to deviate from its true path: Not permitted
 - Joints: Must not significantly affect the playing performance.
- 420 LINE MARKINGS TO MACADAM SURFACES
- Method of application: Fully textured water based acrylic line mark paint
 - Colour: White for primary sport then others on request (generally red, green, yellow, blue)
 - Width: 50mm unless requested otherwise

COMPLETION

- 930 DOCUMENTATION
- General: For all types of surfacing, provide the following:
 - Name and contact details of installer.
 - Date of installation.
 - Name and contact details of manufacturer.
 - Type/ description/ reference of products used.
 - Manufacturer's recommended inspection and maintenance procedures to maintain safety and impact absorbing performance.
 - Manufacturer's recommended cleaning and maintenance methods, where relevant.