

Q26 Special surfacing/ pavings for sports/ general amenity

IMPACT ABSORBING SURFACINGS FOR PLAY AREAS

- 300 EXTENT OF IMPACT ABSORBING SURFACING
- General: Lay to the impact areas shown in the relevant parts of BS EN 1176.
- 301 EXTENT OF IMPACT ABSORBING SURFACING
- General: Lay impact absorbing surfacing as indicated on drawings.
- 360 IN SITU [SYNTHETIC SURFACING](#)
- Sub-base: Base Course Macadam
 - Thickness: 125mm Type 1 MOT
 - Thickness: 50mm Open Textured Porous 20mm aggregate binder course macadam
 - Manufacturer: Sports & Safety Surfaces, Tel: 01625 445766
 - Base: 2-6mm SBR rubber granule material
 - Thickness: To suit the test certificate BS EN 1177
 - Surface Course: [Wet-Pour](#), in situ laid polyurethane bound EPDM rubber crumb surface.
 - Standard: To BS 7188
 - Manufacturer: Soft Surfaces Ltd, 35 Water Lane, Wilmslow, SK9 5AR
 - Tel: 01625 445760, Fax: 01625 525619
 - Email: info@softsurfaces.co.uk Website: www.softsurfaces.co.uk
 - Colour: From standard colour range
 - Features: From wide range of graphics available, Tel: 01625 445760
 - Critical Fall Height when tested to BS EN 1177: TBC
 - Health and Safety: CHAS accredited, API accredited, CONSTRUCTIONLINE accredited
Substance known to be toxic or carcinogenic on skin or released as vapour or dust during normal use: Not permitted.
 - Submit:
 - Resistance to abrasive wear, slip resistance, resistance to indentation and ease of ignition: Evidence of testing to BS 7188.
 - Critical Fall Height: Evidence of testing to BS EN 1177.

COMPLETION

- 920 PLAY SURFACE TESTING
- Standard: To BS EN 1177 and BS 1177, where applicable.
 - Testing Body: A United Kingdom Accreditation Service (UKAS) independent laboratory.
 - Timing: Within ten days of completing the surface works.
 - Test Results: Submit.
- 930 DOCUMENTATION
- General: For all types of surfacing, provide the following:
 - Name and contact details of installer.
 - Date of installation.
 - Name and contact details of manufacturer.
 - Type/ description/ reference of products used.
 - Manufacturer's recommended inspection and maintenance procedures to maintain safety and impact absorbing performance.
 - Manufacturer's recommended cleaning and maintenance methods, where relevant.
- 940 LABELLING
- Signs: Provide permanent labelling in approved locations on all types of surfacing stating:
 - Critical Fall Height;
 - Date of Installation
 - Manufacturer's name and contact details; and
 - Product name.