

AC/DC power supplies - linear - regulated



- Laboratory power supply
- Stepless adjustable constant voltage
- Adjustable constant current source
- The unit has volt/ampere meter
- Terminals for remote sense
- 4 mm insulated terminals (for banana plugs)
- Laboratoriestrømforsyning
- Trinnløs justerbar konstantspenningskilde
- Justerbar konstantstrømskilde
- Instrument for måling av spenning og strøm
- Uttak for fjernsense
- Bøssing for bananplugger

Technical specifications Tekniske data

Input voltage:	Inngangsspenning:	230 VAC +6/-10%, 50/60 Hz
Output voltage (regulated)	Utgangsspenning (stabilisert)	
• Range 1:	• Område 1:	0-15 V
• Range 2:	• Område 2:	0-30 V
Max. output power (at 30 V):	Maks. utgangseffekt (ved 30 V):	45 W
Max. load current	Maks. laststrøm	
• Range 1:	• Område 1:	2,0 A
• Range 2:	• Område 2:	1,5 A
Load regulation (at 15 V output):	Lastregulering (ved 15 V utgang):	< 1,0 mV
Line regulation (2 A load current):	Linjeregulering (2 A laststrøm):	< 1.0 mV
Temperature range:	Temperaturområde:	-200C - +500C
Ripple:	Rippel:	0,3 mV RMS
Current limiting (adjustable from):	Strømbegrensning (stillbar fra):	20 mA, "Fold back"
Insulation class:	Isolasjonsklasse:	II
Electrical safety standard:	Elektrisk sikkerhetsstandard:	EN 60065
EMC standards	EMC standarder	
• Emission:	• Emisjon:	EN 61000-6-3
• Immunity:	• Immunitet:	EN 61000-6-1
Dimensions (LxWxH):	Mål (LxBxH):	180 x 94 x 145 mm
Weight:	Vekt:	2,9 kg

