

CPD 1502

Max. 60 W

AC/DC POWER SUPPLIES - LINEAR - REGULATED

- Laboratoriestrømforsyning
- 3 sifret panel instrument
- Trinnløs justerbar konstant-spenningskilde
- Justerbar konstantstrømskilde
- Kortslutningssikker
- Nettledning
- Bøssing for bananplugg
- Lysdiode viser konstant strøm/spenning modus
- Laboratory power supply
- 3 digit panel meter
- Stepless adjustable constant voltage
- Adjustable constant current source
- Short circuit proof
- Mains cord
- 4 mm insulated terminals (for banana plugs)
- LED for constant current/voltage operating mode



Tekniske data	Technical specifications	
Inngangsspenning (valgbar):	<i>Input voltage (selectable):</i>	115/230 VAC, 50/60 Hz
Utgangsspenning (stabilisert)	<i>Output voltage (regulated)</i>	
• Utgang 1:	• <i>Output 1:</i>	0 - +15 V
• Utgang 2:	• <i>Output 2:</i>	0 - -15 / 0 - +30 V
Maks. utgangseffekt:	<i>Max. output power:</i>	60 W
Laststrøm	<i>Load current</i>	
• Utgang 1:	• <i>Output 1:</i>	0 - 2,0 A
• Utgang 2:	• <i>Output 2:</i>	2,0 A
Konstant spenning modus	<i>Constant voltage mode</i>	
Lastregulering (null til full last):	<i>Load regulation (zero to full load):</i>	±0,02% ±2 mV
Linjeregulering (± 10% nettvariasjon):	<i>Line regulation (±10% line variation):</i>	±0,02% ±2 mV
Rippel og støy:	<i>Ripple and noise:</i>	1 mV RMS max., 20 Hz - 20 MHz
Konstant strøm modus	<i>Constant current mode</i>	
Lastregulering (null til full last):	<i>Load regulation (zero to full load):</i>	±0,5% ±250 uA
Linjeregulering (± 10% nettvariasjon):	<i>Line regulation (±10% line variation):</i>	±0,5% ±250 uA
Temperaturområde:	<i>Temperature range:</i>	0 - +50°C
Temperaturkoeffisient (15 min. oppvarming):	<i>Temperature coefficient (15 min. warm-up):</i>	±0,02% / °C
Isolasjonsspenning	<i>Insulation voltage</i>	
• Inngang - utgang:	• <i>Input - output:</i>	2500 VAC
• Inngang - jord:	• <i>Input - ground:</i>	2000 VAC
• Utgang - jord:	• <i>Output - ground:</i>	500 VAC
Stabilitet (8 t etter oppvarming):	<i>Stability (for 8 h after warm-up):</i>	±0,1% plus 2,5 mV
Mål (LxBxH):	<i>Dimensions (LxWxH):</i>	260 x 95 x 185 mm

19062006

www.mascot.no
sales@mascot.no

Phone:
Fax:

Main Office
PO Box 177
N-1601 FREDRIKSTAD
NORWAY
+47 69 36 43 00
+47 69 36 43 01

Mascot UK
Box 2090, Salisbury
Wiltshire SP2 2BH
UK
+44 1722 504 853
+44 845 299 1210

Mascot DE-AT-CH-BENELUX
Hirschbergstr. 28/7
D-74838 LIMBACH
WANGEN
GERMANY
+49 6287 95140
+49 6287 95141

Tettninger Str. 52
D-88239
GERMANY
+49 7528 951677
+49 7528 951678

Mascot France
38 rue Leo Lagrange
94270 Le Kremlin Bicêtre
FRANCE
+33 1 46 58 71 85
+33 1 46 58 71 85