


- Plug-in unit
- Fixed output voltages
- Thermal fuse in transformer and thermal protection in the regulator
- Exchangeable output plugs
- Plugg-inn enhet
- Faste utgangsspenninger
- Termosikring i transformator og termisk beskyttelse i regulator
- Utskiftbare plugger



Technical specifications

Input voltage:
 Output voltage:
 Max. output power:
 Ripple:
 Insulation class:
 Electrical safety standard:
 EMC standards
 • Emission:
 • Immunity:
 Output terminals
 Cord with/without plug:
 Dimensions excl. plug (LxWxH):
 Weight:

Tekniske data

Inngangsspenning: 230 VAC +6/-10%, 50/60Hz
 Utgangsspenning: 5-24 VDC
 Maks. utgangseffekt: 4,8 W
 Rippel: < 30 mV p-p
 Isolasjonsklasse: II
 Elektrisk sikkerhetsstandard: EN 60065, EN 60950
 EMC standarder
 • Emisjon: EN 61000-6-3
 • Immunitet: EN 61000-6-1
 Utgangsterminaler
 Sek. ledning med/uten plugg: Accessories /Tilbehør
 Mål uten plugg (LxBxH): 95 x 51 x 57 mm
 Vekt: 420 g

Voltage version (VDC) Spenningsversjoner (VDC)	Nominal load (mA) Merkelast (mA)
5	700
6	600
7,5	600
9	500
12	400
15	340
18	280
24	210