

F.5004

PRO-SCREED UNIVERSAL PRIMER



Floorwise F5004 Pro Screed Universal Primer is a water based, solvent free, acrylic dispersion primer formulated for use as a primer/bonding agent prior to the application of Floorwise F5000 and F5001 Pro Screed Smoothing Compounds.

Uses

In undiluted form it can be used on all smooth and dense surfaces, power floated concrete, ceramic tile, quarry tile, rigid metal, terrazzo, asphalt and surface membranes. In diluted form (1:2 with clean water) it can be used on porous substrates.

Specification

Primer Type:	Acrylic Dispersion Primer
Colour:	Pale Green drying to opaque green
Coverage:	Undiluted: approx. 75-100m ² per 5 litres Diluted: approx. 120-150m ² per 5 litres
Application Temperature:	+5°C – +30°C.
Drying Time:	Under good drying conditions Primer will dry within one hour, although under cold, damp conditions this will be extended.
Storage & Shelf Life:	12 months in original, unopened container stored between +5°C and +35°C. Keep out of direct sunlight. Protect from Frost.
Container Size:	5 litre Polybottles

Directions for Use

All aspects of the installation should be in accordance with the recommendations of BS 8203 (Sheet & Tile Flooring), BS5325 (Installation of Textile Floorcoverings) and BS CP102 (Protection of buildings against water from the ground).

Preparation

Sub-floors should be sound, clean, dry and free from rising damp, grease, dust or any loose material. Floorwise F5004 Pro Screed Universal Primer can be used over traces of old residues, they must be well bonded and non moisture soluble.

Application

Smooth dense surfaces: Apply an even coat using a brush or roller.

Porous surfaces: Dilute Floorwise F5004 Universal Primer 2 parts clean water to 1 part primer and apply using a brush or roller making sure that it is worked well into the surface. A second coat may be required.

Cleaning

Clean tools with warm water containing a little detergent whilst the primer is still wet. Once the primer is dry, use hot water or a solvent such as acetone to clean.

Safe Handling

Mop up spilt material immediately with an inert, absorbent material, such as sand and dispose of in accordance with regulations. Do not leave empty containers on site where residue could be a hazard to children, animals or the environment. Replace lids and remove any containers to a central disposal point. This material and its container must be disposed of as hazardous waste.

Health & Safety

In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. After contact with skin, wash immediately with plenty of water. Seek medical attention if irritation persists. wear suitable protective clothing, gloves and eye/face protection. KEEP OUT OF REACH OF CHILDREN.

This product data sheet is provided for guidance only.

