

F.533 CARPET LATEX ADHESIVE

F.533 Carpet Latex Adhesive is a high solids content, fast-break, rubber emulsion for carpet bonding. It dries to form a strong elastic film with good adhesive properties.

- Non Flammable
- Good Adhesive Properties
- Fast-Break

Uses

F.533 Carpet Latex Adhesive is suitable for bonding:
 CARPETS: rubber backed, foam backed, synthetic woven backed, polypropylene backed, jute backed, Axminster, Action Bac and needlepunch.

Specification

Adhesive Type:	Rubber emulsion.
Colour:	Off White.
Flashpoint:	Non-flammable
Coverage:	Approx 5.5m ² per Litre – On a Single Non Porous Surface.
Application Temperature:	+5°C – +25°C.
Open Time:	A few minutes, depending on temperature, humidity & carpet.
Setting Time:	Set to traffic after 18 hours, fully set after 24 hours.
Storage & Shelf Life:	6 months in original, unopened container stored between +5°C and +30°C.
Container Size:	5 Litre Polybottles.

Directions for Use

Before starting work using F.533 Carpet Latex Adhesive, please refer to the section headed "Handling Precautions" and to the separate Safety Data Sheet.

Preparation

All substrates should be sound, clean, dry and free from rising damp, grease, dust or any loose material.

Application

ONE WAY BONDING: When at least one surface is porous, brush an even coat of F.533 Carpet Latex Adhesive onto the least porous surface, and press the two surfaces together immediately. The fast-break nature of the adhesive enables a satisfactory bond to be formed within a very short time.

TWO WAY BONDING: When both surfaces are non porous, brush each surface with a thin film of adhesive and allow to dry to a tacky translucent film. Align the surfaces accurately, and press the two surfaces together lightly to produce a satisfactory and immediate bond.

Cleaning

Clean tools with warm water containing a little detergent whilst the adhesive is still wet.

Health & Safety

This product contains Ammonia. Sufficient fresh air ventilation must be provided during and after use, to ensure the ammonia levels are kept below those given in HSE Guidance Note EH40. This can usually be achieved by opening doors and windows, but in poorly ventilated areas or confined spaces, mechanical extraction may be required.

Avoid prolonged contact with the skin; use barrier creams or gloves for the hands and wear suitable eye protection. In case of contact with eyes, mouth or nose, wash thoroughly with water and seek medical advice. If spilled remove and dispose of in accordance with national and local regulations for waste materials.

Keep out of reach of children.

This product data sheet is provided for guidance only. For further information and advice on application, or if in any doubt as to the suitability of the product for the installation, please contact our Technical Department for advice and carry out tests on a small area to establish suitability.