

# F.592

## CONTACT SPRAY ADHESIVE



F.592 Contact Spray Adhesive is a versatile spray adhesive.

Its high solids/low solvent formula produces a quicker, stronger, more aggressive bonding system which outperforms all conventional aerosol adhesives. Furthermore it has an excellent high temperature resistance (80°C), making it suitable for a wide range of applications.

- High Adhesives Content
- Excellent Bond Strength
- High temperature resistance (up to 80°C)
- Quick Drying
- Easy to Use

### Uses

F.592 Contact Adhesive is suitable for the permanent bonding of carpets, carpet tiles, most vinyl floorcoverings, PVC skirting, fabrics, cork, paper, underlay, felts and much more.

Not suitable for polyurethane backed or highly plasticised PVC floorcoverings.

### Sub-Floors

Concrete bases, cement screed, anhydrite screed, smoothing & levelling underlayment, flooring grade chipboard, hardboard, plywood, stone, terrazzo, quarry tiles, ceramic, brickwork and plaster. It is also suitable for bonding to metal, glass and most plastics.

### Specification

Adhesive type:	Contact Adhesive
Colour:	Clear
Flashpoint:	Highly-Flammable.
Coverage:	Approximately 3m <sup>2</sup> per can.
Application Temperature:	+5°C – +30°C.
Working Time:	Approximately 10 Minutes depending on temperature, humidity & subfloor.
Storage & Shelf Life:	12 months in original, unopened can between +5°C and +30°C. Store in accordance with requirements of Petroleum Regulations.
Container sizes:	500ml Can.

### Directions for Use

Before starting work using F.592 Contact Spray Adhesive, please refer to the section headed "Handling Precautions" and to the separate Safety Data Sheet.

### Preparation

Surfaces to be bonded should be clean, dry and dust free.

Shake can well before use.

### Application

Spray an even coat of adhesive onto both surfaces. Allow adhesive to become touch dry, which can be almost immediately.

Press floorcovering firmly into place. Allow approximately 10 minutes for adhesive to set. After use, invert can and press nozzle to clear adhesive from the spray tip.

### Cleaning

Remove any overspray immediately with Floorwise solvent cleaner or the minimum of white spirit.

DO NOT USE SOLVENTS TO CLEAN THE SKIN.

### Health & Safety

**Warning:** This material is highly flammable and is a "PETROLEUM MIXTURE".

See safety data sheet for full application instructions and safe handling precautions ([www.floorwise.co.uk](http://www.floorwise.co.uk)).

**Caution:** Pressurised container. Protect from sunlight and do not expose to temperatures exceeding 50°C.

Do not pierce or burn even when empty.

Do not spray onto naked flame or any incandescent material.

**NO SMOKING**

**KEEP OUT OF REACH OF CHILDREN**

F.592 Contact Spray Adhesive SI1950

Contains: DICHLOROMETHANE

Harmful by inhalation and if swallowed.

Limited evidence of carcinogenic effects.

Keep out of reach of children.

Use only in well ventilated areas.

Do not breathe spray or vapour.

Wear suitable protective clothing.

Avoid contact with skin or eyes.

This material must be disposed of in a safe way.

If swallowed seek medical advice immediately and show this container or label.

This product data sheet is provided for guidance only. For further information and advice on application, or if in any doubt as to the suitability of the product for the installation, please contact our Technical Department for advice.

