



SAFETY DATA SHEET

Date of Issue: September 2005

Code: FWG/539/02

Page 1 of 3

1. Identification of the Substance/Preparation and Company

F539 WOOD FLOORING ADHESIVE

Company: Floorwise Group Ltd
Floorwise House, 22 High Street
Kegworth, Derby DE74 2DA
Tel: (01509) 673974 Fax: (01509) 674841

2. Composition/Information on Ingredients

| CAS Number: | Chemical Name: | %: | Classification: |
|-------------|-------------------------------|--------|-------------------------|
| 141-78-6 | INDUSTRIAL METHYLATED SPIRITS | 10-15 | F;R11: Xn, R20/22 |
| | ETHYL ACETATE | 10 -15 | F,R11; Xi, R36,R66, R67 |

3. Hazard Identification:

Contains highly volatile solvents. Highly flammable (R11)

4. First Aid Measures:

Inhalation: Remove to fresh air. If discomfort persists seek medical advice
Skin Contact: Remove contamination with proprietary skin cleaner, followed by washing with soap and water. This procedure should also be followed prior to eating drinking, smoking and toilet functions.
Eye Contact: Irrigate immediately with clean water for 15 minutes and obtain medical attention.
Ingestion: If swallowed, seek medical advice immediately. Do not induce vomiting.

5. Fire-Fighting Measures:-

| | |
|--|---|
| Suitable Extinguishing Media: | Dry Powder, CO ₂ , Foam, Sand, Earth |
| Unsuitable Extinguishing Media: | Never use water jet |
| Special Exposure Hazards in Fires: | None known |
| Required Special Protective Equipment for fire fighters: | Wear suitable protective clothing |



SAFETY DATA SHEET

Date of Issue: September 2005

Code: FWG/539/02

Page 2 of 3

6. Accidental Release Measures:

Precautions: Stem flow of spilled material. Extinguish all naked flames and cigarettes. Take precautionary measures against static discharge. Materials should be mopped up immediately with an inert absorbent material such as sand earth etc.

Prevent spills from entering sewers and drains. Dispose of at an appropriate licensed waste disposal site in accordance with current laws and regulations.

7. Handling and Storage

Handling: Ensure adequate ventilation. Keep containers tightly closed. **No smoking.**

Storage: Should be stored under cover out of direct sunlight and away from sources of heat and ignition in accordance with the Highly Flammable Liquids and Liquefied Petroleum Gases Regulations.

8. Exposure Controls:

UK Occupational exposure standards - EH40

Ethanol 1000ppm, 1900mg/m³ 8HR TWA

Ethyl Acetate 200ppm, 700mg/m³ 8HR TWA

Respiratory Protection: Avoid inhalation of vapours, use local exhaust ventilation. In poorly ventilated areas, a cartridge mask approved for organic vapours is recommended.

Hand Protection: Wear suitable impervious gloves

Skin Protection: Appropriate protective clothing

Eye Protection: Appropriate chemical resistant goggles

9. Physical and Chemical Properties:-

Appearance: Biege Coloured Paste

Flammability:

Odour: Of alcohol

Autoflammability: Approx 360°C

pH: Not applicable

Explosive Properties: L19% Vol LEL 3.5% Vol

Boiling point/boiling point range: Not determined

Oxidising Properties: Not applicable

Vapour Pressure: Not determined

Melting point/ melting point range: n/a

Relative Density: Approx 1.5

Solubility (water and fat) S.Soluble

Flashpoint (°C): Approx 17 - closed cup



SAFETY DATA SHEET

Date of Issue: September 2005

Code: FWG/539/02

Page 3 of 3

10. Stability and Reactivity:

Stable under normal conditions. Avoid excessive heat.

Hazardous decomposition products: Carbon dioxide, carbon monoxide, hydrogen gases.

11. Toxicological Information:

Prolonged exposure to vapours may cause irritation of eyes, nose and respiratory tract.

Prolonged exposure of skin may cause dermatitis.

12. Ecological Information:

The preparation has not been tested.

13. Disposal Considerations:

Material and container must be disposed of as hazardous waste in accordance with local regulations.

14. Transport Information:

UN No. (Adhesives) 1133 Class 3 Packaging Group II

15. Regulatory Information

R11 Highly Flammable

S9 Keep container in a well ventilated place.

S16 Keep away from sources of ignition - no smoking

S51 Use only in well ventilated areas

S60 Keep container in well ventilated place

EEC Symbol F Highly Flammable

16. Other Information:

Uses: Wood Flooring Adhesive

The data contained in this Safety Data Sheet has been supplied as required by the Chemical (Hazard Identification and Packaging Regulations 1994), as amended, for the purpose of protecting the health and safety of industrial and commercial users who are deemed capable of understanding and acting on the information provided.

This information is given in good faith, being based on the latest knowledge available to Floorwise Group Ltd. No known relevant information has been omitted from this Safety Data Sheet and the information provided is designed to enable the user to use the product safely. The user should not assume on the basis of the information provided in this sheet that the product is suitable for any abnormal use. If the information provided is insufficient to ensure safety in any particular application, contact the Floorwise Group for further advice before the proposed application is undertaken.