



## TOSA 115

### AUTOMATIC PALLET STRETCH WRAPPING MACHINE WITH ROTATING ARM

While the pallet lies on the conveyor, the wrapping cycle is carried out by a rotating arm holding a film-roll. A steady and compact packing is guaranteed for all sorts of palletized products by a multilayer wrapping made with stretch film. It is particularly suitable for light and unsteady loads. This machine can be installed on any existing packing line and it perfectly meets low production needs. It is complete with powered pre-stretch unit, film hooking and cutting unit, film sealing unit, boundary safety-guards, control board with PLC





## TOSA 115

### Characteristics:

**It is complete with different adjusting and control units:**

- Film-roll up-down stroke speed variable by Inverter
- Stretchable film tension adjustment
- Photocell for automatic pallet height detection
- Arm rotation start and stop at low speed
- Visual display for fault signal and cycles times setting

**This machine can be equipped with different optional units:**

- Top pneumatic presser
- Power roller conveyor placed inside the wrapping machine
- Power roller conveyors placed either at the entry or at the exit points
- Top sheet dispenser mod. 475



### Technical Data:

Maximum pallet dimension 1000 x 1200 x 2000 H mm

Power supply V.380+N/50 Hz

Installed power Kw 3

Air consumption 12 NI/min

Output 30/60 pallet

Self-adhesive stretch film Roll max. Diam. 250 mm

All the technical specifications are subject to change without notice.