



Haven Automation Limited

Calibration Solutions for Industry

Measurement House, Kingsway,
Fforestfach, Swansea SA5 4EX, UK.
Tel: General: +44 (0) 1792 588722
Sales: +44 (0) 1792 580255
Service: +44 (0) 1792 579696
Fax: +44 (0) 1792 582624
Email: mail@haven.co.uk
Web: www.haven.co.uk

DIP COOLERS

The Dip Cooler enables the OTB-8HT Oil/Water Bath to reach below ambient temperatures down to -35°C.

The cooling head of the Dip Coolers fit neatly and unobtrusively into the corner of the standard circulating bath and can be secured with a specially designed mounting bracket. Even if cooling can be achieved by cold tap water, a dip cooler is recommended as it conserves water and is easier and more convenient to use.



	RU-200	RU-500
Minimum Achievable Temperature* (°C)	-20	-35**
Cooling Capacity @ 0°C (watts)	145	240
Cooling Capacity @ 20°C (watts)	145	240
Cooling Capacity @ -10°C (watts)	110	230
Nominal Dimensions (Excluding handles etc) mm		
Width	235	370
Length	420	430
Height	300	325
Coil Dimensions (mm)		
Length	85	85
Diameter	75	75
Weight (kg)	19	39

* In a well insulated 7 litre bath system, at an ambient of 20°C.

** At ambient of 20°C, using a mixture of 40% water, 40% antifreeze, 20% alcohol to achieve -35°C.

