


Opening Doors Worldwide!

Profile System  
SLIDEDOOR Profile System LR 22B



★★★★★  
**TORMAX**  
AUTOMATIC



## The Universal Profile System

SLIDEDOOR Profile System LR 22B is the ideal product in the range of the TORMAX profile systems. This system not only convinces users by its simple handling, but also by its particularly well thought-out total concept.

Combining the compactness of a light frame profile, it can easily carry insulating glass up to 23 mm for dry glazing and 28 mm for wet glazing. Cleverly solved details for connections using specific rubber seals and brushes ensure an optimum tightness. The SLIDEDOOR Profile System LR 22B is the universal solution for all TORMAX automatic doors.

### Application

- Optimum combination with all TORMAX sliding door drives
- For fixed leaves and sliding leaves
- Straight or curved door leaves
- Single sheet or insulating glazing

### Advantages

- Dry or wet glazing to be carried out easily
- Slim design allows elegant door construction
- Low-noise leaf guide thanks to non-abrasive plastic glider, on surface or in-ground construction
- Complying with safety norms – high individuals safety
- Cleverly solved details, such as:
  - installation of light beams
  - finger guard
  - seals installation
  - floor guide

### Technical Specifications

Dimensions	
Facial width	30 mm
Base height	78 mm
Profile depth	34 mm
Glass thickness	
dry	8.5 – 10 mm
wet	21.5 – 23 mm
Seal of the sliding leaves	simple, surround
Norms adhered to	ZH 1/494 prEN 12650 ≤ 8 mm between sliding and fixed leaf according to CEN safety standards

