


Spot light source

# LIGHTNINGCURE™ SERIES

Lamp warranty: Guarantees a long operating life of 4000 hours

## LC8



Light guide is sold separately.  
Computer is provided by the customer.

# Two new functions for making photocuring simple and reliable!

## 1 Operate it from your PC via the RS-232C port.

LC8

This unit has a built-in RS-232C port to allow PC or micro-computer control that was impossible up until now. Making program entries (irradiation intensity, irradiation time) for the Memory Step is now accurate and easy. You can operate the light source even in a location where direct access to it is impossible.


Using the USB adaptor connector lets you use a PC even if it has no RS-232C port. We also offer sample software that displays easy-to-use setup screens, etc.



Memory Step setting dialogue

Light source control dialogue

### When PC starts communication



Communication is started by PC and finished by the result code sent from the unit.

## 2 Light intensity monitor with internal optical feedback function

(Option: Sold separately)

LC8

This unit maintains the light intensity at a fixed level for stable irradiation. Light intensity usually varies over time during lamp operation. Our light source, however, can constantly maintain the preset light intensity since it regulates light intensity while monitoring it with an internal sensor.

This spot light source also has internal light feedback and so does not need a dedicated feedback light guide used in conventional products.

The irradiation intensity (reference value) is displayed as a digital value (in watts) on the LCD display. This eliminates problems that occur due to human error and different operating conditions. Full control even of detailed settings makes it ideal for fully automated production lines.



Display screen showing W (watts units)

## Feature Memory Step™ for 9 types 7-step programs

LC8

Program the irradiation intensity and irradiation time to any level you want! Freely set the UV irradiation conditions to match the component you want to bond.


The LIGHTNINGCURE LC8 lets you store 9 types of 7-step programs in the memory, so optimal irradiation conditions matching the component for bonding can be set just by changing the program number. This holds true even when multiple bonding components are flowing in the same production process or when shifting to different production lines.

The LC8 is especially ideal for components that must be fixed in place with high precision. The mounting positions of these components often deviate due to stress warping and contraction in the adhesive that causes positional shifts. Using the LC8 gives better production stability and higher product yield especially for components demanding high position precision.

### Program example 1: Increasing light intensity in 7 steps

Shutter "open" between steps


Shutter "closed" between steps



### Program example 2: Random light intensity and irradiation time settings

Shutter "open" between steps


Shutter "closed" between steps



### Program example 3: Low light intensity and then long-term high intensity

Shutter "open" between steps

Shutter "closed" between steps





# LIGHTNINGCURE LC8


**"Easy Maintenance" "Great Energy Saving"**

## FEATURES & FUNCTIONS

### Long service life

**Guaranteed service life: 4000 h (-01A type and -02A type)**  
 UV intensity generally declines with lamp operating time. Hamamatsu has drastically improved these drops in light intensity by using a mercury-xenon lamp whose electrodes suffer almost no wear and an improved optical system.

● **Variations in UV intensity [365 nm] over time (typical values)**



### Anybody can use it! One-touch replacement!

Lamp is replaceable in less than 30 seconds!  
 Just insert the lamp to replace it. No wiring to worry about. This is so easy you can do it with one hand.  
 Lamp is the cassette type with a preset optical axis so no troublesome optical alignment is needed after replacement.



### Full line-up of external control equipment

(RS-232C and D-sub connector: standard feature, terminal block: option E9795-01 [sold separately])


You can turn the lamp on and off and control the shutter externally. An alarm signal output is also available. Signals and data can be exchanged with the PC via the RS-232C. This unit will prove ideal for production environments such as semi-automated or fully au-



Upper: D-SUB connector  
 Under: RS-232C

### Clever layout allows a compact body

Superb features are concentrated into a compact body. Weight has been reduced to a mere 6.4 kg. Area of installation can be reduced. Stacking the units allows saving even more space.



Unit: mm

### Great energy saving benefits

Our 200 W lamps have high intensity equal to lamps in the 250 W class. Light sources using our 200 W lamps also have less power consumption than those using 250 W lamps. Power consumption is the lowest in its class (280 VA Typ.). This means using multiple UV light source units at production facilities will yield tremendous energy saving benefits.

### Instantaneous power-outage response program

Restores operation in about 10 seconds after power outages of a second or less. Conventional products take at least a few minutes to start up again after a power shutdown, so you can see this function drastically shrinks downtime due to power outages. This function is especially convenient in places where the supply of power is intermittent or unstable.

### Power supply compatible in world-wide

Internal power supply automatically switches to a 100 V or 200 V input. There is no problem when shifting the operating location in world-wide.



### CE marking compliance

The LIGHTNINGCURE complies with CE marking requirements and can also be used in Europe.

**Meets the following standards**

- Safety standards: IEC 61010-1
- EMC standards: IEC 61326-1 Group 1, Class A

### Selectable positions of light guide port

A front port type and a rear port type are available. The front port type allows lamp replacement from the operation panel side. This helps hold limits on equipment movement and installation location to a minimum. Select the light guide port position that best matches the component for bonding and its mounting position.




Left: Rear light guide port type L9566, Right: Front light guide port type L9588

### Light intensity adjustable anywhere within 0 to 100 %!

An electric diaphragm mechanism allows a digital display of the relative light output from 0 % to 100 % on the LCD panel. Unlike conventional analog scales, this means highly precise light irradiation. Light output also can be controlled from an external device, so meeting various kinds of measurement conditions is now even easier.

#### Output intensity vs. panel display




# "Long Life" "High Output"

## STRUCTURE

### Easy filter replacement

A single screwdriver is all you need to replace the filter via the upper filter insertion port. There is no need to open any cover as on conventional units, so you save even more replacement time.




Filters and filter holder are sold separately.

### High efficiency optical system - no heat problems

The LC8 combines a mercury-xenon lamp having high-intensity UV line spectra with an elliptical reflector (UV cold mirror) having reflectivity higher than 90 % in the UV range and a quartz light guide with excellent UV transmittance.

The lamp can be operated in a horizontal position, so the optical system has less light loss compared to lamps operated in an upright position, allowing the UV light to input efficiently to the light guide. The elliptical reflector efficiently reflects only the UV light, and lets heat rays and visible light pass through to prevent adverse effects from heat on the irradiated point.

#### ●Structural View



TLSXC0040EC

### No optical axis alignment

Uses a highly stable mercury-xenon lamp\* developed expressly for analysis and measurement applications. There is almost no wear on the electrodes and no positional shift of the arc point. Absolutely no optical axis alignment is needed, even during lamp replacement or during lamp use.

#### ●Electrode wear



Before use



After 4000 hours of use

## CHARACTERISTICS


### Selectable wavelength

The LC8 allows you to select the wavelength range you need. The "-01A" type suitable for wavelengths around 365 nm and the "-02A" type enhanced for 250 nm band are provided. Select the light source that matches the adhesive agent you use.

These can also be combined with UV-transmitting filters that cut visible and infrared light, and minimize heat effects on the irradiated point.

A visible light type is also available (radiant wavelength range from 400 nm to 700 nm).

#### ●Radiant spectral distribution




Visible light and the infrared rays can be cut, and it combine with the filter etc. that suppress the heat influence on the irradiation part to the minimum.

### High output

#### UV intensity: 4500 mW/cm<sup>2</sup> (-01A type, at 365 nm)

The LC8 yields an extremely strong spectral distribution in the UV range most effective for UV curing. UV intensity distribution is dependent on the distance from the light guide output end to the target surface to be irradiated, as well as on the type of light guide used. The greater the distance from the light guide output end to the target surface, the more the maximum UV intensity drops and the more the light beam expands (see below).

#### ●UV intensity distribution



Wavelength: 365 nm  
Reference values for this data were taken using the LC8 Spot Light Source and the A10014-35-0110 quartz light guide (φ3.5 mm diameter, 1 m Length) with condenser lens E5147-04

TLSXB0145EB

## CONTROL

Control	Front panel control	Communication connector (RS-232C)	External control terminal (D-SUB connector) *1
Main Power ON/OFF	○	—	—
Lamp ON/OFF	○	○	○
Shutter Drive	Open/Close	○	○
	Auto Open/Close by Timer *2	○	○
	Auto Shutter Time Setting	○	—
Irradiation Program (Memory Step™) Setting	○	○	—
Optical Power Adjustment (UP/DOWN)	○	○	○
Lamp ON Indicator	○	○ (Signal Output)	○ (Signal Output)
Lamp Stability Indicator	○	○ (Signal Output)	○ (Signal Output)
Shutter Open Indicator	○	○ (Signal Output)	○ (Signal Output)
Lamp Operation Hour Meter	○	○	—
Overheat Alarm	○	○ (Signal Output)	○ (Signal Output)
Lamp Operation Time Alarm	○	○ (Signal Output)	○ (Signal Output)
Operating Switch for Power Saving Mode *3	—	—	—

\*1 10P terminal block is available as option E9795-01 (sold separately).

○ : available, — : not available

\*2 Corresponds to "start/stop" of Memory Step™.

\*3 The operating switch is inside

## SPECIFICATIONS

Parameter	L9566	L9588
Light Guide Port	Rear	Operation panel (front)
Lamp Replacement Position	Operation panel (front)	Rear
UV Intensity (Typ.) <sup>(A)</sup>	4500 mW/cm <sup>2</sup> Typ. (at 365 nm, -01A type)	
Radiant Wavelength Range <sup>(B)</sup>	-01A	[365 nm type] 300 nm to 450 nm
	-02A	[250 nm band enhanced type] 240 nm to 400 nm
	-03	[Visible light type] 400 nm to 700 nm
Lamp for Maintenance <sup>(C)</sup>	-01A, -02A	L10852
	-03	L8253 <sup>(D)</sup>
Lamp Service Life	-01A, -02A (L10852)	Guaranteed life 4000 h
	-03 (8253)	Guaranteed life 2000 h
Power Supply Input	100 V ac to 240 V ac (100 V / 200 V auto switching), single phase 47 Hz to 63 Hz	
Power Consumption	280 VA Typ.	
Weight	Approx. 6.4 kg	
Operating Ambient Temperature	+5 °C to +35 °C	
Storage Ambient Temperature	-10 °C to +70 °C	
Operating and Storage Humidity	Less than 80 % (no condensation)	

**NOTE:** <sup>(A)</sup> UV irradiance (at 365 nm) is measured in the center at a point 10 mm away from the output end of the A10014-35-0110 light guide (sold separately) with E5147-04, by using the Hamamatsu C6080-13 UV power meter.

<sup>(B)</sup> Major radiant wavelengths. Various optical filters (sold separately) can also be attached.

<sup>(C)</sup> L10852 is 200 W super-quiet mercury-xenon lamp. L8253 is 150 W super-quiet xenon lamp with ozone-free bulb.

<sup>(D)</sup> Standard quartz type is also provided.

## Optical Power Monitor with Optical Feedback E9793-02

Parameter	Description / Value
Monitoring Wavelength	365 nm <sup>(F)</sup>
Applicable Type	(L9566, L9588) -01A, -02A <sup>(G)</sup>

**NOTE:** <sup>(F)</sup> Monitoring at other wavelengths is not possible.


<sup>(G)</sup> When optical power monitor order with L9566 and L9588, please tell us the type No. whether (L9566, L9588)-01A-02 or (L9566, L9588)-02A-02.



## DIMENSIONAL OUTLINES

### L9566


(Unit: mm)



TL5XA0108ED

### L9588

(Unit: mm)



TL5XA0109ED

## ⚠ WARNING

### ● Light

This equipment emits very strong ultraviolet light which is harmful to eyes and the skin.

Also, as the light emanating from the light guide connection aperture contains infrared light in addition to ultraviolet light, its irradiation will cause heat generation. Be sure to observe following instructions for operation of the equipment.

- Never look directly into the light guide connection aperture or at the light emanating from the light guide. Strong ultraviolet light can cause visual disorder.
- Do not allow light to come into contact with skin. Contact with skin may cause sunburn-grade inflammation. Always wear safety glasses, gloves, and other appropriate protective gear when operating this equipment.
- Never allow light from the light guide to radiate onto flammable material.
- The unit includes an interlock that prevents the lamp from lighting while top cover is open. Never attempt to override the interlock function by manually depressing the switch, as this may result in uncontrolled release of dangerous ultraviolet light.

### ● High-Voltage trigger

- The mercury-xenon lamp employed started by a high-voltage (30 kV) pulse applied at the lamp electrodes.

As protection against accidental electrical shock hazard, the design includes an interlock switch that disables lamp operation while the top cover is open. Never attempt to turn on the lamp by blocking the sensor window of the interlock switch.

### ● Lamp Replacement

- The inside of the lamp housing becomes extremely hot during lamp operation. Before replacing the lamp, switch it off and run the cooling fan for at least 15 minutes.
- Always exercise due caution when handling or replacing a lamp.

A lamp contains high-pressure gas [approximately 1 MPa (10 atmospheres) at room temperature, approximately 4 MPa (40 atmospheres) during operation] and may burst if dropped or otherwise impacted.

### ● Inhibition of Removal and Modification

- Do not remove the cover unless absolutely necessary and never touch any of the screws inside the unit. As the internal components of this unit have been precisely adjusted, disassembling or modifying the equipment can cause problems with the unit, fire and electrical shock.

## DISPOSAL OF LAMPS

Lamps are filled with high pressure (approx. 1 MPa at room temperature) xenon gas (xenon gas and mercury in mercury-xenon lamps). When disposing of the used lamp, take appropriate measures in compliance with applicable regulations regarding waste disposal and correctly dispose of it yourself, or entrust disposal to a licensed industrial waste disposal company. In any case, be sure to comply with the regulations in your country, state, region or province to ensure the used lamp is disposed of legally and correctly.

## WARRANTY PERIOD

This device is guaranteed for one year after delivery date from us. The warranty extends only to replacement of the products. The warranty does not cover damage due to misuse or natural calamity.

# ACCESSORY


# LIGHTNINGCURE LC8

## LIGHT GUIDES


Various light guides using a core material with high UV transmittance are available ranging from the single type up to a 6-furcated type. Select the desired light guide that suits your application. We also welcome requests for custom light guides with different numbers of furcated ends, output end shapes and lengths.

\* The exclusive light guide adaptor is necessary for the one of LC5 / LC6.

### CUSTOM LIGHT GUIDE




### DIMENSIONAL OUTLINE OF OUTPUT END (UNIT: mm)



### TYPE NO. GUIDE

#### A10014-35-0110



A		C		D	
Type No.	Core Material	Suffix	Furcated	Suffix	Length
A10014	Synthetic silica	35	01	10	1 m
A10015	Glass	50	04	15	1.5 m
		70	06	30	3 m


### MAIN LIGHT GUIDE

Type No.				a	b	c	d	e
A	B	C	D					
A10014	35	01	10	45	φ8	φ5.8	φ6	φ3.5
A10014	35	02	10					
A10014	35	03	10					
A10014	35	04	10					
A10014	35	05	10					
A10014	35	06	10	60	φ11	φ6.5	φ7	φ5
A10014	50	01	10					
A10014	50	02	10					
A10014	50	03	10					
A10014	50	04	10					
A10014	70	01	10	60	φ14	φ8.5	φ9	φ7
A10015	50	01	10					


### LIGHT BEAM DISTRIBUTION

Relative light intensity: with 100% equal to the intensity at position 10 mm away from the output end without condensor lens when the LC8 L9566-01 is used with the A10014-50-0110.


#### A10014-35-0110 (at 365 nm)




#### A10014-50-0110 (at 365 nm)



#### A10014-70-0110 (at 365 nm)



#### A10015-50-0110 (at 436 nm) \*2



\*2 Relative light intensity: with 100% equal to the intensity at position 10 mm away from the output end when the LC8 L9566-01 is used with the A10014-50-0110. (436 nm)

### MAXIMUM INTENSITY FOR FURCATED FIBER

#### A10014-35 SERIES

Single (-0110)	2 furcated (-0210)	3 furcated (-0310)	4 furcated (-0410)	5 furcated (-0510)	6 furcated (-0610)
65 %	60 %	50 %	45 %	40 %	35 %

#### A10014-50 SERIES

Single (-0110)	2 furcated (-0210)	3 furcated (-0310)	4 furcated (-0410)
100 %	75 %	60 %	50 %


# ACCESSORY

## CONDENSER LENSES

Condenser lenses collect light emitted from a light guide and make it illuminate an object efficiently.


### DIMENSIONAL OUTLINE

**LONG FOCAL POINT CONDENSER LENS  
E5147,-02**




TLSXA0070EB

**LONG FOCAL POINT CONDENSER LENS  
E7658-01,-02**



TLSXA0087EB


**SHORT FOCAL POINT CONDENSER LENS  
E5147-03,-04**




TLSXA0071EB

### LIGHT BEAM DISTRIBUTION <Reference>


**LONG FOCAL POINT CONDENSER LENS  
E5147 (Output Diameter: φ5 mm)**




**LONG FOCAL POINT CONDENSER LENS  
E7658-01 (Output Diameter: φ5 mm)**




**SHORT FOCAL POINT CONDENSER LENS  
E5147-03 (Output Diameter: φ5 mm)**




**LONG FOCAL POINT CONDENSER LENS  
E5147-02 (Output Diameter: φ3.5 mm)**



**LONG FOCAL POINT CONDENSER LENS  
E7658-02 (Output Diameter: φ3.5 mm)**



**SHORT FOCAL POINT CONDENSER LENS  
E5147-04 (Output Diameter: φ3.5 mm)**



## CONDENSER LENSES (Uniform illumination)

Hamamatsu also provides a special lens that uniformly illuminates an entire surface.


We offer a choice of lenses for uniformly irradiating an entire target area. We provide a condenser lens type that attaches to the tip of the light guide, and a uniform direct irradiation unit that attaches directly to the body of the spot light source.

This uniform direct irradiation unit allows uniform irradiation onto the target surface area with light intensity variations within about ±5 %.

Three different lens types are available according to the size of the irradiation surface area.

Efficiently emits light at wavelengths longer than 300 nm.


### DIRECT BEAM UNIFORM ILLUMINATION UNIT UNIFORMITY



TLSXC0039EA


### DIMENSIONAL OUTLINE (UNIT: mm)

**DISTANCE FROM OUTPUT END E5147-06**



TLSXA0074EC

**DIRECT BEAM UNIFORM ILLUMINATION UNIT**






TLSXA0112ED

\* The holder of the main body needs to be changed.  
The exclusive light guide adaptor is necessary for the one of LC5 / LC6.




Condenser lenses are recommended when illuminating an object located away from the light guide end.

(UNIT: mm)




Relative light intensity: 100 % equal to the intensity at position 10 mm away from the output end without condenser lens \* Z: Distance from output end


**SHORT FOCAL POINT CONDENSER LENS E5147-11 (Output Diameter:  $\phi$ 5 mm)**




**RIGHT-ANGLE ILLUMINATIONS LENS E5147-07 (Output Diameter:  $\phi$ 5 mm)**



**SHORT FOCAL POINT CONDENSER LENS E5147-12 (Output Diameter:  $\phi$ 3.5 mm)**





**RIGHT-ANGLE ILLUMINATIONS LENS E5147-08 (Output Diameter:  $\phi$ 3.5 mm)**



**LIGHT BEAM DISTRIBUTION <Reference>**

Relative light intensity: with 100 % equal to the intensity at position 10 mm away from the output end without condenser lens when the LC8 L9566-01 is used with the A10014-50-01-10.



# ACCESSORY

## UV FILTERS

These filters transmit only the UV radiation needed for UV curing. Use of a UV filter minimizes heat generation on the illuminated surface making it ideal for use with parts and materials which are vulnerable to heat.

The following two filters are available according to the wavelength range to be blocked.


- -03 type: Transmits UV radiation very efficiently but blocks (absorbs) visible light.
- -05 type: Uses two filters to block visible to infrared light, achieving better absorption of heat rays than -03 type.

Both types have a long service life. Almost no drop in the transmittance even after 10 000 hours of operation.

## SPECIFICATIONS


Type No.	Number of Filter Used	Transmittance Wavelength (nm)	UV Transmittance (%)	NOTE
A9616-03	1	280 to 400	Approx. 85	High UV transmittance
A9616-05	2	300 to 400	Approx. 80	Cuts off heat over a wide spectral range more efficiently than -03 type.

## RADIANT SPECTRUM COMPARISON




## DIMENSIONAL OUTLINE


(UNIT: mm)



## LIFE CHARACTERISTICS



## TEMPERATURE COMPARISON ON THE ILLUMINATED SURFACE



**NOTE:** The data shown above is typical values measured by Hamamatsu, just for your reference. Actual performance may greatly depend on the object to be illuminated and distance to it, and may differ from the above data.

## UV POWER METER

### C6080

This optical power meter is specifically designed to measure the intensity of ultraviolet light emitted from the spot light source.

The C6080 is a high-precision power meter. Calibrating it once a year is recommended.

Type No.	Sensitive Area (mm)	Calibrated Wavelength (nm)	Optical Power Measurement Range (mW/cm <sup>2</sup> )
C6080-02	φ6	248	0 to 1999
C6080-03	φ1	365	
C6080-04	φ1	436	
C6080-13	φ1	365	0 to 19990

### C9386 [LIGHT CHECKER]

The C9386 is ideal for making daily checks of irradiation intensity and its pocket-size makes it great for field work. The small sensor head is convenient for measuring narrow and hard to access locations.

Type No.	Sensitive Area (mm)	Calibrated Wavelength (nm)	Optical Power Measurement Range (mW/cm <sup>2</sup> )
C9386	φ0.8	365	0 to 3999

\* The calibration for C9386 should be done by C6080-03 or C6080-13 at customer side.



▲C6080



▲C9386

## FOOT SWITCH

### E8263 SERIES

Pushing on the E8263 foot switch opens and closes the shutter. These are highly effective when a worker is using 1 or more spot light sources.

Different product series are available according to the cable length, connection method and operating method you need.

Type No.	Cable Length	Connection	Operation
E8263-12	2 m	Terminal block	Manual shutter or auto shutter selectable
E8263-15	5 m		
E8263-22	2 m	D-SUB connector	Manual shutter
E8263-25	5 m		Auto shutter
E8263-32	2 m		
E8263-35	5 m		



## LIGHT GUIDE CAP

### A9739 SERIES

The A9739 is a light guide cap for protecting the exit end of a light guide from gas evaporating from adhesive and from dust and scratches.

The light-transmitting window fitted to the cap is easily exchangeable with a spare window (supplied) so there is no maintenance or cleaning down-time. Protecting the light guide end with an A9739 light guide cap eliminates shipping and repair costs required for re-polishing. Two types of light guide caps and replaceable windows are available according to the light guide bundle diameter.

PROTECTIVE CAP (supplied with one replacement window)

A9739-06: Light guide bundle diameter 3.5 mm

A9739-07: Light guide bundle diameter 5 mm

REPLACEMENT WINDOW (material: quartz)

A9740: For light guide bundle diameters 3.5 mm and 5 mm



## PROTECTIVE GLASSES

### A6905

Spot light sources emit invisible intense UV radiation which is harmful to the human eyes. Protective glasses or goggles must be worn during work.





## RELATED PRODUCTS

### UV-LED MODULE LIGHTNINGCURE® LC-L2


This light source is a compact UV-LED module containing an ultraviolet LED element (365 nm or 385 nm). Designed for low power consumption, it is easy on the environment and allows UV irradiation with less thermal effect. Its fanless design ensures reliable use even in clean rooms. The same functions as those of the conventional UV irradiators are included, such as output intensity adjustment and irradiation time setting, etc. Various types of condenser lenses are available as options that allow to obtain irradiation patterns according to the application.



### UV-LED UNIT LIGHTNINGCURE® LC-L5


The LC-L5 is an innovative linear irradiation type UV-LED unit. It allows to set up new production processes that were impossible up to now with conventional LED light source. The LC-L5 can already be found in the recent UV printing equipment and other production facilities.

The product line-up includes a variety of types that allow to select an irradiation width and wavelength (365 nm or 385 nm) to match the workpiece.



### UV-LED UNIT LIGHTNINGCURE® LC-L3


The LC-L3 is a light source unit containing nine UV-LEDs arranged in a 3 × 3 matrix giving a whole new level in performance with LED characteristics maximized for both "long life" and "high output" which have been conflicting goals. The custom optical system ensures highly uniform irradiation coverage. Internal LED wavelength is selectable from 365 nm or 385 nm.



### UV BONDING EQUIPMENT

We design and configure simple UV curing or bonding equipment combined with dispensers and other devices.

We also welcome your queries regarding adhesive, bonding agents and syringes. Feel free to contact our sales office.



### [CONSULT US ABOUT UV CURING OR ANY RELATED ITEM]

We are available to help answer your various questions or concerns about UV curing or bonding. We can provide the ideal combination of UV adhesive to meet your particular needs for bonding strength or job speed, etc.

Subject to local technical requirements and regulations, availability of products included in this promotional material may vary. Please consult with our sales office. Information furnished by HAMAMATSU is believed to be reliable. However, no responsibility is assumed for possible inaccuracies or omissions. Specifications are subject to change without notice. No patent rights are granted to any of the circuits described herein. ©2011 Hamamatsu Photonics K.K.

## HAMAMATSU PHOTONICS K.K. [www.hamamatsu.com](http://www.hamamatsu.com)

### HAMAMATSU PHOTONICS K.K., Electron Tube Division

314-5, Shimokanzo, Iwata City, Shizuoka Pref., 438-0193, Japan, Telephone: (81)539/62-5248, Fax: (81)539/62-2205

U.S.A.: Hamamatsu Corporation: 360 Foothill Road, P. O. Box 6910, Bridgewater, N.J. 08807-0910, U.S.A., Telephone: (1)908-231-0960, Fax: (1)908-231-1218 E-mail: [usa@hamamatsu.com](mailto:usa@hamamatsu.com)

Germany: Hamamatsu Photonics Deutschland GmbH: Arzbergerstr. 10, D-82211 Herrsching am Ammersee, Germany, Telephone: (49)8152-375-0, Fax: (49)8152-2658 E-mail: [info@hamamatsu.de](mailto:info@hamamatsu.de)

France: Hamamatsu Photonics France S.A.R.L.: 19, Rue du Saule Trapu, Parc du Moulin de Massy, 91882 Massy Cedex, France, Telephone: (33)1 69 53 71 00, Fax: (33)1 69 53 71 10 E-mail: [infos@hamamatsu.fr](mailto:infos@hamamatsu.fr)

United Kingdom: Hamamatsu Photonics UK Limited: 2 Howard Court, 10 Tewin Road Welwyn Garden City Hertfordshire AL7 1BW, United Kingdom, Telephone: 44-(0)1707-294888, Fax: 44(0)1707-325777 E-mail: [info@hamamatsu.co.uk](mailto:info@hamamatsu.co.uk)

North Europe: Hamamatsu Photonics Norden AB: Smidesvägen 12, SE-171-41 SOLNA, Sweden, Telephone: (46)8-509-031-00, Fax: (46)8-509-031-01 E-mail: [info@hamamatsu.se](mailto:info@hamamatsu.se)

Italy: Hamamatsu Photonics Italia: S.R.L.: Strada della Moia, 1/E, 20020 Arese, (Milano), Italy, Telephone: (39)02-935 81 733, Fax: (39)02-935 81 741 E-mail: [info@hamamatsu.it](mailto:info@hamamatsu.it)

TLSZ1008E02  
JUN. 2011 IP  
(1000)