

pH/temperature measuring instrument

testo 230

- Measurement of pH and temperature in one instrument
- Display of calibration data and error reports
- Robust and splashproof according to protection class IP54
- Easily legible, 2-line display
- 1, 2, or 3-point calibration possible



The testo 230 combines a complete pH measuring instrument and a full-value temperature measuring instrument in one compact splashproof housing. It reliably records pH values, reduction voltages and temperature in watery solutions as well as in semi-solid to solid media.

The instrument has an automatic temperature compensation, and can be calibrated with standard as well as DIN buffers in the pH area. Thanks to the possibility of connecting different pH probes, the testo 230 is universally applicable, not only for applications in the pharmaceutical industry, but also in the food sector and the field of HVAC.

Technical data / Accessories

testo 230

testo 230, analysis instrument, protection class IP54, automatic temperature compensation, incl. 2 electrode clips and battery

Part no. 0560 2304

£ 364.00



Universal set testo 230

testo 230 set: analysis instrument with 2 electrode clips and battery, Testo buffer set pH 4 and 7, 50ml each, universal plastic electrode with temperature sensor plastic set case and batteries

Part no. 0563 2305

£ 500.00

Sensor type pH

| | |
|----------------------|------------------------|
| Meas. range | 0 to +14 pH |
| Accuracy ±1 digit | ±0.01 pH (0 to +14 pH) |
| Resolution | 0.01 pH |

Sensor type NTC

| | |
|----------------------|--|
| Meas. range | -50 to +150 °C |
| Accuracy ±1 digit | ±0.5% of mv (+100 to +150 °C) ±0.2 °C (-25 to +74.9 °C) ±0.4 °C (-50 to -25.1 °C) ±0.4 °C (+75 to +99.9 °C) |
| Resolution | 0.1 °C |

General technical data

| | |
|--|------------------|
| Operating temperature | 0 to +40 °C |
| Storage temperature | -20 to +70 °C |
| Display | LCD, 2 lines |
| Battery type | 9V block battery |
| Battery life | 100 h |
| Dimensions | 168 x 72 x 27 mm |
| Weight | 170 g |
| Housing material | ABS |
| Warranty | 2 years |
| Temperature compensation: man. -10 to +150°C; auto -50 to +150°C | |





Accessories for measuring instrument



Part no.

£

| | | |
|--|-----------|---------------|
| Set case (plastic) for measuring instrument, probes and accessories user-friendly arrangement of measuring instrument and accessories | 0516 0230 | POA |
| Storage solution for pH-electrode, 50 ml | 0554 2318 | 26.67 |
| ISO calibration certificate/water analysis for pH buffer solutions; calibration points 4 pH; 7 pH; 10 pH | 0520 0007 | 43.19 |
| ISO calibration certificate/water analysis at 3 pH values over the measuring range | 0520 0037 | 230.34 |
| pH buffer solution 4.01 in dosing bottle (250 ml), with DAkkS calibration certificate | 0554 2061 | 11.87 |
| pH buffer solution 7.00 in dosing bottle (250 ml), with DAkkS calibration certificate | 0554 2063 | 11.87 |

Probes

| Probe type | Dimensions Probe shaft/probe shaft tip | Measuring range | Operating temperature | Part no. £ |
|---|---|--------------------|-------------------------------------|--------------------------------|
| pH / °C/ redox electrodes | | | | |
| pH universal plastic electrode without temperature sensor Robust and dirt-insensitive pH electrode with single-pore diaphragm; unbreakable plastic, maintenance-free gel-electrolyte, incl. storage cap |  | 0 to +14 pH | 0 to +60 °C Short-term to +80 °C | 0650 2063 80.33 |
| pH universal plastic electrode with temperature sensor Robust and dirt-insensitive pH electrode with single-pore diaphragm, unbreakable plastic, maintenance-free gel-electrolyte, incl. storage cap |  | 0 to +14 pH | 0 to +60 °C Short-term to +60 °C | 0650 2064 136.00 |
| Glass pH electrode with temperature sensor Robust and dirt-insensitive pH electrode with single-pore diaphragm, Glass electrode with excellent chemical resistance, maintenance-free gel-electrolyte, incl. storage cap |  | 0 to +14 pH | -10 to +80 °C | 0650 1623 188.00 |
| pH food electrode without temperature sensor Robust and dirt-insensitive pH penetration electrode with hole diaphragm, unbreakable plastic coating around glass electrode, maintenance-free food-safe gel-electrolyte, incl. watering cap |  95 mm Ø 6.5 mm | +2 to +14 pH | 0 to +40 °C | 0650 0245 177.00 |

| Probe type | Dimensions Probe shaft/probe shaft tip | Measuring range | Accuracy | t ₉₉ | Part no. £ |
|--|---|------------------------------|---|-----------------|-------------------------------|
| Temperature probes | | | | | |
| Stainless steel NTC food probe (IP65) with PUR cable, Fixed cable |  125 mm 15 mm Ø 4 mm Ø 3 mm | -50 to +150 °C | ±0.5% of mv (+100 to +150 °C) ±0.2 °C (-25 to +74.9 °C) ±0.4 °C (remaining range) | 8 s | 0613 2211 93.98 |
| Robust NTC food penetration probe with special handle, reinforced PUR cable, Fixed cable |  115 mm Ø 5 mm 30 mm Ø 3.5 mm | -25 to +150 °C ¹⁾ | ±0.5% of mv (+100 to +150 °C) ±0.2 °C (-25 to +74.9 °C) ±0.4 °C (remaining range) | 7 s | 0613 2411 86.63 |

1) Long-term measurement range +125 °C, short-term +150 °C (2 minutes)

0981 9251 20/cw/A/01.2014

Subject to change without notice.
All prices are net and valid until 31.12.2014.
Shipping costs & VAT not included.



Testo Limited
Newman Lane
ALTON, HAMPSHIRE
GU34 2UR
Phone: 01420 544 433
Fax: 01420 544 434
Email: info@testo.co.uk