

Flue gas analyzer

testo 310 – Flue gas analysis the easy way

Robust design for daily use

Battery lifetime up to 10 hours

Integrated measurement menus: Flue gas, draught, ambient CO and pressure

Fast sensor zeroing in only 30 seconds

Illuminated display

Documentation of measurement results via printer with infrared interface



The new flue gas analyzer testo 310 combines simple functions with a high level of measurement accuracy, and is therefore perfectly suited to all basic measurements on a heating system. Long battery lifetimes of up to ten hours guarantee high availability. Its easy handling and compact design make the testo 310 a robust tool for day-to-day work – even when things get rough. Clear reports can be created

as required on site thanks to the infrared interface printer specially developed for the testo 310. The current measurement value can be printed out from all measurement menus, either during or after the measurement. The testo 310 offers all advantages of electronic flue gas measurement in high quality at a perfect cost/benefit ratio.

Product properties



Robust
Robust and light instrument for daily use – ideal even for tough and dirty surroundings



Backlit display
Two-line display and clear menu structure. Simple to operate and easy to read.



Fast sensor zeroing
Automatic zeroing of gas sensor in only 30 seconds after starting up, which can be cancelled if not required.



Lithium rechargeable battery
Operation with a Lithium rechargeable battery (1500 mAh) – no change of battery necessary, up to ten hours running time, charging via USB connection possible.



Probe filter
Can be changed quickly and easily.



Attachment
Integrated magnets for easy attachment to the burner.



Condensate trap
Integrated condensate trap – can be emptied very quickly and easily.



Printer
Documentation via infrared printer.

Ordering data

testo 310 flue gas set

testo 310 incl. battery and calibration protocol for the measurement of O₂, CO, hPa and °C; probe 180 mm with cone; case; mains unit incl. cable; silicon hose for pressure measurement; particle filter 5 off.



Part no. 0563 3100

£ 339.00

testo 310 flue gas set with printer

testo 310 incl. battery and calibration protocol for the measurement of O₂, CO, hPa and °C; IR printer (0554 3100); probe 180 mm with cone; case; mains unit incl. cable; silicon hose for pressure measurement; particle filter 5 off; 2 rolls spare thermal paper for printer.



Part no. 0563 3110

£ 439.00

Testo IR printer

Testo IR printer with wireless infrared interface, 1 roll thermal paper and 4 AA batteries.



Part no. 0554 3100

£ 114.00

Accessories

Product sets	Part no.	£
testo 310 flue gas set	0563 3100	339.00
testo 310 flue gas set with printer	0563 3110	439.00
Accessories for measuring instrument		
USB mains unit incl. cable	0554 1105	27.83
Testo IR printer	0554 3100	114.00
Testo fast printer IRDA	0554 0549	171.00
Spare thermal paper for printer, permanent ink	0554 0568	19.49
Spare particle filter	0554 0040	19.11
Spare gas sensors		
Replacement O ₂ sensor	0390 0085	62.15
Spare CO sensor	0390 0119	125.62

Technical data

	Measuring range	Accuracy ± 1 digit	Resolution	Adjustment time t_{90}
Temperature (flue gas)	0 to +400 °C	± 1 °C (0 to +100 °C) $\pm 1.5\%$ of m.v. (>100 °C)	0.1 °C	< 50 s
Temperature (ambient temperature)	-20 to +100.0 °C	± 1 °C	0.1 °C	< 50 s
Draught measurement	-20 to +20 hPa	± 0.03 hPa (-3.00 to +3.00 hPa) $\pm 1.5\%$ of m.v. (remaining range)	0.01 hPa	
Pressure measurement	-40 to 40 hPa	± 0.5 hPa	0.1 hPa	
O₂ measurement	0 to 21 Vol. %	± 0.2 Vol. %	0.1 Vol. %	30 s
CO measurement (without H₂ compensation)	0 to 4000 ppm	± 20 ppm (0 to 400 ppm) $\pm 5\%$ of m.v. (401 to 2000 ppm) $\pm 10\%$ of m.v. (2001 to 4000 ppm)	1 ppm	60 s
Ambient CO measurement	0 to 4000 ppm	± 20 ppm (0 to 400 ppm) $\pm 5\%$ of m.v. (401 to 2000 ppm) $\pm 10\%$ of m.v. (2001 to 4000 ppm)	1 ppm	60 s
Efficiency (ETA)	0 to 120 %	-	0.1 %	-
Flue gas loss	0 to 99.9 %	-	0.1 %	-

General technical data

Storage temperature	-20 to +50 °C
Operating temperature	-5 to +45 °C
Power supply	Battery: 1500 mAh, mains unit 5V/1A
Memory	No memory

Display	Backlit 2-line display
Weight with probe	Approx. 700 g
Dimensions	201 x 83 x 44 mm
Warranty	Measuring instrument, flue gas probe, gas sensors: 24 months Thermocouple: 12 months Battery: 12 months

0981 2671 20/cw/AV/01.2014

Subject to change without notice.
All prices are net and valid until 31.12.2014.
Shipping costs & VAT not included.



Testo Limited
Newman Lane
ALTON, HAMPSHIRE
GU34 2UR
Phone: 01420 544 433
Fax: 01420 544 434
Email: info@testo.co.uk