

# Thermal anemometer

testo 405



---

Flow velocity measuring instrument with temperature measurement

---

Volume flow measurement up to 99990 m<sup>3</sup>/h

---

Extendable telescope up to 300 mm

---

Display illumination

---

m/s

°C

testo 405 is a thermal anemometer. It allows the precise measurement of air flow velocity, volume flow and temperature. With the extendable telescope (up to 300 mm), testo 405 is particularly suited for measuring the flow velocity in ducts. Thanks to the attachment included in delivery, the telescope can be optimally positioned in a duct.

The testo 405 measures especially accurately in the range from 0 and 2 m/s. Low air flow velocities such as at draughty windows, for example, can thus be localized exactly and measured extremely accurately. The display can be rotated into different positions. This enables optimum readout of the measurement values.

## Technical data / Accessories

### testo 405

testo 405 thermal anemometer with duct holder,  
incl. attachment clip and batteries

Part no. 0560 4053

£ 116.00



### General technical data

Storage temperature	-20 to +70 °C
Operating temperature	0 to +50 °C
Battery type	3 AAA micro batteries
Battery life	Approx. 20 h
Dimensions	490 x 37 x 36 mm
Length Probe shaft	300 mm
Diameter Probe shaft / Probe shaft tip	Ø 16 mm / Ø 12 mm
Weight	115 g (with batteries, without packaging)
Warranty	2 years

### Sensor types

	Thermal	NTC
Measuring range	0 to 5 m/s (-20 to 0 °C) 0 to 10 m/s (0 to +50 °C) 0 to +99990 m <sup>3</sup> /h	-20 to +50 °C
Accuracy ±1 digit	±(0.1 m/s + 5% of mv) (0 to +2 m/s) ±(0.3 m/s + 5% of mv) (remaining range)	±0.5 °C
Resolution	0.01 m/s	0.1 °C

### Accessories

Part no.

£

#### Accessories for measuring instrument

	Part no.	£
testovent 410, volume flow funnel, Ø 340 mm/330x330 mm, incl. case	0554 0410	<b>201.00</b>
testovent 415, volume flow funnel, Ø 210 mm/210x210 mm, incl. case	0554 0415	<b>191.00</b>
ISO calibration certificate velocity, two point calibration; calibration points 5m/s and 10m/s	0520 0094	<b>112.35</b>
ISO calibration certificate velocity, hot wire, vane anemometer, Pitot tube; calibration points 1; 2; 5; 10 m/s	0520 0004	<b>179.96</b>

0981 9751 20/cw/AV/01.2014

Subject to change without notice.  
All prices are net and valid until 31.12.2014.  
Shipping costs & VAT not included.



**Testo Limited**  
Newman Lane  
ALTON, HAMPSHIRE  
GU34 2UR  
Phone: 01420 544 433  
Fax: 01420 544 434  
Email: info@testo.co.uk