



## rpm measuring instrument

**testo 470** - For non-contact and mechanical measurement



---

Easy one-hand operation

---

Measurement of rpm, speeds and lengths

---

Storage of mean, max. and min. values as well as the last measurement value

---

Measurement distance up to 600 mm (optical measurement)

---

Battery check "Low Batt"

---

Robust design thanks to SoftCase (protective case)

---

The rpm measuring instrument testo 470, which can be operated with one hand, offers an optimum combination of optical and mechanical rpm measurement. By simply attaching an adapter for a probe tip or a speed disc, the optical measurement becomes a mechanical one. This allows speeds and lengths to be measured additionally. For optical measurements, simply attach a reflective marker

(optional) to the measurement object, point the visible measurement spot at the reflective marker, and measure. The distance to the measurement object is up to 600 mm. The testo 470 stores mean, min. and max. values as well as the last measurement value. The SoftCase included in delivery protects the instrument from impact, ensuring an especially long working life.

## Technical data / Accessories

### testo 470

testo 470 rpm measuring instrument with SoftCase in transport case incl. probe tip, 0.1 m and 6" wheel, reflectors and batteries

Part no. 0563 0470

£ 251.00



### Sensor types

	Optically with mod. light beam
Meas. range	+1 to +99999 rpm
Accuracy ±1 digit	±0.02% of mv
Resolution	0.01 rpm (+1 to +99.99 rpm) 0.1 rpm (+100 to +999.9 rpm) 1 rpm (+1000 to +99999 rpm)
	Mechanical
Meas. range	+0.1 to +19999 rpm
Accuracy ±1 digit	±0.02% of mv

### Accessories

Part no.

£

Accessories for measuring instrument	Part no.	£
Reflectors, self-adhesive (1 pack = 5 off, each 150 mm long)	0554 0493	15.23
Measuring wheel 12"	0554 4755	119.74
Measuring wheel 6"	0554 4754	47.25
ISO calibration certificate/rpm optical and mechanical rpm measuring instruments; cal. points 500; 1000; 3000 rpm	0520 0012	132.53
ISO calibration certificate/rpm optical rpm measuring instruments; calibration points 10; 100; 1000; 10000; 99500 rpm	0520 0022	146.93
ISO calibration certificate/rpm Calibration points freely selectable from 10 to 99500 rpm	0520 0114	POA
DAkkS calibration certificate/rpm Optical rpm probes, 3 points in instrument measurement range (1 to 99999 rpm)	0520 0422	301.10

### General technical data

Operating temperature	0 to +50 °C
Storage temperature	-20 to +70 °C
Battery type	2 AA batteries
Battery life	40 h
Display	5-figure LCD display, 1-line
Dimensions	175 x 60 x 28 mm
Weight	190 g
Warranty	2 years

	0.1 m	6"	12"
<b>m/min</b>	0.10-1999	0.10-1524	0.40-609.6
<b>ft/min</b>	0.40-6550	0.40-5000	0.40-2000
<b>in/min</b>	4.00-78700	4.00-60000	4.00-24000
<b>m/sec</b>	0.10-33.30	0.10-25.40	0.10-10.16
<b>ft/sec</b>	0.10-109	0.10-83.33	0.10-33.33
<b>m</b>	0.00-99999	0.00-99999	0.00-99999
<b>ft</b>	0.00-99999	0.00-99999	0.00-99999
<b>in</b>	0.00-99999	0.00-99999	0.00-99999

Units rpm, m/min, ft/min, in/min, m, ft, in

The mechanical tolerance for measurements with a wheel is 0.2 %, the measurement accuracy is dependent on handling, e.g application pressure, angle etc.



**Testo Limited**  
Newman Lane  
ALTON, HAMPSHIRE  
GU34 2UR  
Phone: 01420 544 433  
Fax: 01420 544 434  
Email: info@testo.co.uk