



Differential pressure measuring instrument

testo 510 – Pocket-sized differential pressure measurement

Differential pressure measurement 0 to 100 hPa

Flow velocity measurement possible with Pitot tube

Temperature and air density compensation

Display illumination

10 selectable units



Illustration 1.1

testo 510 measures differential pressure in the range from 0 to 100 hPa. The differential pressure measurement is temperature-compensated for accurate measurement values. The measurement values can be displayed in Pascal over the entire measurement range. Magnets at the rear permit free-hand work. The backlit display allows the

measurement values to be easily read out, even in unfavourable light conditions. The testo 510, in combination with a Pitot tube, measures air flow velocity. For accurate measurement values, the air density can be compensated. testo 510 is very handy, small and easy to operate.

Technical data / Accessories

testo 510

testo 510 handy measuring instrument for differential pressure incl. protection cap, batteries, belt holder and calibration protocol

Part no. 0560 0510

£ 133.00



Sensor type Differential pressure sensor

Measuring range	0 to 100 hPa
Accuracy ±1 digit	±0.03 hPa (0 to 0.30 hPa) ±0.05 hPa (0.31 to 1.00 hPa) ±(0.1 hPa + 1.5 % of mv) (1.01 to 100 hPa)
Resolution	0.01 hPa

General technical data

Positive pressure	500 mbar
max. static pressure	1.5 bar
Operating temperature	0 to +50 °C
Storage temperature	-40 to +70 °C
Selectable units	hPa, mbar, Pa, mmH ₂ O, inH ₂ O, inHg, mmHg, psi, m/s, fpm
Protection class	IP40
Battery type	2 AAA micro batteries
Battery life	50 h (average, without display illumination)
Measurement rate	0.5 s
Dimensions	119 x 46 x 25 mm
Weight	90 g (with batteries and protective cap)
Warranty	2 years

Accessories

Part no.

£

Accessories for measuring instrument

Connection hose, silicone, 2 m long, max. load 700 hPa (mbar)	0554 0448	16.70
Belt holder	0516 4007	4.66
ISO calibration certificate pressure; differential pressure; 3 points distributed over meas. range	0520 0095	80.73
ISO calibration certificate pressure; differential pressure; 5 points distributed over meas. range	0520 0005	117.43

0981 9761 20/cw/AV/01.2014

Subject to change without notice.
All prices are net and valid until 31.12.2014.
Shipping costs & VAT not included.



Testo Limited
Newman Lane
ALTON, HAMPSHIRE
GU34 2UR
Phone: 01420 544 433
Fax: 01420 544 434
Email: info@testo.co.uk