

# Humidity/temperature measuring instrument

testo 625 - Long-term stable and compact

---

Display of temperature and relative humidity / Wet Bulb temperature / dewpoint

---

Min./max. values

---

Hold-button for fixing measurement value

---

Display illumination

---

Auto-off function

---

TopSafe, protection of instrument against dirt and impact

---



The testo 625 is a compact instrument with an integrated humidity probe head for the measurement of air humidity and temperature. The large two-line display quickly and reliably shows humidity, Wet Bulb temperature or dewpoint, as well as temperature.

For measurements in difficult-to-access places, the humidity probe head can simply be removed and plugged onto the handle with a probe cable (accessory); alternatively, the measurement values can be transferred wirelessly from the probe to the measuring instrument over large distances. For this purpose, the humidity probe head is plugged onto the wireless handle (accessory), and the testo 625 is equipped with the radio module (accessory).

# Humidity/temperature measuring instrument

## testo 625

testo 625 humidity/temperature measuring instrument incl. plug-in humidity probe head, battery and calibration protocol

Part no. 0563 6251

£ 226.00



### General technical data

Storage temperature	-40 to +85 °C
Operating temperature	-20 to +50 °C
Battery type	9V block battery, 6F22
Battery life	70 h (without radio operation)
Weight	195 g
Dimensions	182 x 64 x 40 mm
Housing material	ABS
Warranty	2 years

### Sensor types

	Testo humid. sensor, cap.	NTC	Type K (NiCr-Ni) (Radio probes)
Meas. range	0 to +100 %RH	-10 to +60 °C	-200 to +1370 °C
Accuracy ±1 digit	±2.5 %RH (+5 to +95 %RH)	±0.5 °C	See probe data
Resolution	0.1 %RH	0.1 °C	0.1 °C



Moisture probe head via handle with probe wire



testo 625 with radio handle and radio module



testo 625 with attached probe head

# Accessories

Accessories for measuring instrument	Part no.	£
Handle for plug-in humidity probe head for connection to testo 625, probe cable included (length 120 cm)	0430 9725	<b>39.27</b>
Case for measuring instrument and probes	0516 0210	<b>23.98</b>
TopSafe, protects from impact and dirt	0516 0221	<b>21.84</b>
Control and adjustment set for Testo humidity probes, salt solution with 11.3% RH and 75.3% RH, incl. adapter for Testo humidity probes	0554 0660	<b>213.00</b>
Lithium battery button cell	0515 0028	<b>3.92</b>
9V rech. battery for instrument, instead of battery	0515 0025	<b>27.72</b>
Recharger for 9V rechargeable battery, for external recharging of 0515 0025 battery	0554 0025	<b>28.04</b>

## Calibration Certificates

ISO calibration certificate humidity, Calibration points 11.3 %RH and 75.3 %RH at +25 °C	0520 0006	<b>151.16</b>
ISO calibration certificate/humidity, saturated saline solutions: calibration point 11.3%RH	0520 0013	<b>125.33</b>
ISO calibration certificate/humidity, saturated saline solutions, calibration point 75.3%RH	0520 0083	<b>125.33</b>
DAkkS calibration certificate/humidity, electronic hygrometers; calibration points 11.3%RH and 75.3%RH at +25°C	0520 0206	<b>526.93</b>
DAkkS calibration certificate/humidity, saturated saline solutions; calibration point 11.3%RH	0520 0213	<b>301.10</b>
DAkkS calibration certificate/humidity, saturated saline solutions; calibration point 75.3%RH	0520 0283	<b>301.10</b>

## Radio module for upgrading measuring instrument with radio option

Radio module for measuring instrument, 869.85 MHz, approval for the countries: DE, FR, UK, BE, NL, ES, IT, SE, AT, DK, FI, HU, CZ, PL, GR, CH, PT, SI, MT, CY, SK, LU, EE, LT, IE, LV, NO	0554 0188	<b>32.45</b>
Radio module for measuring instrument, 915.00 MHz FSK, approval for USA, CA, CL	0554 0190	<b>34.22</b>

## Radio handle for attachable humidity probe head (humidity probe head included in delivery of testo 625)



Radio handle for plug-in probe heads, incl. T/C adapter, approval for the countries: DE, FR, UK, BE, NL, ES, IT, SE, AT, DK, FI, HU, CZ, PL, GR, CH, PT, SI, MT, CY, SK, LU, EE, LT, IE, LV, NO; Radio freq. 869.85 MHz FSK	0554 0189	<b>83.27</b>
Radio handle for plug-in probe heads, incl. T/C adapter, approval for USA, CA, CL; Radio freq. 915.00 MHz FSK	0554 0191	<b>83.63</b>

## Technical data Radio handle

Battery type	2 AAA micro batteries
Battery life	215 h (meas. rate 0.5 s) 6 months (meas. rate 10 s)
Measuring rate	0.5 s or 10 s, adjustable on handle
Radio coverage	Up to 20 m (without obstructions)
Radio transmission	Unidirectional
Operating temperature	-20 to +50 °C
Storage temperature	-40 to +70 °C

0981 9671 20/cw/A/01.2014

Subject to change without notice.  
All prices are net and valid until 31.12.2014.  
Shipping costs & VAT not included.



**Testo Limited**  
Newman Lane  
ALTON, HAMPSHIRE  
GU34 2UR  
Phone: 01420 544 433  
Fax: 01420 544 434  
Email: [info@testo.co.uk](mailto:info@testo.co.uk)