

Compressed air counter shaft probe DN40 - DN300

testo 6448



m/s

m³/h;
l/min;
m³

°C

Possibility of installation under pressure

Measurement of flow velocity (m/s) in the measuring range 0 to 80 m/s or 160 m/s; consumption measurement in m³ and media temperature in °C

Recoil protection and ball valve ensure fast and safe installation and deinstallation of the compressed air probe on site.

Highest flexibility thanks to different signal outputs:

- Analog output 4 to 20 mA (4-wire)
 - Pulse output
 - 2 switching outputs (parameterisable: consumption or volume flow-dependent, NO, NC, hysteresis, window)
-

Integrated totaliser, also without additional evaluation unit

Operating menu with LED display

Shaft probe

The mobile compressed air counter testo 6448 is designed for the recording and monitoring of compressed air consumption, and thus not only for the identification of leakages in compressed air systems and the allocation of costs by consumption, but also for the implementation of peak load management. The shaft probe can be used for measurements on different pipe diameters.

An optional drilling clamp allows the exact positional installation of the sensor, without the need for welding work. The affected supply line can remain pressurised when installing the drilling clamp or for sensor maintenance/exchange.

Patented recoil protection

The recoil protection guarantees highest security for the commissioner, and combines three functions in one instrument:

1. the recoil protection, i.e. the sensor can only be inserted in one direction during installation
2. the seal to the process, i.e. thanks to the O-ring, compressed air cannot escape during installation.
3. the positionable fixing, since a penetration depth and positioning which is exact to the millimeter, similar to a car's clutch, is possible.



Technical data

Parameters

Flow velocity

Selectable units	m/s
Measuring range ¹	0 to 80 or 160 m/s
Measurement dynamics	1:150 or 1:300
Accuracy	±3 % of meas. value ±3 % of fsv (at room temperature)
Sensor	Thermal, glass-coated ceramic sensor (calorimetric measurement procedure)
Response time	<0.1 sec (for damping parameter = 0), delayable via operating menu (0 to 1 sec)

(Norm) volume flow

Selectable units	m ³ /h, m ³ /min, m ³
------------------	--

Temperature

Unit	°C
Measuring range	0 to +60 °C / 32 °F to +140 °F

Inputs and outputs

Analog outputs

Output type	4 to 20 mA (4-wire) freely scalable between zero and measuring range end
Load	max. 500 Ω

Further outputs

Pulse output	Pulse speed freely settable in 1 m ³ steps
Switch output	2 switch outputs, parameterisable (consumption or volume flow-dependent, NC, NO, hysteresis, window), loadable with max. 20 to 30 VDC or 250 mA each, switch status is displayed via 2 LEDs.

Supply

Voltage supply	19 to 30 V DC
Current consumption	<100 mA
Connection	M12 x 1 plug, loadable up to 250 mA, short-circuit-proof (synchronised), reverse-polarity-proof, overload-proof

General technical data

Design

Material housing	PBT-GF 20, PC (APEC), Makrolon, V2A (1.4301), Viton
Weight	850 g

Display

Display	4-figure alphanumerical display, two operating buttons, operating menu, LED (4 x green for phys. units, 3 x yellow for display x 1,000 or switch status)
Max. display value norm volume flow	90 m ³ /h

Operation

Parameterization	2 operating buttons
------------------	---------------------

Miscellaneous

Protection class	IP 65/III
EMC	according to guideline 89/336 EEC
Media contact	V2A (1.4301), PEEK, polyester, Viton, anodized aluminium; glass-coated ceramics
Norm reference	Calculation of volume flow due to manual input possibility of temperature, humidity and pressure. Works settings: 15 °C, 1013.25 hPa, 0 %RH.

Operating conditions

Humidity (sensor)	rel. humidity <90 %RH
Operating temperature (housing)	0 to +60 °C (+32 to +140 °F)
Storage temperature	-25 to +85 °C (-13 to +185 °F)
Measurement medium	Compressed air, with special calibration also CO ₂ or N ₂
Process pressure	PN 16 (max 16bar/232psi)
Pressure tightness/ pipe clamp	16 bar (max.) for DN40-DN200; 10 bar (max.) for DN250-DN300
Air quality	ISO 8573: recommended classes 1-4-1

¹ Specifications according to DIN 2533 (+15 °C, 1013.25 hPa, 0 %rF)

Options / Ordering example

Order data testo 6448

AXXX configuration
 BXX Drilling clamp selection
 CXX Measurement fitting selection

AXXX configuration

- A0 accessories only *
- A1 with transmitter incl. recoil protection **
- AA0 80 m/s
- AA1 160 m/s
- AC0 Air (compressed air)
- AC1 Alternative gas: nitrogen
- AC2 Alternative gas: CO₂
- AD0 factory protocol only
- AD1 ISO calibration protocol m/s at 6 points
- AD2 ISO calibration protocol m³/s at 6 points for specific nominal diameter (pls. indicate diameter)
- AE0 Standard length 285 mm (for DN40 to DN100)
- AE1 Length variant 435 mm (for DN125 to DN300)

* If this selection is made, further configuration AXX is not necessary. Continue with BX.
 **Further Configuration necessary! Continue with AXX.
 ***A connection cable, e.g. order no. 0699 3393 is required for operation.

BXX Drilling clamp selection

- B00 Without drilling clamp
- B01 With drilling clamp DN40
- B02 With drilling clamp DN50
- B03 With drilling clamp DN65
- B04 With drilling clamp DN80
- B05 With drilling clamp DN100
- B06 With drilling clamp DN125
- B07 With drilling clamp DN150
- B08 With drilling clamp DN200
- B09 With drilling clamp DN250
- B10 With drilling clamp DN300

CXX Measurement fitting selection

- C00 Without measurement fitting / without ball valve
- C01 With measurement fitting (incl. ball valve for e.g. other meas. parameter)
- C02 With ball valve (DN15)

Ordering example

Order code for transmitter testo 6448 – Compressed air counter shaft probe

- With transmitter incl. recoil protection
- 80 m/s
- Air (compressed air)
- Without calibration
- Length variant 435 mm (for DN125 to DN300)
- Without drilling clamp
- Without measurement fitting / without ball valve

-> 0555 6448 A1 AA0 AC0 AD0 AE1 B0 C0

Order code for transmitter testo 6448 – drilling clamp DN40:

- Accessories
- With drilling clamp DN40
- Without measurement fitting / without ball valve

-> 0555 6448 A0 B01 C0

0981 8374/msp/A/10.2012

Subject to change without notice.

