

Shadow Lifter (Graffiti Cleaner) - Application Guide



Introduction

The purpose of this document is to give guidance to approved contractors and suppliers who are engaged in cleaning graffiti or masonry using Astro Shadow Lifter

Shadow Lifter

Pressure wash the area to be treated to prevent any unnecessary absorption and streaking.

Apply undiluted Shadow Lifter with a bristle brush to the affected area: start at the bottom edge and work upwards.

Areas to be cleaned should be wetted prior to application to prevent streaking.

Allow to dwell for 1-2 minutes before rinsing.

Pressure wash with a pump capable of 1500 psi @ 14 lpm, with a slow even movement keeping the lance 15-20 cm away from the surface until complete rinsing has been achieved.

Coverage Rate:
Should be applied at 5 m² per Litre.

Storage:
Store away from direct sunlight and sources of heat.
Shelf life approximately 12 months (in original sealed container)
Protect from frost.

actual performance of the products mentioned or referred to, and no liability whatsoever will be accepted for any loss, damage or injury arising from the use of the information given of products mentioned or referred to herein.

The above information to the best of our knowledge is true and accurate and based upon current test data and is supplied for your guidance only. Customers should satisfy themselves to the suitability of the product in its intended use and no guarantee is given or implied since the conditions of actual use are beyond our control. ASTROflame (Fireseals) Ltd, disclaim any liability for loss, damage or other expense arising from the use of information, data or products mentioned or referred to and reserve the right to change any details or specifications without notice.

Astroflame (Fire Seals) Ltd. Intumescent House
Unit 8, The IO Centre, Stephenson Road, Segensworth
FAREHAM, ENGLAND PO15 5RU

tel 0800 023 2482
(01329 844500)

fax 0800 023 2483
(01329 844600)

intl
tel +44 1329 844500

fax +44 1329 844600

email sales@astroflame.com