

KITO HOISTS
Always on the safe side

Hook latch with safety tip

KITO Original freewheel chain adjusting mechanism protects from accidental freewheeling

Nickel plated load chain grade 100 (V) (1000 N/mm²), in accordance with standard EN 818-7

Fourfold riveted increased safety



Options:

Kito-Clip*



Point load hook for special applications / e.g. in shipbuilding and in sheet metal forming



- LB-OF without freewheel chain adjusting mechanism
- LB-OLL with optional slip clutch



Technical data valid for all LB models

*to be used for pulling horizontal loads only

Type	LB008	LB010	LB016	LB025	LB032	LB063	LB090
Capacity, kg	800	1000	1600	2500	3200	6300	9000
Standard lift, m	1,5	1,5	1,5	1,5	1,5	1,5	1,5
Hand pull to lift full load, daN	28,4	35,3	33,3	36,3	36,3	37,2	38,2
Load chain diameter, mm	5,6 x 15,7	5,6 x 15,7	7,1 x 19,9	8,8 x 24,6	10 x 28,0	10 x 28,0	10 x 28,0
Chain fall	1	1	1	1	1	2	3
Net weight, kg	5,7	5,9	8,0	11,2	15,0	26,0	40,0
Headroom C, mm	280	300	335	375	395	540	680
Weight for additional 1 m lift, kg	0,7	0,7	1,1	1,7	2,3	4,7	7,0

Disclaimer:
KITO does not assume liability for inappropriate usage of products.
Operating instructions must be followed at all times.
Subject to technical change, misprint and errors.

Contact
sales@rriuk.com