



**Technical Data**

Type	SHB010	SHB020	SHB030	SHB050	SHB075	SHB100	
Maximum capacity (kg)	1000	2000	3000	5000	7500	10000	
Standard lift (m)	3,0	3,0	3,0	3,0	3,5	3,5	
Length of folded handchain (m)	3,0	3,0	3,0	3,5	4,0	4,0	
Pull to lift load (daN) – Chain Hoist	31,4	28,4	36,3	44,1	45,0	47,0	
Pull at full load (daN) – Trolley	3,2	2,9	3,7	4,5	3,6	4,8	
Flange width (mm)	Standard	58-163	82-204	82-204	125-204	150-220	150-220
	W 30	164-305	205-305	205-305	205-305	221-305	221-305
Load chain diameter (mm)	5,0 x 15,1	7,1 x 21,2	8,0 x 24,2	9,0 x 27,2	9,0 x 27,2	9,0 x 27,2	
Chain falls	2	2	2	2	4	4	
Net weight (kg)	67,0	110,0	160,0	280,0	366,0	366,0	
Weight for additional 1m lift (kg)	3,0	4,2	4,6	5,4	10,8	10,8	
Headroom C (mm)	115	145	165	195	255	255	

Exclusion of liability  
KITO will not be held liable for any malfunction, lack of performance or accident if the product is being used in conjunction with any unauthorized part, or not in accordance with the operating instructions. Please take note of our owners manual. All specifications herein are subject to change without notice.

Contact  
[sales@rriuk.com](mailto:sales@rriuk.com)