

CMT150

Rack Conveyor Dishwasher Up to 160 Racks Per Hour



CMT 150 Rack Conveyor Dishwasher - Key Features

The CMT 150 Features:

- Heavy duty prewash (820mm long module)
- Integrated Power wash and rinse (Power wash - 950mm, final rinse - 200mm) (1150mm in total)
- Optional Heat recovery system and drying tunnel.

Proportional Rinse System

This exclusive system has a rinse booster pump to ensure constant rinse water pressure during operation. It also uniquely adjusts the water usage to match the output speed of the machine; significantly reducing the water consumption when the dishwasher is operated at intermediate speeds.

WRC Approved

Water is fed via a WRC approved circuit with a stainless steel break tank

Extremely Low Water Consumption, The CMT 150 operates from 1.1L per rack, making it one of the most efficient machines on the market.

Patented Double Flow Pumps

The Prewash and wash modules use a wash system with powerful patented double flow pumps to create a 'hydraulic brush' and 'water box' effect ensuring perfect cleaning.

Three-Stage Water Filtering System

The three-stage water filtering system ensures the best quality results and also comes with a strainer that can be removed for cleaning without opening the modules door.

Full Double Wall Construction

The CMT range all feature noise reducing and heat retaining double wall construction, plus insulated counter-balanced doors, giving full access for all internal cleaning.

- Wash temperature between 60 - 63°C and rinse temperature between 65 - 82°C (depending on wash program)
- Available in three versions – Cold Feed, cold feed with heat recovery and hot feed (>45°C).
- LED numeric screen and soft touch operation for ease of use.
- Standard USB connection to external controls and optional plug-in connection module for Bluetooth and WiFi connections.
- Four specialised wash programs for maximum flexibility. Max capacity – 160 racks/hr.

Main Features

- **Reversible Direction**

The direction of the racks' movement can be changed on site during installation with a very simple operation without requiring any special kits or tools.
- **Integrated Wash and Rinse Module**
 - 1.150 mm long, double skinned with insulated full-length counter-balanced inspection door.
 - 70 L deep drawn tank,
 - 3 stages progressive water filtering concept:
 1. drawer-like strainer in stainless steel with 1 mm mesh.
 2. integral tank strainer with 2.5 mm mesh in procomposit composite material.
 3. safety strainer on the pump intake.
 - Double flow 1.500 W wash pump (as effective as a 2000 W traditional single-flow unit), five wash arms in stainless steel with 12 specially conformed IdroWash3 nozzles each. Maximum soil removal action ensured by the "water box" and "hydraulic brush" effects. Wash temperature between 60 and 63 °C depending on the selected wash program, 10.500 W high power heating element.
- **Final Rinse**

Uses fresh external water and is located in a 200 mm long section; it includes an upper and a lower arm fed by a dedicated 17L boiler with electrical heating elements in incoloy alloy. The boiler is fed through a prorinse hydraulic circuit including a WRC approved break tank and an high power rinse booster pump to grant a consistent rinse pressure in operation.
- **Proportional Rinse System**

This exclusive system has a rinse booster pump to ensure constant rinse water pressure during operation. It also uniquely adjusts the water usage to match the output speed of the machine; significantly reducing the water consumption when the dishwasher is operated at intermediate speeds. Enormously increasing the rinse efficiency and up to 25% savings on running costs.
- **Hi-Tech Rinse Arms** in composite material with flow conformal water channel to minimize the loss in pressure and maximize efficiency. Spray nozzles are high precision units in stainless steel. Easy to fit in place.
- **Prowind Drying Area**

600 mm long operating with dry air from outside the machine. 3 upper splits originate high pressure air blades at a temperature of approximately 65°C. The air is powered by a 550 W fan with a delivery of 1.400 m³/hr and heated by a 6.000 W (optional 9.000 W) electrically operated unit. This external module is equipped with a dedicated drain circuit and is available as a factory mounted option or as an after market kit.
- **Total Clean Construction Concept**

With deep drawn tanks, internal chambers without pipes or dirt traps, fully accessible tanks due to the side rack drive rails, multiple removable strainers that keep most of the dirt out of the tanks, self cleaning wash pumps, full access underneath the machine for cleaning and adjustable feet.
- **Optional Built-in Proheat System** recovers the latent condensation heat of the steam and uses it to heat the incoming cold water for the final rinse from 15 °C to approx.. 40 °C with a significant energy saving. There are 2 alu/copper heat exchange batteries with a total surface of 50 m², easily accessible for cleaning, and the steam is moved by a 180 W fan with a delivery of 700 m³/hr. Available as factory mounted device only.
- **Energy Saving Controlled Wash AutoTimer**

Stops all the pumps and services if there are no racks to wash inside the machine. The temperatures are kept at the correct level so that the machine can be restarted at any moment by simply introducing a rack.
- **Thermostop Device**

Automatically stops the advancing of the racks until the correct temperature in the boiler is restored.
- **High Clearance Height**

Clearance enhanced up to 45 cm allowing an easy wash even of the tallest thermos insulated trays.
- **Optional ProDose Chemical System**

Pre-arrangement for the installation of chemical pumps is available the prodose system composed of detergent and rinse aid peristaltic pumps electronically controlled and fully adjustable from the control panel

- Double rail system with side sled with alternative movement. High resistance and high rigidity side rails with 30/10 AISI 304 advance teeth.
- Clog-proof drive motor installation without friction elements. Multiple motor speeds allowed.
- Advanced soft touch interface ProSmart including a wide easy to read four digits LED screen; two color changing bars to supply all-at-a-glance information about the machine status. Allows to manage any function and module of the machine, as well as to record functional data and to connect the dishwasher to external equipment and to the web. Built in USB connection, optional plug-in internal board for Bluetooth and Wi-Fi connection.

Optional emergency stop switch

IPX 5 water protection

User interface ergonomically placed at eye's level

All parameters are fully adjustable

Performance and Connections

- Up to four different selectable programs (depending on the model), different for capacity, wash temperature, wash pump power, rinse temperature, hourly rinse water consumption.
 - 1. High capacity:** for freshly, lightly soiled items
 - 2. General purpose:** suitable for most applications
 - 3. Prolonged contact:** allows a contact time of 120" (DIN spec 10534)
 - 4. Glasses:** lower rinse temperature, more delicate wash
- Water consumption is extremely limited, with a minimum of 1,1 lt/rack and a maximum of 2,2 ltrs/rack. The consumption depends on the selected program as :
 - Electrical connection 400V – 50 Hz – 3 ph + N
 - Maximum electric load with cold feed W 28.700
 - Maximum electric load with heat recovery W 24.900
 - Maximum electric load with hot feed W 22.200
 - Minimum feed water temperature 15°C
 - Minimum feed water temperature for hot feed power 45°C
 - Maximum feed water feed 60°C
 - Minimum dynamic water pressure 1.0 bar



Programs

CMT 150	Capacity	Wash temp	Rinse temp	Rinse consumpt	Rinse consumpt
	raks/hr	°c	°c	Ltrs/hr	Ltrs/rack
Speed 1	160	63	82	170	1.1
Speed 2	120	60	82	130	1.1
Speed 3 (according to DIN)	60	63	82	130	2.2

Features

Standard features	CMT 150
Modular Construction promont	●
Entry clearance 45 cm	●
Full double wall construction	●
Fully insulate double wall doors	●
Deep drawn tanks	●
Wash chambers without internal piping	●
Internal tank strainers prostrainer	●
Drawer-like additional strainer in each tank	●
Progressive water filtering progressive	●
Safety filters on pumps intake	●
Heavy duty prewash XL	●
Heavy duty wash module	●
Double flow pumps duoflow	●
Wah arms idrowash	●
Hydraulic brush cleaning system	●
Side rack rails	●
Electronic control of rack speed	●
Heavy duty dryer prowind	●
Intergrated rinse isyrinse	●
Intergrated rinse toprinse	●
Water feed via break tank according to WRAS regulation rinse pump duoflow	●
Adaptive rinse proportional	●
Rinse arm itech	●

Standard features	CMT 150
Power management	●
Propower rinse economizer	●
Time controlled wash	●
Autotimer LED interface	●
Prosmart	●
Four wash programs	●
Fully adjustable	●
Advanced self diagnostic	●
Built-in USB Connection	●


Optional features	CMT 150
Heat recovery system	●
Drying tunnel	●
Drying tunnel on 90 ° curve	●
Corner prewash	●
300mm hood on entry	●
Side detergent dispenser	●
Chemical product's level	●
Probe emergency switch	●
Main switch on board	●
End limit switch	●
USB and Wi-Fi plug in board	●

Supplies	Units	CMT 150
Water		
Inlet water pressure	bar	1,0-4,0
Inlet water hardness	°fH	7-15
Cold water temperature	°C	10-45
Hot water temperature	°C	45-60
Incoming water line size		3/4"GM
Drain line size		1.5"GM
Initial fill requirement	Lt	87

Key Information	Unit	CMT 150
Reversible on site		yes
Productivity -max-gen.Purp	r/h	160-120
Productivity -with 2' contact time	r/h	60
Productivity - glasses	r/h	80
Water consumption min	Ltrs/h	170
Noise level	db	<70

Supplies	Units	CMT 200
Electric		
Electric supply voltage		400V-50Hz-3N ph
Maximum absorbed power (coldfill set) with heat recovery	w	28.700
Maximum absorbed power (coldfill set)	w	324.900
Maximum absorbed power (hot fill set)	w	22.200
Max current absorbed (cold fill set)	A	50 (63 with optionals)
Max current absorbed (hot fill set)	A	40 (50 with optionals)

Key Information	Units	CMT 200
Dimensions	mm	
Table to table length	mm	1,615
Depth	mm	770
Height	mm	1,588
Height with open doors	mm	2,088
Adjustanle feet range	mm	195 ± 35
Charging width	mm	540
Charging clearance	mm	450
Other items included		
Racks for 18 plates	n°	1
Flat racks	n°	1
Drain hose	n°	1
Fill hose	n°	1
Electric power cable	n°	not included
End limit switch	n°	not included



Main technical features

Features	Units	CMT 200
Overall dimensions (w x d x h)	mm	1.150 x 770 x 1.615
Active lenght according to DIN spec10534	mm	1.050
With drying tunnel add to the total width	mm	600
Adjustable feet's height	mm	195 ± 35
Rack size	mm	500 x 500
Usable height	mm	450,0
Mouth width	mm	540,0
Construction material (tanks and wash chambers)		AISI 304
Construction material (outer panels)		AISI 201
Construction material (back external cover)		skin plated sheet iron
User's inteface	type	pro smart
Interface positioning		on the jamb
Rinse activator		electronic
Auto timer (Timer controlled wash)		electronic
Thermostop (electronic)		electronic
USB slot		on the board
Main wash module - length	cm	115
Main wash module - construction		double skin
Main wash module - door		double skin and insulated
Main wash module - tank volume	Ltrs	70
Main wash module - tank;s heating element	w	10.500
Main wash module - tank strainers		standard - stainless steel
Main wash module - drawer - like strainer		standard - stainless steel
Main wash module - drawer - like strainer sieve		3.0
Main wash module - wash pump 's type		double flow
Main wash module - wash pump's power	w	1,500
Main wash module - wash pump's delivery	Ltrs/min	720
Main wash module - wash arms n"/type		3 (2 sup - 1 inf)
Toatl number of wash nozzels		36
Main wash module - rinse		single rinse
Main wash module - rinse flow variation system		yes
Main wash module - bolier's type		pressurized by the pump
Main wash module - break tank	Ltrs	yes
Main wash module - boiler's volume	Ltrs	17,0
Main wash module - rinse booster pump		yes
Main wash module - rinse booster pump power	w	200
Main wash module - rinse booster pump flow rate	Ltrs/min	110
Main wash module - wash pump's type		double flow
Main wash module - wash pump's power	w	1,500
Main wash module - wash pump's delivery	Ltrsmin	720
Minimum external pressure	bar	1.0
Main wash module - boiler's heating element (c.w)	w	16.000
Main wash module - boiler's heating element (c.w. + hr)	w	12.000
Main wash module - boiler's heating element (hr)	w	9.500

Features	Units	CMT 200
Main wash module - rinse arms	n°/type	2 - composite/inox nozzles
Main wash module - heat recovery system		optional
Main wash module - heat recovery system - n° of batteries		2 - alu/copper
Main wash module - heat recovery system - total exchange surface	M2	50
Main wash module - heat recovery system - fan power	kW	180
Main wash module - heat recovery system - air delivery	m3/hr	700
Main wash module - temperature recovery from 15°C	°c	25
Drying module	cm	optional
Drying module - total length	cm	60
Drying module - dripping area	cm	no
Drying module - construction		double skin
Drying module - door		no
Drying module - drain circuit		yes
Drying module - fan power	w	550
Drying module - fan delivery	m3/hr	1,400
Drying module - heating element	w	6,000
Drying module - temperature of blowed air	°c	65
Drying module - lower air flow diversion winglets		no
Drying module - n° of upper ai blowing ducts	°c	2

Classeq Ltd,
Classeq House, Roebuck Way,
Knowlhill, Milton Keynes
Buckinghamshire MK5 8WH
United Kingdom

Tel: +44 (0)844 225 9250
Email: sales@classeq.co.uk

www.classeq.co.uk

CLASSEQ
Warewashing Made Simple.