

May 2012



## L20 SAMPLE SPECIFICATION EXTERNAL NONE FIRE RATED DOORSET

### Components

#### INTERNAL NONE FIRE RATED TIMBER DOORSETS:

Product reference: Series K

Manufacturer: Noberne Doors Ltd, Lupton Street, Hunslet, Leeds LS10 2QP

telephone: 0113 277 8577, email: sales@nobernedoors.co.uk

#### Door leaf:

Core: Solid 540kg/m<sup>3</sup> timber thermal core

Door Thickness: 56mm thick

U-value: Capable of 1.27w/m<sup>2</sup>k

Facing: External quality ply

Lipping: Visible 10mm hardwood lipping to all edges

Glazing details:

Finish as delivered: Factory finished one coat primer to all surfaces

#### Frame:

Wood species: Hardwood 94x57fs one piece rebated

Class (to BS EN 942): J40 and J50

Finish as delivered: Primed for site painting

Preservative treatment: N/A

Moisture content on delivery: 13 to 19%

#### Architrave:

Wood Species: (MDF/hardwood to one side)

Class (to BS EN 942): J40 and J50

Preservative treatment: N/A

Moisture content on delivery: 9 to 13%

#### Ironmongery:

Door hung in frame on Noberne BZP butt 3 per door leaf

#### Perimeter seals:

Budget weatherseal to frame, drip to frame head, weatherboard to door

#### Other requirements:

Fixing: In strict accordance with manufacturers instructions and BS8214 2008

Note: All doors to be labelled with manufacturers metal foil labels

Please amend (items) as required. We would be happy to review or discuss your specification requirements. Telephone 0113 2778577 or Email sales@nobernedoors.co.uk