

Uniclass
L7826
March 2010



## ANPR Bollard Camera

**Bollard ANPR Camera, 3-20m range (ANPRB20)**



### ANPR Features

Suitable for Car Parks, Hospitals, Surgeries, Ports, Schools, Garages, Hotels

Log Vehicles with multiple images

Alert Staff to vehicles of interest

Provide Car Park access control

Control unauthorised commuter parking

Increase gatehouse efficiency

Opens barriers / gates

Car Park auditing, ticketing and management

Allow sophisticated database management

Communicate with remote sites over LAN/WAN/3G

There are many situations where a standard camera is just not suitable and therefore developed these floor standing bollard cameras for just these applications. When vehicles need to be identified at a vehicle barrier or gate, the camera needs to be at low-level and on the unsecure side of the barrier in order to get a clear view of the license plate.

These bollards are made of heavy-gauge steel and now come with a 3 year anti-corrosion guarantee. They feature a Lexan window and a full height lockable rear door which provide internal access. There are no external fixings which results in a tamper-proof assembly.

An internal base clamp allows the bollard to be rotated before being securely locked in position. We recommend that a substantial concrete base is used and, where necessary, that steel or concrete bollards are used to protect the camera from wayward vehicles.

Range	3-20 metres
Power pulse IR LED illuminator	Yes
Min operating light level	0 lux
Shutter speed	1/1000th sec
Resolution (TV Lines)	530
Quickset keypad	Yes
RS485 remote telemetry local/remote select switch	Yes
Video opto-isolator (anpr)	Yes
Supply voltage	24v ac (230v)
Power consumption	20w
Camera dimensions (HxWxD)	101x101x101
Junction box dimensions mm	910x220x220
Weight	24kg (25Kg)
IP rating	IP65

